EW 3-28-2013

2-20-2013 FB

State of Utah

GARY R. HERBERT
Governor

GREG BELL
Lieutenant Governor

Department of
Environmental Quality
Amanda Smith
Executive Director

DIVISION OF WATER QUALITY
Walter L. Baker, P.E.
Director

FILE COPY

FEB 2 0 2013

CERTIFIED MAIL
(Return Receipt requested)

Brian Harris
Price River Water Improvement District
P.O. Box 903
Price, Utah 84501

Dear Mr. Harris:

Subject: Renewal Permit Issuance for UPDES Permit No. UT0021814, Price River Water Improvement District

Enclosed is a signed copy of the Utah Pollutant Discharge Elimination System (UPDES) Renewal Permit No. UT0021814 for the above referenced facility. The conditions and requirements of the renewal permit are effective as of March 1, 2013 as scheduled, subject to the right to challenge this decision in accordance with the provisions of *Utah Administrative Code*, Section R317-9.

Discharge Monitoring Reports (DMR) forms (EPA form 3320-1) for reporting and self-monitoring requirements as specified in the permit are available upon request, however EPA's NetDMR process for on line DMR submittal is now available and required. As a reminder, DMR forms are due to be completed on-line or in our office by the 28th of each month following each monthly monitoring period. To sign up for NetDMR, please visit our website at http://www.waterquality.utah.gov/UPDES/NetDMR.htm.

A fee schedule was included in the Utah Department of Environmental Quality Budget appropriation request at the direction of the Legislature and in accordance with *Utah Code Annotated* 19-1-201. The fee schedule, as approved by the Legislature, includes a prescribed fee for specific categories. The prescribed fee for a UPDES Individual Major Permit, Small Publically Owned Treatment Works category is $1,000.00 annually. An invoice will be prepared and mailed to you in the near future.

The Utah Division of Water Quality (DWQ) values your feedback, and as the State agency charged with the administration of issuing UPDES permits, we are continuously looking for ways

to improve our quality of service to you. DWQ Director Walter L. Baker is committed to continually assessing and improving the level and quality of services provided to you.

In an effort to improve the State UPDES permitting process, we are asking for your input. Please take a few minutes to comment on the quality of service you received by completing the "Give Feedback to DWQ" form link on DWQ's webpage at www.waterquality.utah.gov. Thank you for assisting us in improving our service to you.

If you have any questions with regards to this matter, please contact Kim Shelley of this office at (801) 536-4385 or by e-mail at kshelley@utah.gov.

Sincerely,

John Kennington, P.E., Manager
UPDES ENGINEERING Section

JK/KS/fb

Enclosure

cc: Amy Clark, EPA Region VIII (w/encl)
Brady Bradford, Southeastern Utah District Health Department
Dave Ariotti, DEQ District Engineer
Randy Sargent, Utah DWQ

DWQ-2013-001512.doc

STATE OF UTAH
DIVISION OF WATER QUALITY
DEPARTMENT OF ENVIRONMENTAL QUALITY
SALT LAKE CITY, UTAH

UTAH POLLUTANT DISCHARGE ELIMINATION SYSTEM (UPDES) PERMITS

Major Municipal Permit No. **UT0021814**
Biosolids Permit No. **UTL0021814**
Storm Water Permit No. **UTR000000**

In compliance with provisions of the Utah *Water Quality Act, Title 19, Chapter 5, Utah Code Annotated ("UCA") 1953, as amended* (the *"Act"*),

PRICE RIVER WATER IMPROVEMENT DISTRICT

is hereby authorized to discharge from its wastewater treatment facility to receiving waters named **Price River**,

to dispose of biosolids,

and to discharge storm water,

in accordance with specific limitations, outfalls, and other conditions set forth herein.

This permit shall become effective on March 1, 2013.

This permit expires at midnight on February 28, 2018.

Signed this 14th day of February, 2013.

Walter L. Baker, P.E.
Director
Utah Division of Water Quality

Table of Contents

Outline — Page Number

I. DISCHARGE LIMITATIONS AND REPORTING REQUIREMENTS 1
A. Description of Discharge Point 1
B. Narrative Standard 1
C. Specific Limitations and Self-Monitoring Requirements 1
D. Reporting of Wastewater Monitoring Results 7
II. INDUSTRIAL PRETREATMENT PROGRAM 8
A. Pretreatment Reporting Requirements 8
B. Self-Monitoring and Reporting Requirements 8
C. Industrial Wastes. 8
III. BIOSOLIDS REQUIREMENTS 8
A. Biosolids Treatment and Disposal 11
B. Specific Limitations and Monitoring Requirements 11
C. Site Restrictions 14
D. Management Practices for Application of Biosolids to Land 15
E. Special Conditions on Biosolids Storage 17
F. Representative Sampling 17
G. Reporting of Monitoring Results 17
G. Additional Record Keeping Requirements Specific to Biosolids 18
IV. STORM WATER REQUIREMENTS 20
A. Coverage of This Section 20
B. Prohibition of Non-Storm Water Discharges 20
C. Storm Water Pollution Prevention Plan Requirements 20
D. Monitoring and Reporting Requirements 26
V. MONITORING, RECORDING & GENERAL REPORTING REQUIREMENTS 28
A. Representative Sampling 28
B. Monitoring Procedures 28
C. Penalties for Tampering 28
D. Compliance Schedules 28
E. Additional Monitoring by the Permittee 28
F. Records Contents 28
G. Retention of Records 28
H. Twenty-four Hour Notice of Noncompliance Reporting 29
I. Other Noncompliance Reporting 30
J. Inspection and Entry 30
VI. COMPLIANCE RESPONSIBILITIES 31
A. Duty to Comply 31
B. Penalties for Violations of Permit Conditions 31
C. Need to Halt or Reduce Activity not a Defense 31
D. Duty to Mitigate 31
E. Proper Operation and Maintenance 31
F. Removed Substances 31
G. Bypass of Treatment Facilities 32
H. Upset Conditions 33
VII. GENERAL REQUIREMENTS 35
A. Planned Changes 35
B. Anticipated Noncompliance 35
C. Permit Actions 35
D. Duty to Reapply 35
E. Duty to Provide Information 35
F. Other Information 35

G. Signatory Requirements 35
H. Penalties for Falsification of Reports 36
I. Availability of Reports 37
J. Oil and Hazardous Substance Liability 37
K. Property Rights 37
L. Severability 37
M. Transfers 37
N. State or Federal Laws 37
O. Water Quality - Reopener Provision 38
P. Biosolids – Reopener Provision 38
Q. Toxicity Limitation - Reopener Provision 38
R. Storm Water-Reopener Provision 39
VIII. DEFINITIONS 40
A. Wastewater 40
B. Biosolids 42
C. Storm Water 44

I. DISCHARGE LIMITATIONS AND REPORTING REQUIREMENTS

A. Description of Discharge Point. The authorization to discharge wastewater provided under this part is limited to those outfalls specifically designated below as discharge locations. Discharges at any location not authorized under a UPDES permit are violations of the *Act* and may be subject to penalties under the *Act*. Knowingly discharging from an unauthorized location or failing to report an unauthorized discharge may be subject to criminal penalties as provided under the *Act*.

Outfall Number	Location of Discharge Outfall
001	Located at latitude 39° 32' 21" and longitude 110° 42' 44" the discharge is through a 60" pipe on the east side of the facility discharging into the Price River. It is approximately 1 ½ miles southwest of Wellington, on the west side of the Price River and the Denver and Rio Grande Western Railroad tracks, at 5382 Washer\Plant Road, Wellington, Carbon County, Utah.

B. Narrative Standard. It shall be unlawful, and a violation of this permit, for the permittee to discharge or place any waste or other substance in such a way as will be or may become offensive such as unnatural deposits, floating debris, oil, scum, or other nuisances such as color, odor or taste, or cause conditions which produce undesirable aquatic life or which produce objectionable tastes in edible aquatic organisms; or result in concentrations or combinations of substances which produce undesirable physiological responses in desirable resident fish, or other desirable aquatic life, or undesirable human health effects, as determined by a bioassay or other tests performed in accordance with standard procedures.

C. Specific Limitations and Self-Monitoring Requirements.

1. Effective immediately, and lasting through the life of this permit, there shall be no acute toxicity in Outfall 001 as defined in *Part VIII*, and determined by test procedures described in *Part I. C.3* of this permit.

2. Effective immediately and lasting the duration of this permit, the permittee is authorized to discharge from Outfall 001. Such discharges shall be limited and monitored by the permittee as specified below:

Effluent Limitations					
Parameter	Maximum Monthly Avg	Maximum Weekly Avg	Daily Minimum	Daily Maximum	Yearly Maximum
Flow, MGD	2.2	NA	NA	3.0	NA
BOD_5, mg/L	25	35	NA	NA	NA
BOD_5 Min. % Removal	85	NA	NA	NA	NA

Effluent Limitations					
Parameter	Maximum Monthly Avg	Maximum Weekly Avg	Daily Minimum	Daily Maximum	Yearly Maximum
TSS, mg/L TSS Min. % Removal	25 85	35 NA	NA NA	NA NA	NA NA
E-Coli, No./100mL	126	157	NA	NA	NA
Ammonia, mg/L	10	NA	NA	16	NA
TRC, mg/L	0.056	NA	NA	0.076	NA
Oil & Grease, mg/L	NA	NA	NA	10	NA
Dissolved Oxygen, mg/L	NA	NA	5.0	NA	NA
pH, Standard Units	NA	NA	6.5	9.0	NA
TDS, mg/L	NA	NA	NA	1700	NA
TDS, (annual) tons[b]	NA	NA	NA	NA	7304
WET, Acute Biomonitoring	NA	NA	NA	NA	Pass at 100% Effluent

NA – Not Applicable

Self-Monitoring and Reporting Requirements[a]			
Parameter	Frequency	Sample Type	Units
Total Flow[c,d]	Continuous	Recorder	MGD
BOD_5, Influent[e] Effluent	2 x Weekly 2 x Weekly	Composite Composite	mg/L mg/L
TSS, Influent[e] Effluent	2 x Weekly 2 x Weekly	Composite Composite	mg/L mg/L
E-coli	2 x Weekly	Grab	No./100mL
Ammonia	2 x Weekly	Grab	mg/L
TRC	Daily	Grab	mg/L
WET, Acute Biomonitoring[f]	2 x Year	Composite	Pass/Fail
Oil & Grease	2 x Weekly	Visible	Yes/No
Oil & Grease[g]	Monthly	Grab	mg/L
Dissolved Oxygen	2 x Weekly	Grab	mg/L
pH	2 x Weekly	Grab	su
TDS	Monthly	Grab	mg/L
Metals[e, i], Influent Effluent	Yearly Yearly	Composite[h] Composite[h]	mg/L mg/L
Organic Toxics[j]	2nd & 4th year of permit	Grab	mg/L
Phosphorus	Quarterly	Grab	mg/L
CBOD	Quarterly	Grab	mg/L
Nitrate	Quarterly	Grab	mg/L
Nitrite	Quarterly	Grab	mg/L

a See Definitions, *Part VIII*, for definition of terms within the effluent limitations tables and the self-monitoring and reporting requirements tables.

b The measurement of TDS tons will be total accumulated during the calendar year. Beginning in January 1, of each year the total TDS tons will start at zero again.

c Flow measurements of influent/effluent volume shall be made in such a manner that the permittee can affirmatively demonstrate that representative values are being obtained.

d If the rate of discharge is controlled, the duration of that rate shall be reported also.

e For this constituent, in addition to monitoring the final discharge, influent samples shall be taken and analyzed at the same frequency as required in the discharge.

f Wet monitoring will be acute according to *Methods for Measuring the Acute Toxicity of Effluents and Receiving Waters to Freshwater and Marine Organisms. Fifth Edition. October 2002, EPA/821/R/02/012* as per *40 CFR 136.3(a) TABLE 1A-LIST OF APPROVED BIOLOGICAL METHODS.* The permittee shall use Ceriodaphnia dubia the first 6 months and Pimephales promelas (fathead minnow) the next 6 month period. Each year the permittee will change the order the species so that the species are not tested in the same half of the year each year.

g Monitoring and reporting the results of a laboratory analyzed sample for oil & grease is not required unless the visual sample produces a positive result.

h Samples of mercury can be taken as composite or grab.

i Metals samples shall conform to the requirements in the table titled "Metals Monitoring for Pretreatment Program" found in Part II.A.1.

j A total toxic organics (TTO) test shall be performed sometime during the 2nd and 4th year of the permit.

3. Acute Whole Effluent Toxicity (WET) Testing.

a. *Whole Effluent Testing – Acute Toxicity*. Starting on the effective date of this permit, the permittee shall twice yearly conduct acute static replacement toxicity tests on a composite sample of the final effluent. The sample shall be collected at outfall 001.

The monitoring frequency for acute tests shall be every 6 months unless a sample is found to be acutely toxic during a routine test. If that occurs, the monitoring frequency shall become weekly (See *Part I.C.3, Accelerated Testing*). Samples shall be collected on a two day progression; i.e., if the first sample is on a Monday, during the next sampling period, the sampling shall begin on a Wednesday, etc.

The replacement static acute toxicity tests shall be conducted in general accordance with the procedures set out in the latest revision of *Methods for Measuring the Acute Toxicity of Effluents and Receiving Waters to Freshwater and Marine Organisms. Fifth Edition. October 2002, EPA/821/R/02/012 as per 40 CFR 136.3(a) TABLE 1A-LIST OF APPROVED BIOLOGICAL METHODS.* The permittee shall conduct the 48-hour static replacement toxicity test using Ceriodaphnia dubia and the acute 96-hour static replacement toxicity test using Pimephales promelas (fathead minnow). A CO_2 atmosphere may be used (in conjunction with an unmodified test) in order to account for artificial pH drift, as previously demonstrated to and authorized by the Director.

Acute toxicity occurs when 50 percent or more mortality is observed for either species at any effluent concentration (lethal concentration or LC_{50}). Mortality in the control must simultaneously be 10 percent or less for the results to be considered valid. If more than 10 percent control mortality occurs, the test shall be repeated until satisfactory control mortality is achieved.

If the permit contains a total residual chlorine limitation greater than 0.20 mg/L, the permittee may request from the Director approval to de-chlorinate the sample, or collect the sample prior to chlorination.

Semi-annual test results shall be reported along with the Discharge Monitoring Report (DMR) submitted for the end of the reporting calendar quarter e.g., biomonitoring results for the calendar quarter ending March 31 shall be reported with the DMR due April 28, with the remaining biomonitoring reports submitted with DMRs due each July 28, October 28, and January 28). All test results shall be reported along with the DMR submitted for that reporting period. The format for the report shall be consistent with the latest revision of the *Region VIII Guidance for Acute Whole Effluent Reporting (August, 1997)* and shall include all chemical and physical data as specified.

If the results for a minimum of ten consecutive tests indicate no acute toxicity, the permittee may request a reduction in testing frequency and/or reduction to one species. The Director may approve, partially approve, or deny the request based on results and other available information. If approval is given, the modification will take place without a public notice.

b. *Accelerated Testing.* When acute toxicity is indicated during routine biomonitoring as specified in this permit, the permittee shall notify the Director in writing within five (5) days after becoming aware of the test result. The permittee shall perform an accelerated schedule of biomonitoring to establish whether a pattern of toxicity exists. Accelerated testing will begin within seven (7) days after the permittee becomes aware of the test result. Accelerated testing shall be conducted as specified under *Part I.C.4, Pattern of Toxicity*. If the accelerated testing demonstrates no pattern of toxicity, routine monitoring shall be resumed.

c. *Pattern of Toxicity.* A pattern of toxicity is defined by the results of a series of up to five (5) biomonitoring tests pursuant to the accelerated testing requirements using 100 percent effluent on the single species found to be more sensitive, once every week for up to five (5) consecutive weeks.

If two (2) consecutive tests (not including the scheduled quarterly or monthly test which triggered the search for a pattern of toxicity) do not result in acute toxicity, no further accelerated testing will be required and no pattern of toxicity will be found to exist. The permittee will provide written verification to the Director within five (5) days, and resume routine monitoring.

A pattern of toxicity is established if one of the following occurs:

(1) If two (2) consecutive test results (not including the scheduled quarterly or monthly test, which triggered the search for a pattern of toxicity) indicate acute toxicity, this constitutes an established pattern of toxicity.

(2) If consecutive tests continue to yield differing results each time, the permittee will be required to conduct up to a maximum of five (5) acute tests (not including the scheduled quarterly or monthly test which triggered the search for a pattern of toxicity). If three out of five test results indicate acute toxicity, this will constitute an established pattern of toxicity.

d. *Preliminary Toxicity Investigation.*

(1) When a pattern of toxicity is detected the permittee will notify the Director in writing within five (5) days and begin an evaluation of the possible causes of the toxicity. The permittee will have fifteen (15) working days from demonstration of the pattern to complete a Preliminary Toxicity Investigation (PTI) and submit a written report of the results to the Director. The PTI may include, but is not limited to, additional chemical and biological monitoring, examination of pretreatment program records, examination of discharge monitoring reports, a thorough review of the testing protocol, evaluation of treatment processes and chemical use, inspection of material storage and transfer areas to determine if a spill may have occurred, and similar procedures.

(2) If the PTI identifies a probable toxicant and/or a probable source of toxicity the permittee shall submit, as part of its final results written notification of that effect to the Director. Within thirty (30) days of completing the PTI the permittee shall submit for approval a control program to control effluent toxicity and shall proceed to implement such a plan within seven (7) days following approval. The control program, as submitted to or revised by the Director, may be incorporated into the permit.

(3) If no probable explanation for toxicity is identified in the PTI, the permittee shall notify the Director as part of its final report, along with a schedule for conducting a Phase I Toxicity Reduction Evaluation (TRE) (See *Part I.C.4, Toxicity Reduction Evaluation*).

(4) If toxicity spontaneously disappears during the PTI, the permittee shall submit written notification to that effect to the Director as part of the reporting requirements of paragraph a of this section.

e. *Toxicity Reduction Evaluation (TRE).* If toxicity is detected during the life of this permit and it is determined by the Director that a TRE is necessary, the permittee shall be so notified and shall initiate a TRE immediately thereafter. The purpose of the TRE will be to establish the cause of toxicity, locate the source(s) of the toxicity, and control or provide treatment for the toxicity.

A TRE may include but is not limited to one, all, or a combination of the following:

(1) Phase I – Toxicity Characterization

(2) Phase II – Toxicity Identification Procedures

(3) Phase III – Toxicity Control Procedures

(4) Any other appropriate procedures for toxicity source elimination and control.

If the TRE establishes that the toxicity cannot be immediately eliminated, the permittee shall submit a proposed compliance plan to the Director. The plan shall include the proposed approach to control toxicity and a proposed compliance schedule for achieving control. If the approach and schedule are acceptable to the Director, this permit may be reopened and modified.

If the TRE shows that the toxicity is caused by a toxicant(s) that may be controlled with specific numerical limitations, the permittee may:

(a) Submit an alternative control program for compliance with the numerical requirements.

(b) If necessary, provide a modified biomonitoring protocol, which compensates for the pollutant(s) being controlled numerically.

If acceptable to the Director, this permit may be reopened and modified to incorporate any additional numerical limitations, a modified compliance schedule if judged necessary by the Director, and/or a modified biomonitoring protocol.

Failure to conduct an adequate TRE, or failure to submit a plan or program as described above, or the submittal of a plan or program judged inadequate by the Director, shall be considered a violation of this permit.

D. Reporting of Wastewater Monitoring Results. Monitoring results obtained during the previous month shall be summarized for each month and reported on a Discharge Monitoring Report Form (EPA No. 3320-1) or by NetDMR, post-marked or entered into NetDMR no later than the 28th day of the month following the completed reporting period. The first report is due on April 28, 2013. If no discharge occurs during the reporting period, "no discharge" shall be reported. Legible copies of these, and all other reports including whole effluent toxicity (WET) test reports required herein, shall be signed and certified in accordance with the requirements of *Signatory Requirements (see Part VII.G)*, and submitted by NetDMR, or to the Division of Water Quality at the following address:

Department of Environmental Quality
Division of Water Quality
PO Box 144870
Salt Lake City, Utah 84114-4870

II. INDUSTRIAL PRETREATMENT PROGRAM

A. Self-Monitoring and Reporting Requirements.

1. Because the design capacity of this municipal wastewater treatment facility is less than 5 MGD, the permittee will not be required to develop a State-approved industrial pretreatment program at this time. However, in order to determine if development of an industrial pretreatment program is warranted, the permittee shall conduct an **industrial waste survey**, as described in *Part II.B.1*, and submit it to the Division of Water Quality within **sixty (60) calendar days** of the effective date of this permit and shall sample and analyze both the influent and effluent annually, for the following parameters.

Metals Monitoring for Pretreatment Program			
Parameter	Sample Type	Frequency	Units
Total Arsenic	Composite	Yearly	mg/L
Total Cadmium			
Total Chromium			
Total Copper			
Total Cyanide			
Total Lead			
Total Mercury	Composite/Grab		
Total Molybdenum	Composite		
Total Nickel			
Total Selenium			
Total Silver			
Total Zinc			

The results of these analyses shall be submitted along with the Discharge Monitoring Report (DMR) at the end of that reporting period.

B. Industrial Wastes.

1. The "Industrial Waste Survey" as required by *Part II.A.1.* consists of; identifying each significant industrial user (SIU), determination of the qualitative and quantitative characteristics of each discharge, and appropriate production data. A (SIU) is defined as an industrial user discharging to a publicly-owned treatment works (POTW) that satisfies any of the following: (1) has a process wastewater flow of 25,000 gallons or more per average work day; (2) has a flow greater than five percent of the flow carried by the municipal system receiving the waste; (3) is subject to Categorical Pretreatment Standards, or (4) has a reasonable potential for adversely affecting the POTW's operation or for violating any pretreatment standard or requirement.

2. The permittee must notify the Director of any new introductions by new or existing SIUs or any substantial change in pollutants from any major industrial source. Such notice must contain the information described in 1. above and be forwarded no later than sixty (60) days following the introduction or change.

3. Pretreatment Standards (*40 CFR 403.5*) developed pursuant to *Section 307* of *The Water Quality Act of 1987* require that under no circumstances shall the permittee allow introduction of the following pollutants into the waste treatment system from any source of non-domestic discharge:

   a. Pollutants which create a fire or explosion hazard in the publicly owned treatment works (POTW), including, but not limited to, wastestreams with a closed cup flashpoint of less than 140°F (60°C);

   b. Pollutants, which will cause corrosive structural damage to the POTW, but in no case, discharges with a pH lower than 5.0;

   c. Solid or viscous pollutants in amounts which will cause obstruction to the flow in the POTW resulting in interference;

   d. Any pollutant, including oxygen demanding pollutants (BOD, etc.) released in a discharge at such volume or strength as to cause interference in the POTW;

   e. Heat in amounts, which will inhibit biological activity in the POTW, resulting in interference, but in no case, heat in such quantities that the influent to the sewage treatment works exceeds 104°F (40°C);

   f. Petroleum oil, nonbiodegradable cutting oil, or products of mineral oil origin in amounts that will cause interference or pass through;

   g. Pollutants which result in the presence of toxic gases, vapor, or fumes within the POTW in a quantity that may cause worker health or safety problems; or,

   h. Any trucked or hauled pollutants, except at discharge points designated by the POTW.

   i. Any pollutant that causes pass through or interference at the POTW.

4. In addition to the general and specific limitations expressed above, more specific pretreatment limitations have been and will be promulgated for specific industrial categories under *Section 307* of *the Water Quality Act of 1987 as amended (WQA). (See 40 CFR, Subchapter N, Parts 400* through *500*, for specific information).

5. The permittee shall provide adequate notice to the Director and the Division of Water Quality Industrial Pretreatment Coordinator of;

   a. Any new introduction of pollutants into the treatment works from an indirect discharger (i.e., industrial user) which would be subject to *Sections 301* or *306* of the *WQA* if it were directly discharging those pollutants;

b. Any substantial change in the volume or character of pollutants being introduced into the treatment works by a source introducing pollutants into the treatment works at the time of issuance of the permit; and

c. For the purposes of this section, adequate notice shall include information on:

(1) The quality and quantity of effluent to be introduced into such treatment works; and,

(2) Any anticipated impact of the change on the quantity or quality of effluent to be discharged from such publicly owned treatment works.

6. At such time as a specific pretreatment limitation becomes applicable to an industrial user of the permittee, the Director may, as appropriate, do the following:

a. Amend the permittee's UPDES discharge permit to specify the additional pollutant(s) and corresponding effluent limitation(s) consistent with the applicable national pretreatment limitation;

b. Require the permittee to specify, by ordinance, contract, or other enforceable means, the type of pollutant(s) and the maximum amount which may be discharged to the permittee's facility for treatment. Such requirement shall be imposed in a manner consistent with the POTW program development requirements of the *General Pretreatment Regulations* at *40 CFR 403*; and/or,

c. Require the permittee to monitor its discharge for any pollutant, which may likely be discharged from the permittee's facility, should the industrial user fail to properly pretreat its waste.

7. The Director retains, at all times, the right to take legal action against the industrial user and/or the treatment works, in those cases where a permit violation has occurred because of the failure of an industrial user to discharge at an acceptable level. If the permittee has failed to properly delineate maximum acceptable industrial contributor levels, the Director will look primarily to the permittee as the responsible party.

8. If local limits are developed per R317-8-8.5(4)(b) to protect the POTW from pass-through or interference, then the POTW must submit limits to DWQ for review and public notice R317-8-8.5(4)(c).

III. BIOSOLIDS REQUIREMENTS

A. Biosolids Treatment and Disposal. The authorization to dispose of biosolids provided under this permit is limited to those biosolids produced from the treatment works owned and operated by the PRWID. The treatment methods and disposal practices are specifically designated below.

1. Anaerobic Treatment. Biosolids produced at the PRWID are stabilized in the anaerobic digesters for at least 15 days at a temperature of at least 35° C (95° F) to meet Class B standards.

2. Description of Biosolids Disposal Method.

   a) Class B biosolids may be land applied for agriculture use.

   b) Biosolids that do not meet at least Class B requirements are land filled.

Changes in Treatment Systems and Disposal Practices. Should the permittee change their disposal methods or the biosolids generation and handling processes of the plant, the permittee must notify the Director at least 180 days in advance. This includes, but is not limited to, the addition or removal of any biosolids treatment units (i.e., digesters, drying beds, belt presses, etc.) and/or any other change, which would require a major modification of the permit.

For any biosolids that are land filled, the requirements of *Utah Administrative Code R315-301-5* and *Section 2.12* of the latest version of the *EPA Region VIII Biosolids Management Handbook* must be followed.

B. Specific Limitations and Monitoring Requirements.

All biosolids generated by this facility that are to be sold or given away that are to land applied shall meet the requirements of *Part III.B.1, 2,and 3* listed below.

1. Heavy Metals Limitations:

   Class A
   For the biosolids to be considered Class A with respect to heavy metals, the biosolids must meet the heavy metals limitations in Table 3 as described below for record keeping purposes. For the biosolids to be considered Class B with respect to heavy metals, the biosolids must meet Tables 1 or 2 below. If the biosolids do not meet one of the Tables below, the biosolids do meet Class A or B standards, and must be disposed in a landfill.

Heavy Metals	Table 1	Table 2	Table 3 (Considered Exceptional Quality)
All heavy metals concentrations shall be measured and reported	Daily Maximum mg/Kg a/b/c/	Cumulative Loading Rate Kg/Ha a/	Monthly Average Concentration mg/Kg a/b/c/d/
Total Arsenic	75	41	41
Total Cadmium	85	39	39
Total Copper	4300	1500	1500
Total Lead	840	300	300
Total Mercury	57	17	17
Total Molybdenum	75	N/A	N/A
Total Nickel	420	420	420
Total Selenium	100	100	100
Total Zinc	7500	2800	2800

a/ See Part VIII. of the permit for definition of terms.

b/ The limitations represent the maximum allowable levels of heavy metals in any biosolids intended for land application.

c/ Any violation of these limitations shall be reported in accordance with the requirements of *Part III .H., 1, 2, 3 and 4* of the permit.

d/ These limitations represent the maximum allowable levels of heavy metals based on an average of all samples taken during a 30-day period.

2. Pathogen Limitations:

Class B

If the biosolids are to be land applied the biosolids shall meet Class B pathogen requirements (including the site restrictions and management practices) as described below. If the biosolids do not meet the Class B pathogen requirements, the biosolids cannot be land applied.

Class B Pathogen Requirements a/

Fecal Coliform shall be less than 2,000,000 most probable number per gram of total solids. b/	OR	The process to significantly reduce pathogens will be accomplished through anaerobic digesters that have a minimum retention time of at least 15 days and a temperature of a least 95°F (35°C)

3. Vector Attraction Reduction Requirements a/

Anaerobic Biosolids

Vector attraction reduction will be met by a 38% reduction in volatile solids through anaerobic digesters for at least 15 days at a temperature of at least 95°F (35°C)).

a/ There are additional pathogen reduction and vector attraction reduction alternatives available in *40 CFR 503.32* and *40 CFR 503.33.* If the permittee intends to use one of these alternatives the Director and the EPA must be informed at least 30 days prior to its use. This change may be made without additional public notice.

b/ Based on a minimum of seven (7) samples of biosolids collected over a two-week period (or as approved by the Director in your sampling and analysis plan).

4. Self-Monitoring Requirements

a. At a minimum, upon the effective date of this permit, all metals, pathogens and applicable vector attraction reduction requirements shall be monitored according to *40 CFR 503.16.*

Minimum Frequency of Monitoring (Dry Metric Tons (DMT))	
Amount of Biosolids Disposed Per Year	Monitoring Frequency
> 0 to < 290 DMT	Once per year
> 290 to < 1,500 DMT	Four times per year

b. Deep soil monitoring for nitrate-nitrogen is required for all land application sites. (Does not apply to sites where biosolids are applied less than once every five years). A minimum of six sample sites for each 320-acre area (or less) is to be collected. These samples are to be collected at a depth of 5 feet or to the confining layer whichever is shallower. Each one-

foot increment is to be a composite with the other samples from the site and one analysis for nitrate is to be done for each increment. Samples are required to be taken once every five years for non-irrigated sites or annually for irrigated sites.

c. Soil monitoring for phosphorus (reported as P) is required for all land application sites (does not apply to sites where biosolids are applied less than once every five years). Six samples of a one-foot depth each are to be collected for each 320-acre area and composited. Samples are required to be taken once every five years for non-irrigated sites or annually for irrigated sites.

d. Sample collection, preservation and analysis shall be performed in a manner consistent with the requirements of *40 CFR Part 503* and/or other criteria specified in this permit. Metals analysis is to be performed using *Method SW 846* with *Method 3050* used for digestion. For the digestion procedure, an amount of biosolids equivalent to one-gram dry weight shall be used. The methods are also described in the latest version of the *Region VIII Biosolids Management Handbook.* Monitoring for soil nitrate and phosphorus is to be performed using the methods in *Methods of Soil Analysis, Part 2. Chemical and Microbiological Properties*. Page, A. L., Ed., American Society of Agronomy and Soil Science Society of America, Madison, WI, 1982.

e. The Director may request additional monitoring for specific pollutants derived from biosolids if the data shows a potential for concern.

C. Site Restrictions

If the biosolids are Class B with respect to pathogens, the PRWID shall comply with all applicable site restrictions listed below:

1. Food crops with harvested parts that touch the biosolids/soil mixture and are totally above the land surface shall not be harvested for 14 months after application.

2. Food crops with harvested parts below the land surface shall not be harvested for 20 months after application if the biosolids remains on the land surface for four months or more prior to incorporation into the soil.

3. Other food crops and feed crops shall not be harvested from the land for 30 days after application.

4. Animals shall not be allowed to graze on the land for 30 days after application.

5. Turf grown on land where biosolids is applied shall not be harvested for one year after application if the harvested turf is placed on either land with a high potential for public exposure or a lawn.

6. Public access to land with a high potential for public exposure shall be restricted for one year after application.

D. Management Practices for Application of Biosolids to Land

The permittee shall operate and maintain the land application site operations in accordance with the following requirements:

1. The permittee shall provide to the Director and the EPA within 90 days of the effective date of this permit a land application plan if requested by the permitting authority.

2. Application of biosolids shall be conducted in a manner that will not contaminate the groundwater or impair the use classification for that water underlying the sites.

3. Application of biosolids shall be conducted in a manner that will not cause a violation of any receiving water quality standard from discharges of surface runoff from the land application sites. Biosolids shall not be applied to land 10 meters or less from waters of the United States (as defined in *40 CFR 122.2*).

4. No person shall apply biosolids for beneficial use to frozen, ice-covered, or snow-covered land where the slope of such land is greater than three percent and is less than or equal to six percent unless one of the following requirements is met:

   a. There is 80 percent vegetative ground cover; or,

   b. Approval has been obtained based upon a plan demonstrating adequate runoff containment measures.

5. Application of biosolids is prohibited to frozen, ice-covered, or snow covered sites where the slope of the site exceeds six percent.

6. Biosolids shall not be applied to sites where the available phosphorous content of the soil exceeds the following a/:

   a. 100 ppm as determined by the sodium bicarbonate extraction method

   b. 50 ppm as determined by the AB-DPTA extraction method

   c. 170 ppm by the Bray P1 extraction method

   a/ These phosphorous limits do not apply to the application sites if the PRWID has bermed the sites to prevent runoff from entering surface waters of the State. The berm shall be constructed to hold a 24 hour, 100 year storm event. The available phosphorous limits apply to all other sites

the PRWID may apply biosolids to unless the PRWID provides a separate justification for each site for a change or elimination of the limits. The PRWID is still required to monitor each site for phosphorous as stated in *Part III. B. 4. c.* of this permit.

7. Application of biosolids shall be conducted in a manner that does not exceed the agronomic rate for available nitrogen of the crops grown on the site. At a minimum, the permittee is required to follow the methods for calculating agronomic rate outlined in the latest version of the *Region VIII Biosolids Management Handbook* (other methods may be approved by the Director). The treatment plant shall provide written notification to the applier of the biosolids of the concentration of total nitrogen (as N on a dry weight basis) in the biosolids. Written permission from the Director is required to exceed the agronomic rate.

   The permittee may request the limits of *Part III, D., 6 and 7* be modified if different limits would be justified based on local conditions. The limits are required to be developed in cooperation with the local agricultural extension office or university.

8. Biosolids shall not be applied to any site area with standing surface water. If the annual high groundwater level is known or suspected to be within five feet of the surface, additional deep soil monitoring for nitrate-nitrogen as described in *Part III.B.4.b* is to be performed. At a minimum, this additional monitoring will involve a collection of more samples in the affected area and possibly more frequent sampling. The exact number of samples to be collected will be outlined in a deep soil-monitoring plan to be submitted to the Director and the EPA within 90 days of the effective date of this permit. The plan is subject to approval by the Director.

9. The specified cover crop shall be planted during the next available planting season. If this does not occur, the permittee shall notify the Director in writing. Additional restrictions may be placed on the application of the biosolids on that site on a case-by-case basis to control nitrate movement. Deep soil monitoring may be increased under the discretion of the Director.

10. When weather and or soil conditions prevent adherence to the biosolids application procedure, biosolids shall not be applied on the site.

11. For biosolids that are sold or given away, an information sheet shall be provided to the person who receives the biosolids. The label or information sheet shall contain:

    a. The name and address of the person who prepared the biosolids for sale or give away for application to the land.

    b. A statement that prohibits the application of the biosolids to the land except in accordance with the instructions on the label or information sheet.

12. Biosolids subject to the cumulative pollutant loading rates in Table 2 *(Part III.B.1.)* shall not be applied to agricultural land, forest, a public contact site, or a reclamation site if any of the cumulative pollutant loading rates in Table 2 has been reached.

13. If the treatment plant applies the biosolids, it shall provide the owner or leaseholder of the land on which the biosolids are applied notice and necessary information to comply with the requirements in this permit.

14. For biosolids or material derived from biosolids that are stored in piles for one year or longer, measures shall be taken to ensure that erosion (whether by wind or water) does not occur. However, best management practices should also be used for piles used for biosolids treatment. If a treatment pile is considered to have caused a problem, best management practices could be added as a requirement in the next permit renewal.

15. The permittee shall inspect the application of the biosolids to active sites to prevent malfunctions and deterioration, operator errors and discharges, which may cause or lead to the release of biosolids to the environment or a threat to human health. The permittee must conduct these inspections often enough to identify problems in time to correct them before they harm human health or the environment. The permittee shall keep an inspection log or summary including at least the date and time of inspection, the printed name and the handwritten signature of the inspector, a notation of observations made and the date and nature of any repairs or corrective action.

E. Special Conditions on Biosolids Storage

Permanent storage of biosolids is prohibited. Biosolids shall not be temporarily stored for more than two years. Written permission to store biosolids for more than two years must be obtained from the Director. Storage of biosolids for more than two years will be allowed only if it is determined that significant treatment is occurring.

F. Representative Sampling. Biosolids samples used to measure compliance with Part I of this Permit shall be collected at locations representative of the quality of biosolids generated at the treatment works and immediately prior to land application.

G. Reporting of Monitoring Results.

Biosolids. The permittee shall provide the results of all monitoring performed in accordance with *Part III.B*, and information on management practices, biosolids treatment, site restrictions and certifications shall be provided no later than February 19 of each year. Each report is for the previous calendar year. If no biosolids were sold or given away during the reporting period, "no biosolids were sold or given away" shall be reported. Legible copies of these, and all other reports required herein, shall be signed and certified in accordance with the *Signatory Requirements (see Part VII.G)*, and submitted to the Utah Division of Water Quality and the EPA at the following addresses:

Original to: Biosolids Coordinator
Utah Division of Water Quality
P. O. Box 144870
Salt Lake City Utah, 84114-4870

Copy to: Biosolids Coordinator, 8P-W-P
U. S. Environmental Protection Agency
Region VIII
999 18th Street, Suite 500
Denver, Colorado 80202-2466

H. Additional Record Keeping Requirements Specific to Biosolids.

1. The permittee is required to keep the following information for at least 5 years:

   a) Concentration of each heavy metal in Table 3 in *Part III.B.1*.

   b) A description of how the pathogen reduction requirements in *Part III.B.2* were met.

   c) A description of how the vector attraction reduction requirements in *Part III.B.3* were met.

   d) A description of how the site restrictions in *Part III.C* were met (if necessary).

   e) A description of how the management practices in *Part III.D* were met (if necessary).

   f) The following certification statement:

   "I certify under the penalty of law, that the heavy metals requirements in *Part III.B.1*, the pathogen requirements in *Part III.B.2*, the vector attraction requirements in *Part III.B.3*, the site restrictions were met in *Part III.C*. and management practices were met in *Part III.D*. This determination has been made under my direction and supervision in accordance with the system designed to assure that qualified personnel properly gather and evaluate the information used to determine that the pathogen requirements, the vector attraction reduction requirements and the management practices have been met. I am aware that there are significant penalties for false certification including the possibility of imprisonment."

2. The permittee shall retain records of all monitoring information, including all calibration and maintenance records and all original strip chart recordings for continuous monitoring instrumentation, copies of all reports required by this permit and records of all data used to complete the application for this permit

for the life of the permit. Data collected on site, copies of Biosolids Report forms, and a copy of this UPDES biosolids-only permit must be maintained on site during the duration of activity at the permitted location.

IV. STORM WATER REQUIREMENTS.

A. Coverage of This Section. The requirements listed under this section shall apply to storm water discharges. Storm water discharges from the following portions of the facility may be eligible for coverage under this permit: biosolids drying beds, haul or access roads on which transportation of biosolids may occur, grit screen cleaning areas, chemical loading, unloading and storage areas, salt or sand storage areas, vehicle or equipment storage and maintenance areas, or any other wastewater treatment device or system, used in the storage, treatment, recycling, and reclamation of municipal or domestic sewage, including lands dedicated to the disposal of sewage sludge that are located within the confines of the facility that may have a reasonable expectation to contribute to pollutants in a storm water discharge.

B. Prohibition of Non-Storm Water Discharges. Except for discharges identified in *Part I.*, and discharges described below in this paragraph, non-storm water discharges are prohibited. The following non-storm water discharges may be authorized under this permit provided the non-storm water component of the discharge is in compliance with this section; discharges from fire fighting activities; fire hydrant flushing; potable water sources including waterline flushing; drinking fountain water; irrigation drainage and lawn watering; routine external building wash down water where detergents or other compounds have not been used in the process; pavement wash waters where spills or leaks of toxic or hazardous materials (including oils and fuels) have not occurred (unless all spilled material has been removed) and where detergents are not used; air conditioning condensate; uncontaminated compressor condensate; uncontaminated springs; uncontaminated ground water; and foundation or footing drains where flows are not contaminated with process materials such as solvents.

C. Storm Water Pollution Prevention Plan Requirements. The permittee must have (on site) or develop and implement a storm water pollution prevention plan as a condition of this permit.

1. Contents of the Plan. The plan shall include, at a minimum, the following items:

a. *Pollution Prevention Team.* Each plan shall identify a specific individual or individuals within the facility organization as members of a storm water Pollution Prevention Team who are responsible for developing the storm water pollution prevention plan and assisting the facility or plant manager in its implementation, maintenance, and revision. The plan shall clearly identify the responsibilities of each team member. The activities and responsibilities of the team shall address all aspects of the facility's storm water pollution prevention plan.

b. *Description of Potential Pollutant Sources.* Each plan shall provide a description of potential sources which may reasonably be expected to add significant amounts of pollutants to storm water discharges or which may result in the discharge of pollutants during dry weather from separate storm sewers draining the facility. Each plan shall identify all activities and significant materials, which may be reasonably expected to have the potential as a significant pollutant source. Each plan shall include, at a minimum:

(1) *Drainage*. A site map indicating drainage areas and storm water outfalls. For each area of the facility that generates storm water discharges associated with the waste water treatment related activity with a reasonable potential for containing significant amounts of pollutants, a prediction of the direction of flow and an identification of the types of pollutants that are likely to be present in storm water discharges associated with the activity. Factors to consider include the toxicity of the pollutant; quantity of chemicals used, produced or discharged; the likelihood of contact with storm water; and history of significant leaks or spills of toxic or hazardous pollutants. Flows with a significant potential for causing erosion shall be identified. The site map shall include but not be limited to:

(a) Drainage direction and discharge points from all wastewater associated activities including but not limited to grit screen cleaning, bio-solids drying beds and transport, chemical/material loading, unloading and storage areas, vehicle maintenance areas, salt or sand storage areas.

(b) Location of any erosion and sediment control structure or other control measures utilized for reducing pollutants in storm water runoff.

(c) Location of bio-solids drying beds where exposed to precipitation or where the transportation of bio-solids may be spilled onto internal roadways or tracked off site.

(d) Location where grit screen cleaning or other routinely performed industrial activities are located and are exposed to precipitation.

(e) Location of any handling, loading, unloading or storage of chemicals or potential pollutants such as caustics, hydraulic fluids, lubricants, solvents or other petroleum products, or hazardous wastes and where these may be exposed to precipitation.

(f) Locations where any major spills or leaks of toxic or hazardous materials have occurred.

(g) Location of any sand or salt piles.

(h) Location of fueling stations or vehicle and equipment maintenance and cleaning areas that are exposed to precipitation.

(i) Location of receiving streams or other surface water bodies.

(j) Locations of outfalls and the types of discharges contained in the drainage areas of the outfalls.

(2) *Inventory of Exposed Materials*. An inventory of the types of materials handled at the site that potentially may be exposed to precipitation. Such inventory shall include a narrative description of significant materials that have been handled, treated, stored or disposed in a manner to allow exposure to storm water between the time of 3 years prior to the effective date of this permit and the present; method and location of onsite storage or disposal; materials management practices employed to minimize contact of materials with storm water runoff between the time of 3 years prior to the effective date of this permit and the present; the location and a description of existing structural and nonstructural control measures to reduce pollutants in storm water runoff; and a description of any treatment the storm water receives.

(3) *Spills and Leaks*. A list of significant spills and significant leaks of toxic or hazardous pollutants that occurred at areas that are exposed to precipitation or that otherwise drain to a storm water conveyance at the facility after the date of 3 years prior to the effective date of this permit. Such list shall be updated as appropriate during the term of the permit.

(4) *Sampling Data*. A summary of existing discharge sampling data describing pollutants in storm water discharges from the facility, including a summary of sampling data collected during the term of this permit.

(5) *Summary of Potential Pollutant Sources and Risk Assessment*. A narrative description of the potential pollutant sources from the following activities associated with treatment works: access roads/rail lines; loading and unloading operations; outdoor storage activities; material handling sites; outdoor vehicle storage or maintenance sites; significant dust or particulate generating processes; and onsite waste disposal practices. Specific potential pollutants shall be identified where known.

(6) *Measures and Controls*. The permittee shall develop a description of storm water management controls appropriate for the facility, and implement such controls. The appropriateness and priorities of controls in a plan shall reflect identified potential sources of pollutants at the facility. The description of storm water management controls shall address the following minimum components, including a schedule for implementing such controls:

(7) *Good Housekeeping*. All areas that may contribute pollutants to storm waters discharges shall be maintained in a clean, orderly manner. These are practices that would minimize the generation of pollutants at the source or before it would be necessary to employ sediment ponds or other control measures at the discharge outlets. Where applicable, such measures or other equivalent measures would include the following: sweepers and covered storage to minimize dust generation and storm runoff; conservation of vegetation where possible to minimize erosion;

sweeping of haul roads, bio-solids access points, and exits to reduce or eliminate off site tracking; sweeping of sand or salt storage areas to minimize entrainment in storm water runoff; collection, removal, and proper disposal of waste oils and other fluids resulting from vehicle and equipment maintenance; other equivalent measures to address identified potential sources of pollution.

(8) *Preventive Maintenance*. A preventive maintenance program shall involve timely inspection and maintenance of storm water management devices (e.g., cleaning oil/water separators, catch basins) as well as inspecting and testing facility equipment and systems to uncover conditions that could cause breakdowns or failures resulting in discharges of pollutants to surface waters, and ensuring appropriate maintenance of such equipment and systems.

(9) *Spill Prevention and Response Procedures*. Areas where potential spills that can contribute pollutants to storm water discharges can occur, and their accompanying drainage points, shall be identified clearly in the storm water pollution prevention plan. Where appropriate, specifying material handling procedures, storage requirements, and use of equipment such as diversion valves in the plan should be considered. Procedures and equipment for cleaning up spills shall be identified in the plan and made available to the appropriate personnel.

(10) *Inspections*. In addition to the comprehensive site evaluation required under paragraph (*Part IV.C.1.b.(16)*) of this section, qualified facility personnel shall be identified to inspect designated equipment and areas of the facility on a periodic basis. The following areas shall be included in all inspections: access roads/rail lines, equipment storage and maintenance areas (both indoor and outdoor areas); fueling; material handling areas, residual treatment, storage, and disposal areas; and wastewater treatment areas. A set of tracking or follow-up procedures shall be used to ensure that appropriate actions are taken in response to the inspections. Records of inspections shall be maintained. The use of a checklist developed by the facility is encouraged.

(11) *Employee Training*. Employee training programs shall inform personnel responsible for implementing activities identified in the storm water pollution prevention plan or otherwise responsible for storm water management at all levels of responsibility of the components and goals of the storm water pollution prevention plan. Training should address topics such as spill response, good housekeeping and material management practices. The pollution prevention plan shall identify how often training will take place, but training should be held at least annually (once per calendar year). Employee training must, at a minimum, address the following areas when applicable to a facility: petroleum product management; process chemical management; spill prevention and control; fueling procedures; general good housekeeping

practices; proper procedures for using fertilizers, herbicides and pesticides.

(12) *Record keeping and Internal Reporting Procedures*. A description of incidents (such as spills, or other discharges), along with other information describing the quality and quantity of storm water discharges shall be included in the plan required under this part. Inspections and maintenance activities shall be documented and records of such activities shall be incorporated into the plan.

(13) *Non-storm Water Discharges*.

(a) *Certification*. The plan shall include a certification that the discharge has been tested or evaluated for the presence of non-storm water discharges. The certification shall include the identification of potential significant sources of non-storm water at the site, a description of the results of any test and/or evaluation for the presence of non-storm water discharges, the evaluation criteria or testing method used, the date of any testing and/or evaluation, and the onsite drainage points that were directly observed during the test. Certifications shall be signed in accordance with *Part VII.G* of this permit.

(b) *Exceptions*. Except for flows from fire fighting activities, sources of non-storm water listed in *Part IV.B.* (Prohibition of Non-storm Water Discharges) of this permit that are combined with storm water discharges associated with industrial activity must be identified in the plan. The plan shall identify and ensure the implementation of appropriate pollution prevention measures for the non-storm water component(s) of the discharge.

(c) *Failure to Certify*. Any facility that is unable to provide the certification required (testing for non-storm water discharges), must notify the *Director* within 180 days after the effective date of this permit. If the failure to certify is caused by the inability to perform adequate tests or evaluations, such notification shall describe: the procedure of any test conducted for the presence of non-storm water discharges; the results of such test or other relevant observations; potential sources of non-storm water discharges to the storm sewer; and why adequate tests for such storm sewers were not feasible. Non-storm water discharges to waters of the State, which are not, authorized by a *UPDES* permit are unlawful, and must be terminated.

(14) *Sediment and Erosion Control*. The plan shall identify areas, which, due to topography, activities, or other factors, have a high potential for significant soil erosion, and identify structural, vegetative, and/or stabilization measures to be used to limit erosion.

(15) *Management of Runoff.* The plan shall contain a narrative consideration of the appropriateness of traditional storm water management practices (practices other than those which control the generation or source(s) of pollutants) used to divert, infiltrate, reuse, or otherwise manage storm water runoff in a manner that reduces pollutants in storm water discharges from the site. The plan shall provide that measures that the permittee determines to be reasonable and appropriate shall be implemented and maintained. The potential of various sources at the facility to contribute pollutants to storm water discharges associated with industrial activity *Part IV.C.1.b* (Description of Potential Pollutant Sources) of this permit] shall be considered when determining reasonable and appropriate measures. Appropriate measures or other equivalent measures may include: vegetative swales and practices, reuse of collected storm water (such as for a process or as an irrigation source), inlet controls (such as oil/water separators), snow management activities, infiltration devices, wet detention/retention devices and discharging storm water through the waste water facility for treatment.

(16) *Comprehensive Site Compliance Evaluation.* Qualified personnel shall conduct site compliance evaluations at appropriate intervals specified in the plan, but in no case less than once a year. Such evaluations shall provide:

(a) Areas contributing to a storm water discharge associated with industrial activity shall be visually inspected for evidence of, or the potential for, pollutants entering the drainage system. Measures to reduce pollutant loadings shall be evaluated to determine whether they are adequate and properly implemented in accordance with the terms of the permit or whether additional control measures are needed. Structural storm water management measures, sediment and erosion control measures, and other structural pollution prevention measures identified in the plan shall be observed to ensure that they are operating correctly. A visual inspection of equipment needed to implement the plan, such as spill response equipment, shall be made.

(b) Based on the results of the evaluation, the description of potential pollutant sources identified in the plan in accordance with *Part IV.C.1.b* (Description of Potential Pollutant Sources) of this section and pollution prevention measures and controls identified in the plan in accordance with *Part IV.C.1.b.(6)* (Measures and Controls) of this section shall be revised as appropriate within 2 weeks of such evaluation and shall provide for implementation of any changes to the plan in a timely manner, but in no case more than 12 weeks after the evaluation.

(c) A report summarizing the scope of the evaluation, personnel making the evaluation, the date(s) of the evaluation, major observations relating to the implementation of the storm water pollution

prevention plan, and actions taken in accordance with paragraph *i.* (above) shall be made and retained as part of the storm water pollution prevention plan for at least 3 years after the date of the evaluation. The report shall identify any incidents of noncompliance. Where a report does not identify any incidents of noncompliance, the report shall contain a certification that the facility is in compliance with the storm water pollution prevention plan and this permit. The report shall be signed in accordance with *Part VII.G* (Signatory Requirements) of this permit.

(17) *Deadlines for Plan Preparation and Compliance*. The permittee shall prepare and implement a plan in compliance with the provisions of this section within 270 days of the effective date of this permit. If the permittee already has a plan, it shall be revised according to *Part IV.C.1.b.(16)*, Comprehensive Site Evaluation.

(18) *Keeping Plans Current*. The permittee shall amend the plan whenever there is a change in design, construction, operation, or maintenance, that has a significant effect on the potential for the discharge of pollutants to the waters of the state or if the storm water pollution prevention plan proves to be ineffective in eliminating or significantly minimizing pollutants from sources identified by the plan, or in otherwise achieving the general objective of controlling pollutants in storm water discharges associated with the activities at the facility.

D. Monitoring and Reporting Requirements.

1. Quarterly Visual Examination of Storm Water Quality. Facilities shall perform and document a visual examination of a storm water discharge associated with industrial activity from each outfall, except discharges exempted below. The examination must be made at least once in each of the following designated periods during daylight hours unless there is insufficient rainfall or snow melt to produce a runoff event: January through March; April through June; July through September; and October through December.

   a. *Sample and Data Collection*. Examinations shall be made of samples collected within the first 30 minutes (or as soon thereafter as practical, but not to exceed 1 hour) of when the runoff or snowmelt begins discharging. The examinations shall document observations of color, odor, clarity, floating solids, settled solids, suspended solids, foam, oil sheen, and other obvious indicators of storm water pollution. The examination must be conducted in a well lit area. No analytical tests are required to be performed on the samples. All such samples shall be collected from the discharge resulting from a storm event that is greater than 0.1 inches in magnitude and that occurs at least 72 hours from the previously measurable (greater than 0.1 inch rainfall) storm event. Where practicable, the same individual should carry out the collection and examination of discharges for entire permit term.

b. *Visual Storm Water Discharge Examination Reports*. Visual examination reports must be maintained onsite in the pollution prevention plan. The report shall include the examination date and time, examination personnel, the nature of the discharge (i.e., runoff or snow melt), visual quality of the storm water discharge (including observations of color, odor, clarity, floating solids, settled solids, suspended solids, foam, oil sheen, and other obvious indicators of storm water pollution), and probable sources of any observed storm water contamination.

c. *Representative Discharge*. When the permittee has two or more outfalls that, based on a consideration of industrial activity, significant materials, and management practices and activities within the area drained by the outfall, the permittee reasonably believes discharge substantially identical effluents, the permittee may collect a sample of effluent of one of such outfalls and report that the observation data also applies to the substantially identical outfall(s) provided that the permittee includes in the storm water pollution prevention plan a description of the location of the outfalls and explains in detail why the outfalls are expected to discharge substantially identical effluents. In addition, for each outfall that the permittee believes is representative, an estimate of the size of the drainage area (in square feet) and an estimate of the runoff coefficient of the drainage area [e.g., low (under 40 percent), medium (40 to 65 percent), or high (above 65 percent)] shall be provided in the plan.

d. *Adverse Conditions*. When a discharger is unable to collect samples over the course of the visual examination period as a result of adverse climatic conditions, the discharger must document the reason for not performing the visual examination and retain this documentation onsite with the results of the visual examination. Adverse weather conditions, which may prohibit the collection of samples, include weather conditions that create dangerous conditions for personnel (such as local flooding, high winds, hurricane, tornadoes, electrical storms, etc.) or otherwise make the collection of a sample impracticable (drought, extended frozen conditions, etc.).

e. *Inactive and Unstaffed Site*. When a discharger is unable to conduct visual storm water examinations at an inactive and unstaffed site, the operator of the facility may exercise a waiver of the monitoring requirement as long as the facility remains inactive and unstaffed. The facility must maintain a certification with the pollution prevention plan stating that the site is inactive and unstaffed so that performing visual examinations during a qualifying event is not feasible.

V. MONITORING, RECORDING & GENERAL REPORTING REQUIREMENTS

A. Representative Sampling. Samples taken in compliance with the monitoring requirements established under *Part I* shall be collected from the effluent stream prior to discharge into the receiving waters. Samples and measurements shall be representative of the volume and nature of the monitored discharge. Samples of biosolids shall be collected at a location representative of the quality of biosolids immediately prior to the use-disposal practice.

B. Monitoring Procedures. Monitoring must be conducted according to test procedures approved under *Utah Administrative Code ("UAC") R317-2-10 and 40CFR Part 503*, unless other test procedures have been specified in this permit.

C. Penalties for Tampering. The *Act* provides that any person who falsifies, tampers with, or knowingly renders inaccurate, any monitoring device or method required to be maintained under this permit shall, upon conviction, be punished by a fine of not more than $10,000 per violation, or by imprisonment for not more than six months per violation, or by both.

D. Compliance Schedules. Reports of compliance or noncompliance with, or any progress reports on, interim and final requirements contained in any Compliance Schedule of this permit shall be submitted no later than 14 days following each schedule date.

E. Additional Monitoring by the Permittee. If the permittee monitors any parameter more frequently than required by this permit, using test procedures approved under *UAC R317-2-10* and *40 CFR 503* or as specified in this permit, the results of this monitoring shall be included in the calculation and reporting of the data submitted in the DMR or the Biosolids Report Form. Such increased frequency shall also be indicated. Only those parameters required by the permit need to be reported.

F. Records Contents. Records of monitoring information shall include:

1. The date, exact place, and time of sampling or measurements:
2. The individual(s) who performed the sampling or measurements;
3. The date(s) and time(s) analyses were performed;
4. The individual(s) who performed the analyses;
5. The analytical techniques or methods used; and,
6. The results of such analyses.

G. Retention of Records. The permittee shall retain records of all monitoring information, including all calibration and maintenance records and all original strip chart recordings for continuous monitoring instrumentation, copies of all reports required by this permit, and records of all data used to complete the application for this permit, for a period of at least five years from the date of the sample, measurement, report or application. This period may be extended by request of the

Director at any time. A copy of this UPDES permit must be maintained on site during the duration of activity at the permitted location

H. Twenty-four Hour Notice of Noncompliance Reporting.

1. The permittee shall (orally) report any noncompliance including transportation accidents, spills, and uncontrolled runoff from biosolids transfer or land application sites which may seriously endanger health or environment, as soon as possible, but no later than twenty-four (24) hours from the time the permittee first became aware of circumstances. The report shall be made to the Division of Water Quality, (801) 538-6146, or 24-hour answering service (801) 536-4123.

2. The following occurrences of noncompliance shall be reported by telephone (801) 536-4123 as soon as possible but no later than 24 hours from the time the permittee becomes aware of the circumstances:

   a. Any noncompliance which may endanger health or the environment;

   b. Any unanticipated bypass, which exceeds any effluent limitation in the permit (See *Part VI.G, Bypass of Treatment Facilities.)*;

   c. Any upset which exceeds any effluent limitation in the permit (See *Part VI.H, Upset Conditions.*);

   d. Violation of a maximum daily discharge limitation for any of the pollutants listed in the permit; or,

   e. Violation of any of the Table 3 metals limits, the pathogen limits, the vector attraction reduction limits or the management practices for biosolids that have been sold or given away.

3. A written submission shall also be provided within five days of the time that the permittee becomes aware of the circumstances. The written submission shall contain:

   a. A description of the noncompliance and its cause;

   b. The period of noncompliance, including exact dates and times;

   c. The estimated time noncompliance is expected to continue if it has not been corrected;

   d. Steps taken or planned to reduce, eliminate, and prevent reoccurrence of the noncompliance; and,

   e. Steps taken, if any, to mitigate the adverse impacts on the environment and human health during the noncompliance period.

4. The Director may waive the written report on a case-by-case basis if the oral report has been received within 24 hours by the Division of Water Quality, (801) 538-6146.

5. Reports shall be submitted to the addresses in *Part I.D, Reporting of Monitoring Results*.

I. Other Noncompliance Reporting. Instances of noncompliance not required to be reported within 24 hours shall be reported at the time that monitoring reports for *Part I.D* are submitted. The reports shall contain the information listed in *Part V.H.3*

J. Inspection and Entry The permittee shall allow the Director, or an authorized representative, upon the presentation of credentials and other documents as may be required by law, to:

1. Enter upon the permittee's premises where a regulated facility or activity is located or conducted, or where records must be kept under the conditions of the permit;

2. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;

3. Inspect at reasonable times any facilities, equipment (including monitoring and control equipment), practices, or operations regulated or required under this permit, including but not limited to, biosolids treatment, collection, storage facilities or area, transport vehicles and containers, and land application sites;

4. Sample or monitor at reasonable times, for the purpose of assuring permit compliance or as otherwise authorized by the *Act*, any substances or parameters at any location, including, but not limited to, digested biosolids before dewatering, dewatered biosolids, biosolids transfer or staging areas, any ground or surface waters at the land application sites or biosolids, soils, or vegetation on the land application sites; and,

5. The permittee shall make the necessary arrangements with the landowner or leaseholder to obtain permission or clearance, the Director, or authorized representative, upon the presentation of credentials and other documents as may be required by law, will be permitted to enter without delay for the purposes of performing their responsibilities.

VI. COMPLIANCE RESPONSIBILITIES

A. Duty to Comply. The permittee must comply with all conditions of this permit. Any permit noncompliance constitutes a violation of the Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or modification; or for denial of a permit renewal application. The permittee shall give advance notice to the Director of any planned changes in the permitted facility or activity, which may result in noncompliance with permit requirements.

B. Penalties for Violations of Permit Conditions. The *Act* provides that any person who violates a permit condition implementing provisions of the *Act* is subject to a civil penalty not to exceed $10,000 per day of such violation. Any person who willfully or negligently violates permit conditions or the Act is subject to a fine not exceeding $25,000 per day of violation. Any person convicted under *UCA 19-5-115(2)* a second time shall be punished by a fine not exceeding $50,000 per day. Except as provided at *Part VI.G, Bypass of Treatment Facilities* and *Part VI.H, Upset Conditions*, nothing in this permit shall be construed to relieve the permittee of the civil or criminal penalties for noncompliance.

C. Need to Halt or Reduce Activity not a Defense. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.

D. Duty to Mitigate. The permittee shall take all reasonable steps to minimize or prevent any discharge in violation of this permit, which has a reasonable likelihood of adversely affecting human health or the environment. The permittee shall also take all reasonable steps to minimize or prevent any land application in violation of this permit.

E. Proper Operation and Maintenance. The permittee shall at all times properly operate and maintain all facilities and systems of treatment and control (and related appurtenances) which are installed or used by the permittee to achieve compliance with the conditions of this permit. Proper operation and maintenance also includes adequate laboratory controls and quality assurance procedures. This provision requires the operation of back-up or auxiliary facilities or similar systems, which are installed by a permittee only when the operation is necessary to achieve compliance with the conditions of the permit.

F. Removed Substances. Collected screening, grit, solids, sludge, or other pollutants removed in the course of treatment shall be disposed of in such a manner so as to prevent any pollutant from entering any waters of the state or creating a health hazard. Sludge/digester supernatant and filter backwash

shall not directly enter either the final effluent or waters of the state by any other direct route.

G. Bypass of Treatment Facilities.

1. Bypass Not Exceeding Limitations. The permittee may allow any bypass to occur which does not cause effluent limitations to be exceeded, but only if it also is for essential maintenance to assure efficient operation. These bypasses are not subject to paragraph 2 and 3 of this section.

2. Prohibition of Bypass.

   a. Bypass is prohibited, and the Director may take enforcement action against a permittee for bypass, unless:

      (1) Bypass was unavoidable to prevent loss of human life, personal injury, or severe property damage;

      (2) There were no feasible alternatives to bypass, such as the use of auxiliary treatment facilities, retention of untreated wastes, or maintenance during normal periods of equipment downtime. This condition is not satisfied if adequate backup equipment should have been installed in the exercise of reasonable engineering judgment to prevent a bypass which occurred during normal periods of equipment downtime or preventive maintenance, and

      (3) The permittee submitted notices as required under *section VI.G.3*.

   b. The Director may approve an anticipated bypass, after considering its adverse effects, if the Director determines that it will meet the three conditions listed in *sections VI.G.2.a (1), (2) and (3)*.

3. Notice.

   a. *Anticipated bypass*. Except as provided above in *section VI.G.2* and below in *section VI.G.3.b*, if the permittee knows in advance of the need for a bypass, it shall submit prior notice, at least ninety days before the date of bypass. The prior notice shall include the following unless otherwise waived by the Director:

      (1) Evaluation of alternative to bypass, including cost-benefit analysis containing an assessment of anticipated resource damages:

(2) A specific bypass plan describing the work to be performed including scheduled dates and times. The permittee must notify the Director in advance of any changes to the bypass schedule;

(3) Description of specific measures to be taken to minimize environmental and public health impacts;

(4) A notification plan sufficient to alert all downstream users, the public and others reasonably expected to be impacted by the bypass;

(5) A water quality assessment plan to include sufficient monitoring of the receiving water before, during and following the bypass to enable evaluation of public health risks and environmental impacts; and,

(6) Any additional information requested by the Director.

b. *Emergency Bypass*. Where ninety days advance notice is not possible, the permittee must notify the Director, and the Director of the Department of Natural Resources, as soon as it becomes aware of the need to bypass and provide to the Director the information in *section VI.G.3.a.(1) through (6)* to the extent practicable.

c. *Unanticipated bypass*. The permittee shall submit notice of an unanticipated bypass to the Director as required under *Part IV.H*, Twenty Four Hour Reporting. The permittee shall also immediately notify the Director of the Department of Natural Resources, the public and downstream users and shall implement measures to minimize impacts to public health and environment to the extent practicable.

H. Upset Conditions.

1. Effect of an upset. An upset constitutes an affirmative defense to an action brought for noncompliance with technology based permit effluent limitations if the requirements of paragraph 2 of this section are met. Director's administrative determination regarding a claim of upset cannot be judiciously challenged by the permittee until such time as an action is initiated for noncompliance.

2. Conditions necessary for a demonstration of upset. A permittee who wishes to establish the affirmative defense of upset shall demonstrate, through properly signed, contemporaneous operating logs, or other relevant evidence that:

a. An upset occurred and that the permittee can identify the cause(s) of the upset;

b. The permitted facility was at the time being properly operated;

c. The permittee submitted notice of the upset as required under *Part V.H, Twenty-four Hour Notice of Noncompliance Reporting*; and,

d. The permittee complied with any remedial measures required under *Part VI.D, Duty to Mitigate*.

3. Burden of proof. In any enforcement proceeding, the permittee seeking to establish the occurrence of an upset has the burden of proof.

VII. GENERAL REQUIREMENTS

A. Planned Changes. The permittee shall give notice to the Director as soon as possible of any planned physical alterations or additions to the permitted facility. Notice is required only when the alteration or addition could significantly change the nature or increase the quantity of parameters discharged or pollutant sold or given away. This notification applies to pollutants, which are not subject to effluent limitations in the permit. In addition, if there are any planned substantial changes to the permittee's existing sludge facilities or their manner of operation or to current sludge management practices of storage and disposal, the permittee shall give notice to the Director of any planned changes at least 30 days prior to their implementation.

B. Anticipated Noncompliance. The permittee shall give advance notice to the Director of any planned changes in the permitted facility or activity, which may result in noncompliance with permit requirements.

C. Permit Actions. This permit may be modified, revoked and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance, does not stay any permit condition.

D. Duty to Reapply. If the permittee wishes to continue an activity regulated by this permit after the expiration date of this permit, the permittee shall apply for and obtain a new permit. The application shall be submitted at least 180 days before the expiration date of this permit.

E. Duty to Provide Information. The permittee shall furnish to the Director, within a reasonable time, any information which the Director may request to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The permittee shall also furnish to the Director, upon request, copies of records required to be kept by this permit.

F. Other Information. When the permittee becomes aware that it failed to submit any relevant facts in a permit application, or submitted incorrect information in a permit application or any report to the Director, it shall promptly submit such facts or information.

G. Signatory Requirements. All applications, reports or information submitted to the Director shall be signed and certified.

1. All permit applications shall be signed by either a principal executive officer or ranking elected official.

2. All reports required by the permit and other information requested by the Director shall be signed by a person described above or by a duly authorized representative of that person. A person is a duly authorized representative only if:

   a. The authorization is made in writing by a person described above and submitted to the Director, and,

   b. The authorization specifies either an individual or a position having responsibility for the overall operation of the regulated facility, such as the position of plant manager, superintendent, position of equivalent responsibility, or an individual or position having overall responsibility for environmental matters. A duly authorized representative may thus be either a named individual or any individual occupying a named position.

3. Changes to authorization. If an authorization under *paragraph VII.G.2* is no longer accurate because a different individual or position has responsibility for the overall operation of the facility, a new authorization satisfying the requirements of *paragraph VII.G.2.* must be submitted to the Director prior to or together with any reports, information, or applications to be signed by an authorized representative.

4. Certification. Any person signing a document under this section shall make the following certification:

   "I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations."

H. Penalties for Falsification of Reports. The *Act* provides that any person who knowingly makes any false statement, representation, or certification in any record or other document submitted or required to be maintained under this permit, including monitoring reports or reports of compliance or noncompliance shall, upon conviction be punished by a fine of not more than

$10,000.00 per violation, or by imprisonment for not more than six months per violation, or by both.

I. Availability of Reports. Except for data determined to be confidential under *UAC R317-8-3.2*, all reports prepared in accordance with the terms of this permit shall be available for public inspection at the office of Director. As required by the *Act*, permit applications, permits and effluent data shall not be considered confidential.

J. Oil and Hazardous Substance Liability. Nothing in this permit shall be construed to preclude the permittee of any legal action or relieve the permittee from any responsibilities, liabilities, or penalties to which the permittee is or may be subject under the *Act*.

K. Property Rights. The issuance of this permit does not convey any property rights of any sort, or any exclusive privileges, nor does it authorize any injury to private property or any invasion of personal rights, nor any infringement of federal, state or local laws or regulations.

L. Severability. The provisions of this permit are severable, and if any provisions of this permit, or the application of any provision of this permit to any circumstance, is held invalid, the application of such provision to other circumstances, and the remainder of this permit, shall not be affected thereby.

M. Transfers. This permit may be automatically transferred to a new permittee if:

1. The current permittee notifies the Director at least 20 days in advance of the proposed transfer date;

2. The notice includes a written agreement between the existing and new permittee's containing a specific date for transfer of permit responsibility, coverage, and liability between them; and,

3. The Director does not notify the existing permittee and the proposed new permittee of his or her intent to modify, or revoke and reissue the permit. If this notice is not received, the transfer is effective on the date specified in the agreement mentioned in paragraph *2* above.

N. State or Federal Laws. Nothing in this permit shall be construed to preclude the institution of any legal action or relieve the permittee from any responsibilities, liabilities, or penalties established pursuant to any applicable state law or regulation under authority preserved by *UCA 19-5-117* and *Section 510* of the *Act* or any applicable Federal or State transportation

regulations, such as but not limited to the Department of Transportation regulations.

O. Water Quality - Reopener Provision. This permit may be reopened and modified (following proper administrative procedures) to include the appropriate effluent limitations and compliance schedule, if necessary, if one or more of the following events occurs:

1. Water Quality Standards for the receiving water(s) to which the permittee discharges are modified in such a manner as to require different effluent limits than contained in this permit.

2. A final wasteload allocation is developed and approved by the State and/or EPA for incorporation in this permit.

3. Revisions to the current CWA § 208 area wide treatment management plans or promulgations/revisions to TMDLs (40 CFR 130.7) approved by the EPA and adopted by DWQ which calls for different effluent limitations than contained in this permit.

P. Biosolids – Reopener Provision. This permit may be reopened and modified (following proper administrative procedures) to include the appropriate biosolids limitations (and compliance schedule, if necessary), management practices, other appropriate requirements to protect public health and the environment, or if there have been substantial changes (or such changes are planned) in biosolids use or disposal practices; applicable management practices or numerical limitations for pollutants in biosolids have been promulgated which are more stringent than the requirements in this permit; and/or it has been determined that the permittees biosolids use or land application practices do not comply with existing applicable state of federal regulations.

Q. Toxicity Limitation - Reopener Provision. This permit may be reopened and modified (following proper administrative procedures) to include, whole effluent toxicity (WET) limitations, a compliance date, a compliance schedule, a change in the whole effluent toxicity (biomonitoring) protocol, additional or modified numerical limitations, or any other conditions related to the control of toxicants if one or more of the following events occur;

1. Toxicity is detected, as per *Part I.C.3.a* of this permit, during the duration of this permit.

2. The TRE results indicate that compliance with the toxic limits will require an implementation schedule past the date for compliance and the Director agrees with the conclusion.

3. The TRE results indicate that the toxicant(s) represent pollutant(s) that may be controlled with specific numerical limits, and the Director agrees that numerical controls are the most appropriate course of action.

4. Following the implementation of numerical control(s) of toxicant(s), the Director agrees that a modified biomonitoring protocol is necessary to compensate for those toxicant that are controlled numerically.

5. The TRE reveals other unique conditions or characteristics, which in the opinion of the permit issuing authority justify the incorporation of unanticipated special conditions in the permit.

R. Storm Water-Reopener Provision. At any time during the duration (life) of this permit, this permit may be reopened and modified (following proper administrative procedures) as per *UAC R317.8*, to include, any applicable storm water provisions and requirements, a storm water pollution prevention plan, a compliance schedule, a compliance date, monitoring and/or reporting requirements, or any other conditions related to the control of storm water discharges to "waters-of-State".

VIII. DEFINITIONS

A. Wastewater.

1. The "7-day (and weekly) average", other than for e-coli bacteria, fecal coliform bacteria, and total coliform bacteria, is the arithmetic average of all samples collected during a consecutive 7-day period or calendar week, whichever is applicable. Geometric means shall be calculated for e-coli bacteria, fecal coliform bacteria, and total coliform bacteria. The 7-day and weekly averages are applicable only to those effluent characteristics for which there are 7-day average effluent limitations. The calendar week, which begins on Sunday and ends on Saturday, shall be used for purposes of reporting self-monitoring data on discharge monitoring report forms. Weekly averages shall be calculated for all calendar weeks with Saturdays in the month. If a calendar week overlaps two months (i.e., the Sunday is in one month and the Saturday in the following month), the weekly average calculated for that calendar week shall be included in the data for the month that contains Saturday.

2. The "30-day (and monthly) average," other than for e-coli bacteria, fecal coliform bacteria and total coliform bacteria, is the arithmetic average of all samples collected during a consecutive 30-day period or calendar month, whichever is applicable. Geometric means shall be calculated for e-coli bacteria, fecal coliform bacteria and total coliform bacteria. The calendar month shall be used for purposes of reporting self-monitoring data on discharge monitoring report forms.

3. "Act," means the *Utah Water Quality Act*.

4. "Acute toxicity" occurs when 50 percent or more mortality is observed for either test species at any effluent concentration (lethal concentration or "LC_{50}").

5. "Bypass," means the diversion of waste streams from any portion of a treatment facility.

6. "Composite Samples" shall be flow proportioned. The composite sample shall, as a minimum, contain at least four (4) samples collected over the compositing period. Unless otherwise specified, the time between the collection of the first sample and the last sample shall not be less than six (6) hours nor more than 24 hours. Acceptable methods for preparation of composite samples are as follows:

a. Constant time interval between samples, sample volume proportional to flow rate at time of sampling;

b. Constant time interval between samples, sample volume proportional to total flow (volume) since last sample. For the first sample, the flow rate at the time the sample was collected may be used;

c. Constant sample volume, time interval between samples proportional to flow (i.e., sample taken every "X" gallons of flow); and,

d. Continuous sample volume, with sample collection rate proportional to flow rate.

7. "CWA," means *The Federal Water Pollution Control Act*, as amended, by *The Clean Water Act of 1987*.

8. "Daily Maximum" (Daily Max.) is the maximum value allowable in any single sample or instantaneous measurement.

9. "EPA," means the United States Environmental Protection Agency.

10. "Director," means Director of the Utah Water Quality Board.

11. A "grab" sample, for monitoring requirements, is defined as a single "dip and take" sample collected at a representative point in the discharge stream.

12. An "instantaneous" measurement, for monitoring requirements, is defined as a single reading, observation, or measurement.

13. "Severe Property Damage," means substantial physical damage to property, damage to the treatment facilities which causes them to become inoperable, or substantial and permanent loss of natural resources which can reasonably be expected to occur in the absence of a bypass. Severe property damage does not mean economic loss caused by delays in production.

14. "Upset," means an exceptional incident in which there is unintentional and temporary noncompliance with technology-based permit effluent limitations because of factors beyond the reasonable control of the permittee. An upset does not include noncompliance to the extent caused by operational error, improperly designed treatment facilities, inadequate treatment facilities, lack of preventative maintenance, or careless or improper operation.

B. Biosolids.

1. "Biosolids," means any material or material derived from sewage solids that have been biologically treated.

2. "Dry Weight-Basis," means 100 percent solids (i.e. zero percent moisture).

3. "Land Application" is the spraying or spreading of biosolids onto the land surface; the injection of biosolids below the land surface; or the incorporation of biosolids into the land so that the biosolids can either condition the soil or fertilize crops or vegetation grown in the soil. Land application includes distribution and marketing (i.e. the selling or giving away of the biosolids).

4. "Pathogen," means an organism that is capable of producing an infection or disease in a susceptible host.

5. "Pollutant" for the purposes of this permit is an organic substance, an inorganic substance, a combination of organic and inorganic substances, or pathogenic organisms that after discharge and upon exposure, ingestion, inhalation, or assimilation into an organism either directly from the environment or indirectly by ingestion through the food-chain, could on the basis of information available to the Administrator of EPA, cause death, disease, behavioral abnormalities, cancer, genetic mutations, physiological malfunctions (including malfunction in reproduction), or physical deformations in either organisms or offspring of the organisms.

6. "Runoff" is rainwater, leachate, or other liquid that drains over any part of a land surface and runs off the land surface.

7. "Similar Container" is either an open or closed receptacle. This includes, but is not limited to, a bucket, a box, a carton, and a vehicle or trailer with a load capacity of one metric ton or less.

8. "Total Solids" are the materials in the biosolids that remain as a residue if the biosolids are dried at 103° or 105° Celsius.

9. "Treatment Works" are either Federally owned, publicly owned, or privately owned devices or systems used to treat (including recycling and reclamation) either domestic sewage or a combination of domestic sewage and industrial waste or liquid manure.

10. "Vector Attraction" is the characteristic of biosolids that attracts rodents, flies mosquito's or other organisms capable of transporting infectious agents.

11. "Animals" for the purpose of this permit are domestic livestock.

12. "Annual Whole Sludge Application Rate" is the amount of sewage sludge (dry-weight basis) that can be applied to a unit area of land during a cropping cycle.

13. "Agronomic Rate is the whole sludge application rate (dry-weight basis) designed to: (1) provide the amount of nitrogen needed by the crop or vegetation grown on the land; and (2) minimize the amount of nitrogen in the sewage sludge that passes below the root zone of the crop or vegetation grown on the land to the ground water.

14. "Annual Pollutant Loading Rate" is the maximum amount of a pollutant (dry-weight basis) that can be applied to a unit area of land during a 365-day period.

15. "Application Site or Land Application Site" means all contiguous areas of a users' property intended for sludge application.

16. "Cumulative Pollutant Loading Rate" is the maximum amount of an inorganic pollutant (dry-weight basis) that can be applied to a unit area of land.

17. "Grit and Screenings" are sand, gravel, cinders, other materials with a high specific gravity and relatively large materials such as rags generated during preliminary treatment of domestic sewage at a treatment works and shall be disposed of according to *40 CFR 258*.

18. "High Potential for Public Contact Site" is land with a high potential for contact by the public. This includes, but is not limited to, public parks, ball fields, cemeteries, plant nurseries, turf farms, and golf courses.

19. "Low Potential for Public Contact Site" is the land with a low potential for contact by the public. This includes, but is not limited to, farms, ranches, reclamation areas, and other lands which are private lands, restricted public lands, or lands which are not generally accessible to or used by the public.

20. "Monthly Average" is the arithmetic mean of all measurements taken during the month.

21. "Volatile Solids" is the amount of the total solids in sewage sludge lost when the sludge is combusted at 550 degrees Celsius for 15-20 minutes in the presence of excess air.

C. Storm Water.

1. "Best Management Practices" ("BMPs") means schedules of activities, prohibitions of practices, maintenance procedures, and other management practices to prevent or reduce the pollution of waters of the State. BMPs also include treatment requirements, operating procedures, and practices to control facility site runoff, spillage or leaks, sludge or waste disposal, or drainage from raw material storage.

2. "Coal pile runoff" means the rainfall runoff from or through any coal storage pile.

3. "Co-located industrial activity" means when a facility has industrial activities being conducted onsite that are described under more than one of the coverage sections of *Appendix II* in the General Multi-Sector Permit for Storm Water Discharges Associated with Industrial Activity. Facilities with co-located industrial activities shall comply with all applicable monitoring and pollution prevention plan requirements of each section in which a co-located industrial activity is described.

4. "Commercial Treatment and Disposal Facilities" means facilities that receive, on a commercial basis, any produced hazardous waste (not their own) and treat or dispose of those wastes as a service to the generators. Such facilities treating and/or disposing exclusively residential hazardous wastes are not included in this definition.

5. "Landfill" means an area of land or an excavation in which wastes are placed for permanent disposal, and that is not a land application unit, surface impoundment, injection well, or waste pile.

6. "Land application unit" means an area where wastes are applied onto or incorporated into the soil surface (excluding manure spreading operations) for treatment or disposal.

7. "Municipal separate storm sewer system" (large and/or medium) means all municipal separate storm sewers that are either:

   a. Located in an incorporated place (city) with a population of 100,000 or more as determined by the latest Decennial Census by the Bureau of

Census (at the issuance date of this permit, Salt Lake City is the only city in Utah that falls in this category); or

b. Located in the counties with unincorporated urbanized populations of 100,000 or more, except municipal separate storm sewers that are located in the incorporated places, townships or towns within such counties (at the issuance date of this permit Salt Lake County is the only county that falls in this category); or

c. Owned or operated by a municipality other than those described in paragraph *a.* or *b.* (above) and that are designated by the *Director* as part of the large or medium municipal separate storm sewer system.

8. "NOI" means "notice of intent", it is an application form that is used to obtain coverage under the General Multi-Sector Permit for Storm Water Discharges Associated with Industrial Activity.

9. "NOT" means "notice of termination", it is a form used to terminate coverage under the General Multi-Sector Permit for Storm Water Discharges Associated with Industrial Activity.

10. "Point source" means any discernible, confined, and discrete conveyance, including but not limited to, any pipe, ditch, channel, tunnel, conduit, well, discrete fissure, container, rolling stock, concentrated animal feeding operation, landfill leachate collection system, vessel or other floating craft from which pollutants are or may be discharged. This term does not include return flows from irrigated agriculture or agricultural storm water runoff.

11. "Section 313 water priority chemical" means a chemical or chemical categories that:

a. Are listed at *40 CFR 372.65* pursuant to *Section 313* of the *Emergency Planning and Community Right-to-Know Act* (*EPCRA*) (also known as *Title III of the Superfund Amendments and Reauthorization Act* (*SARA*) of 1986);

b. Are present at or above threshold levels at a facility subject to *EPCRA Section 313* reporting requirements; and

c. Meet at least one of the following criteria:

(1) Are listed in *Appendix D* of *40 CFR Part 122* on either Table II (organic priority pollutants), Table III (certain metals, cyanides,

and phenols) or Table V (certain toxic pollutants and hazardous substances);

(2) Are listed as a hazardous substance pursuant to *Section 311(b)(2)(A)* of the *CWA* at *40 CFR 116.4*; or

(3) Are pollutants for which EPA has published acute or chronic water quality criteria. See *Appendix III* of this permit. This appendix was revised based on final rulemaking EPA published in the *Federal Register* November 30, 1994.

12. "Significant materials" includes, but is not limited to: raw materials; fuels; materials such as solvents, detergents, and plastic pellets; finished materials such as metallic products; raw materials used in food processing or production; hazardous substances designated under *Section 101(14)* of *CERCLA*; any chemical the facility is required to report pursuant to *EPCRA Section 313*; fertilizers; pesticides; and waste products such as ashes, slag and sludge that have the potential to be released with storm water discharges.

13. "Significant spills" includes, but is not limited to: releases of oil or hazardous substances in excess of reportable quantities under *Section 311 of the Clean Water Act* (see *40 CFR 110.10* and *CFR 117.21*) or *Section 102* of *CERCLA* (see *40 CFR 302.4*).

14. "Storm water" means storm water runoff, snowmelt runoff, and surface runoff and drainage.

15. "SWDMR" means "storm water discharge monitoring report", a report of the results of storm water monitoring required by the permit. The Division of Water Quality provides the storm water discharge monitoring report form.

16. "Storm water associated with industrial activity" (*UAC R317-8-3.8(6)(c) & (d)*) means the discharge from any conveyance that is used for collecting and conveying storm water and that is directly related to manufacturing, processing or raw materials storage areas at an industrial plant. The term does not include discharges from facilities or activities excluded from the *UPDES* program. For the categories of industries identified in paragraphs *(a)* through *(j)* of this definition, the term includes, but is not limited to, storm water discharges from industrial plant yards; immediate access roads and rail lines used or traveled by carriers of raw materials, manufactured products, waste material, or by-products used or created by the facility; material handling sites; refuse sites; sites used

for the application or disposal of process waste waters (as defined in *40 CFR Part 401*); sites used for the storage and maintenance of material handling equipment; sites used for residual treatment, storage, or disposal; shipping and receiving areas; manufacturing buildings; storage areas (including tank farms) for raw materials, and intermediate and finished products; and areas where industrial activity has taken place in the past and significant materials remain and are exposed to storm water. For the categories of industries identified in paragraph *(k)* of this definition, the term includes only storm water discharges from all areas (except access roads and rail lines) listed in the previous sentence where material handling equipment or activities, raw materials, intermediate products, final products, waste materials, by-products, or industrial machinery are exposed to storm water. For the purposes of this paragraph, material handling activities include the storage, loading and unloading, transportation, or conveyance of any raw material, intermediate product, finished product, by-product or waste product. The term excludes areas located on plant lands separate from the plant's industrial activities, such as office buildings and accompanying parking lots as long as the drainage from the excluded areas is not mixed with storm water drained from the above described areas. Industrial facilities (including industrial facilities that are Federally, State, or municipally owned or operated that meet the description of the facilities listed in paragraphs *(a)* to *(k)* of this definition) include those facilities designated under *UAC R317-8-3.8(1)(a)5.* The following categories of facilities are considered to be engaging in "industrial activity" for purposes of this subsection:

a. Facilities subject to storm water effluent limitations guidelines, new source performance standards, or toxic pollutant effluent standards under *40 CFR Subchapter N* (except facilities with toxic pollutant effluent standards that are exempted under category (k) of this definition);

b. Facilities classified as Standard Industrial Classifications 24 (except 2434), 26 (except 265 and 267), 28 (except 283 and 285), 29, 311, 32 (except 323), 33, 3441, 373;

c. Facilities classified as Standard Industrial Classifications 10 through 14 (mineral industry) including active or inactive mining operations (except for areas of coal mining operations no longer meeting the definition of a reclamation area under *40 CFR 434.11(l)* because the performance bond issued to the facility by the appropriate SMCRA authority has been released, or except for areas of non-coal mining operations that have been released from applicable State or Federal reclamation requirements after December 17, 1990) and oil and gas

exploration, production, processing, or treatment operations, or transmission facilities that discharge storm water contaminated by contact with or that has come into contact with, any overburden, raw material, intermediate products, finished products, byproducts or waste products located on the site of such operations; inactive mining operations are mining sites that are not being actively mined, but that have an identifiable owner/operator;

d. Hazardous waste treatment, storage, or disposal facilities, including those that are operating under interim status or a permit under Subtitle C of RCRA;

e. Landfills, land application sites, and open dumps that have received any industrial wastes (waste that is received from any of the facilities described under this subsection) including those that are subject to regulation under *Subtitle D* of *RCRA*;

f. Facilities involved in the recycling of materials, including metal scrapyards, battery reclaimers, salvage yards, and automobile junkyards, including but limited to those classified as Standard Industrial Classification 5015 and 5093;

g. Steam electric power generating facilities, including coal handling sites;

h. Transportation facilities classified as Standard Industrial Classifications 40, 41, 42 (except 4221-25), 43, 44, 45 and 5171 that have vehicle maintenance shops, equipment cleaning operations, or airport deicing operations. Only those portions of the facility that are either involved in vehicle maintenance (including vehicle rehabilitation, mechanical repairs, painting, fueling, and lubrication), equipment cleaning operations, airport deicing operations, or that are otherwise identified under paragraphs (a) to (g) or (I) to (k) of this subsection are associated with industrial activity;

i. Treatment works treating domestic sewage or any other sewage sludge or wastewater treatment device or system, used in the storage treatment, recycling, and reclamation of municipal or domestic sewage, including land dedicated to the disposal of sewage sludge that are located within the confines of the facility, with a design flow of 1.0 mgd or more, or required to have an approved pretreatment program under *40 CFR Part 403*. Not included are farm lands, domestic gardens or lands used for sludge management where sludge is

beneficially reused and that are not physically located in the confines of the facility, or areas that are in compliance with *40 CFR Part 503*;

j. Construction activity including clearing, grading and excavation activities except: operations that result in the disturbance of less than 5 acres of total land area that are not part of a larger common plan of development or sale;

k. Facilities under Standard Industrial Classifications 20, 21, 22, 23, 2434, 25, 265, 267, 27, 283, 285, 30, 31 (except 311), 323, 34 (except 3441), 35, 36, 37 (except 373), 38, 39, 4221-25, (and that are not otherwise included within categories (a) to (j))

17. "Waste pile" means any non-containerized accumulation of solid, non-flowing waste that is used for treatment or storage.

STATEMENT OF BASIS
PRICE RIVER WATER IMPROVEMENT DISTRICT (PRIWID)
RENEWAL PERMIT: DISCHARGE, BIOSOLIDS & STORM WATER
UPDES PERMIT NUMBER: UT0021814
UPDES BIOSOLIDS PERMIT NUMBER: UTL0021814
UPDES MULTI-SECTOR STORM WATER GENERAL PERMIT NUMBER: UTR000000
MAJOR MUNICIPAL

FACILITY CONTACTS

Person Name:	Jeffery R. Richins
Position:	District Manager
Person Name:	Brian Harris
Position:	Wastewater Treatment Plant Superintendent
Facility Name:	Price River Water Improvement District
Facility Address:	5382 East Washer Plant Road Wellington, Utah 84542
Mailing Address:	P.O. Box 903 Price, Utah 84501
Telephone:	435-637-8547

DESCRIPTION OF FACILITY

Price River Water Improvement District (PRWID) owns and operates a wastewater treatment facility which serves the communities of Helper, Price, Wellington and the majority of residents within the Price River Valley.

PRWID Wastewater Treatment Plant has an average flow of 1.7 MGD over the last 5 years. The treatment consists of screens, aerated grit chamber, pista-grit removal system, 2 rectangular primary clarifiers, 2 rock media trickling filters, 2 solids contact floc formation basins, 2 activated sludge aeration basins, 2 circular clarifiers, chlorine contact chamber followed by dechlorination with SO_2.

PRWID applies Class B biosolids on its on-farm operation where feed for non-dairy cattle and horses is grown. These biosolids are prepared as follows:

Anaerobic Digestion:	1 primary digester 1 secondary digester
Pathogen Reduction Step:	2 aerated deep facultative sludge basins sun dried biosolids, land application

SUMMARY OF CHANGES FROM PREVIOUS PERMIT

The facility has a maximum wet weather daily design flow of 6 MGD and a max monthly design flow of 4 MGD. However, because the facility has operated steadily for the last 5 years at a monthly average flow of 1.7 MGD, the facility has requested that a chronic flow of 2.2 MGD and an acute flow of 3.0 MGD be used for the development of the Wasteload Analysis (WLA). These flow limits are included in the renewal permit.

The renewal permit contains monthly average and max daily effluent limits for ammonia. The previous permit only contained a daily maximum effluent limit for ammonia.

Influent and effluent monitoring requirements for metals have been reduced from twice yearly to yearly in the renewal permit. This reduction in monitoring is warranted because the last 10 monitoring results have demonstrated that metal concentrations in the effluent are below water quality standards and that the facility does not have a pretreatment program.

Quarterly monitoring requirements for phosphorus, CBOD, nitrate and nitrite are included in the renewal permit. It is expected that the results from this sampling will aide in the development of future renewal permits.

DISCHARGE

DESCRIPTION OF DISCHARGE

PRWID has reported self-monitoring results on Discharge Monitoring Reports on a monthly basis and has a good compliance history. A summary of the last 5 years of data is included as an addendum to this document.

Outfall	Description of Discharge Point
001	Located at latitude 39° 32' 21" and longitude 110° 42' 44" the discharge is through a 60" pipe on the east side of the facility discharging into the Price River. It is approximately 1 ½ miles southwest of Wellington, on the west side of the Price River and the Denver and Rio Grande Western Railroad tracks, at 5382 Washer\Plant Road, Wellington, Carbon County, Utah.

RECEIVING WATERS AND STREAM CLASSIFICATION

The final discharge flows into the stretch of the Price River. According to the *Utah Administrative Code* R317-2-13, this segment of the Price River is classified as the following:

Class 2B	-Protected for secondary contact recreation such as boating, wading, or similar uses.
Class 3C	-Protected for nongame fish and other aquatic life, including the necessary aquatic organisms in their food chain.
Class 4	-Protected for agricultural uses including irrigation of crops and stock watering.

BASIS FOR EFFLUENT LIMITATIONS

Limitations on total suspended solids (TSS), biochemical oxygen demand (BOD_5), E. coli, pH and percent removal for BOD_5 and TSS are based on current Utah Secondary Treatment Standards (*UAC R317-1-3.2*). Oil and grease is based on best professional judgment (BPJ). Ammonia, total residual chlorine (TRC), and dissolved oxygen (DO), are based on Utah water quality standards. The concentration limit for total dissolved solids (TDS) is based directly on the Utah water quality site specific standard for TDS for the stretch of the Price River identified as, "Price River and tributaries from the confluence with Coal Creek to Carbon Canal Diversion" (see footnote (4) under *UAC R317-2-14*). The load limit for TDS is based on the *Price River, San Rafael River, and Muddy Creek TMDLs for Total Dissolved Solids West Colorado Watershed Management Unit, Utah*, which as a site specific criterion is an appropriate TDS loading limit in lieu of the Colorado River Basin Salinity Control Forum Policy requirement as authorized in *UAC R317-2-4*.

The permit effluent limitations are:

Effluent Limitations					
Parameter	Maximum Monthly Avg	Maximum Weekly Avg	Daily Minimum	Daily Maximum	Yearly Maximum
Flow, MGD	2.2	NA	NA	3.0	NA
BOD_5, mg/L BOD_5 Min. % Removal	25 85	35 NA	NA NA	NA NA	NA NA
TSS, mg/L TSS Min. % Removal	25 85	35 NA	NA NA	NA NA	NA NA
E-Coli, No./100mL	126	157	NA	NA	NA
Ammonia, mg/L	10	NA	NA	16	NA
TRC, mg/L	0.056	NA	NA	0.076	NA
Oil & Grease, mg/L	NA	NA	NA	10	NA
Dissolved Oxygen, mg/L	NA	NA	5.0	NA	NA
pH, Standard Units	NA	NA	6.5	9.0	NA
TDS, mg/L	NA	NA	NA	1700	NA
TDS, (annual) tons[b]	NA	NA	NA	NA	7304
WET, Acute Biomonitoring	NA	NA	NA	NA	Pass at 100% Effluent

NA – Not Applicable

SELF-MONITORING AND REPORTING REQUIREMENTS

Self-monitoring requirements are shown in the table below. The permit will require reports to be submitted monthly on Discharge Monitoring Report (DMR) forms due 28 days after the end of the monitoring period. Lab sheets for biomonitoring must be attached to the biomonitoring DMR.

Self-Monitoring and Reporting Requirements[a]			
Parameter	Frequency	Sample Type	Units
Total Flow[c,d]	Continuous	Recorder	MGD
BOD_5, Influent[e] Effluent	2 x Weekly 2 x Weekly	Composite Composite	mg/L mg/L
TSS, Influent[e] Effluent	2 x Weekly 2 x Weekly	Composite Composite	mg/L mg/L
E-coli	2 x Weekly	Grab	No./100mL
Ammonia	2 x Weekly	Grab	mg/L
TRC	Daily	Grab	mg/L
WET, Acute Biomonitoring[f]	2 x Year	Composite	Pass/Fail
Oil & Grease	2 x Weekly	Visible	Yes/No
Oil & Grease[g]	Monthly	Grab	mg/L
Dissolved Oxygen	2 x Weekly	Grab	mg/L
pH	2 x Weekly	Grab	su
TDS	Monthly	Grab	mg/L
Metals[e, i], Influent Effluent	Yearly Yearly	Composite[h] Composite[h]	mg/L mg/L
Organic Toxics[j]	2nd & 4th year of permit	Grab	mg/L
Phosphorus	Quarterly	Grab	mg/L
CBOD	Quarterly	Grab	mg/L
Nitrate	Quarterly	Grab	mg/L
Nitrite	Quarterly	Grab	mg/L

a See Definitions, *Part VIII*, for definition of terms within the effluent limitations tables and the self-monitoring and reporting requirements tables.

b The measurement of TDS tons will be total accumulated during the calendar year. Beginning in January 1, of each year the total TDS tons will start at zero again.

c Flow measurements of influent/effluent volume shall be made in such a manner that the permittee can affirmatively demonstrate that representative values are being obtained.

d If the rate of discharge is controlled, the duration of that rate shall be reported also.

e For this constituent, in addition to monitoring the final discharge, influent samples shall be taken and analyzed at the same frequency as required in the discharge.

f Wet monitoring will be acute according to *Methods for Measuring the Acute Toxicity of Effluents and Receiving Waters to Freshwater and Marine Organisms. Fourth Edition. August 1993, EPA/600/4-90/027F* as per *40 CFR 136.3(a) TABLE 1A-LIST OF APPROVED BIOLOGICAL METHODS*, and the *Region VIII EPA NPDES Acute Test Conditions – Static Renewal Whole Effluent Toxicity Test (August, 1997)*. The permittee shall use Ceriodaphnia dubia the first 6 months and Pimephales promelas (fathead minnow) the next 6 month period. Each year the permittee will change the order the species so that the species are not tested in

the same half of the year each year.

g Monitoring and reporting the results of a laboratory analyzed sample for oil & grease is not required unless the visual sample produces a positive result.

h Samples of mercury can be taken as composite or grab.

i Metals samples shall conform to the requirements in the table titled "Metals Monitoring for Pretreatment Program" found in Part II.A.1.

j A total toxic organics (TTO) test shall be performed sometime during the 2nd and 4th year of the permit.

BIOSOLIDS

DESCRIPTION OF TREATMENT AND DISPOSAL

The solids (sewage sludge) at the PRWID are stabilized in primary and secondary anaerobic digesters with a hydraulic residence time of about 40 days and a temperature of 98° F (36.7° C). After digestion, the biosolids are transferred to one of two facultative lagoons for a period of one to three years for additional stabilization. After this time period, one of the two lagoons is allowed to dry out for approximately one year and the biosolids are scooped out with a front end loader, and loaded onto a dump truck. The biosolids are hauled to a local farm, and land applied at agronomic rates (based on nitrogen) to produce hay or grain for livestock feed.

In 2011 the PRWID disposed of 190 DMT of Class B biosolids to agricultural fields owned by Glen Wells for the production of sorghum for livestock feed. In the fall of 2012 Class B biosolids will once again be land applied to the Glens Wells property at agronomic rates for alfalfa.

FUTURE DISPOSAL METHODS

The PRWID plans to treat and dispose of their biosolids in the same basic manner for the next five years. The only changes that may be made, is whose property the biosolids are land applied on, and the type of cover crop grown on the property.

SELF-MONITORING REQUIREMENTS

Under *40 CFR 503.16(a)(1),* the self-monitoring requirements are based upon the amount of biosolids disposed per year and shall be monitored according to the chart below.

Minimum Frequency of Monitoring Based Upon Dry Metric Tons (DMT)	
Amount of Biosolids Produced Per Year	Monitoring Frequency
> 0 to < 290 DMT	Once Per Year
> 290 to < 1,500 DMT	Four Times Per Year

In 2011, the PRWID produced a total of 190 DMT of biosolids, therefore the PRWID was required to sample at least once. If the PRWID produces and disposes of more than 290 DMT of biosolids in one year, they will be required to sample four times a year.

BIOSOLIDS LIMITATIONS

Heavy Metals

Class B Requirements for Agriculture and Reclamation Sites
The intent of the heavy metals regulations of Tables 1, 2 and 3, of *40 CFR 503.13* is to ensure that heavy metals do not build up in the soil at farms, forest land, and land reclamation sites to the point where the heavy metals become phytotoxic to plants. The permittee will be required to produce an information sheet (see *Part III. D. 11.* of the permit) to be handed out to all people who are receiving and land applying Class B biosolids to farms, ranches, and land reclamation sites (if biosolids are only applied to land owned by the PRWID, the information sheet requirements are waived). If the biosolids are land applied according to the regulations of *40 CFR 503.13,* to any reasonable degree, the Class B biosolids will be able to be land applied year after year, to the same farms, ranches, and land reclamation sites without any deleterious effects to the environment.

Class B Requirements With Regards to Heavy Metals
If the biosolids are to be land applied to agricultural land, forest land, a public contact site or a reclamation site it must meet at all times:

> The maximum heavy metals listed in *Table 1* and the heavy metals loading rates in *Table 2*; or
>
> The maximum heavy metals in Table 1 and the monthly heavy metals concentrations in *Table 3*.
>
> If the biosolids do not meet these requirements they cannot be land applied.

40 CFR, 503.13, Tables 1, 2, and *3* of Heavy Metal Limitations

Heavy Metals	Table 1	Table 2	Table 3 (Considered Exceptional Quality)
All heavy metals concentrations shall be measured and reported	Daily Maximum mg/Kg a/b/c/	Cumulative Loading Rate Kg/Ha a/	Monthly Average Concentration mg/Kg a/b/c/d/
Total Arsenic	75	41	41
Total Cadmium	85	39	39
Total Copper	4300	1500	1500
Total Lead	840	300	300
Total Mercury	57	17	17

Total Molybdenum	75	N/A	N/A
Total Nickel	420	420	420
Total Selenium	100	100	100
Total Zinc	7500	2800	2800

a/ See Part VIII. of the permit for definition of terms.

b/ The limitations represent the maximum allowable levels of heavy metals in any biosolids intended for land application.

c/ Any violation of these limitations shall be reported in accordance with the requirements of *Part III .H., 1, 2, 3 and 4* of the permit.

d/ These limitations represent the maximum allowable levels of heavy metals based on an average of all samples taken during a 30-day period.

Pathogen Limitations

Class B Requirements for Agriculture and Land Reclamation Use
If biosolids are to be land applied for agriculture or land reclamation the solids need to be treated by a specific process to significantly reduce pathogens (PSRP). The PRWID may achieve Class B biosolids in one of two different ways with regards to pathogens:

1. Under *40 CFR 503.32 (b)(2),* the PRWID may test the biosolids and must meet a microbiological limit of less than 2,000,000 MPN of fecal coliform per gram for the biosolids to be considered Class B biosolids with respect to pathogens.

2. Under *40 CFR 503.32 (b)(3)* the PSRP may be accomplished through anaerobic digesters that have a minimum retention time of 15 days at 95° F (35° C) or 60 days at 68° F (20°C).

Vector Attraction Reduction
If the biosolids are land applied PRWID will be required to meet a method of vector attraction reduction under *40 CFR 503.33.* The PRWID needs to meet the vector attraction reduction requirement below.

Under *40 CFR 503.33(b)(1),* the solids need to be treated through anaerobic digestion for at least 15 days at a temperature of a least 35° C (95° F) with a 38% reduction of volatile solids.

Landfill Monitoring
Under *40 CFR 258,* the landfill monitoring requirements include a paint filter test to determine if the biosolids exhibit free liquid. If the biosolids do not pass a paint filter test, the biosolids cannot be disposed in the sanitary landfill *(40 CFR 258.28(c)(1).*

METALS MONITORING DATA
The PRWID was required to sample for metals at least once in 2011. The monitoring data shows

the metals met *Table 3* of *40 CFR 503.13*. Therefore the PRWID biosolids qualify as Exceptional Quality (EQ) with regards to metals.

The monitoring data is below.

Metals Monitoring Data 2011

Heavy Metals	PRWID 2011, Yearly Average, mg/Kg	PRWID 2011, Yearly Maximum, mg/Kg	*40 CFR 503.13*, Table 3, (Exceptional Quality) mg/Kg
Arsenic	15.3	15.3	41.0
Cadmium	2.12	2.12	39.0
Copper	444.0	444.0	1,500.0
Lead	55.4	55.4	300.0
Mercury	3.83	3.83	17.0
Molybdenum	6.96	6.96	75.0
Nickel	20.9	20.9	420.0
Selenium	13.1	13.1	36.0
Zinc	969.0	969.0	2,800.0

PATHOGEN MONITORING DATA The PRWID was not required to monitor the anaerobic biosolids for pathogens because PRWID met a PSRP. Therefore, there is not any monitoring data for the Class B biosolids. All biosolids land applied in 2011 met the Class B pathogen standards through anaerobic digestion.

REPORTING AND RECORD KEEPING REQUIREMENTS

Record keeping

The record keeping requirements from *40 CFR 503.17* are included under *Part III.H.* of the permit. The amount of time the records must be maintained are dependent on the quality of the biosolids in regards to the metals concentrations. If the biosolids continue to meet the Class A metals limitations of *Table 3 of 40 CFR 503.13*, and are sold or given away and land applied the records must be retained for a minimum of five years. If the biosolids do not meet Class A standards with regards to heavy metals, and meet Class B standards and are land applied, the records must be maintained perpetually. If the biosolids are disposed in a landfill the records must also retained for a minimum of five years.

Reporting

The PRWID must report annually as required in *40 CFR 503.18*. This report is to include the results of all monitoring performed in accordance with *Part III.C.* of the permit, information on management practices, biosolids treatment, and certifications. This report is due no later than **February 19** of each year. Each report is for the previous calendar year.

STORM WATER

STORM WATER REQUIREMENTS

The storm water requirements are based on the UPDES Multi-Sector General Permit for Storm Water Discharges for Industrial Activity, General Permit No. UTR000000 (MSGP). All sections of the MSGP that pertain to discharges from wastewater treatment plants have been included and sections which are redundant or do not pertain have been deleted.

The permit requires the preparation and implementation of a storm water pollution prevention plan for all areas within the confines of the plant. Elements of this plan are required to include: 1. The development of a pollution prevention team: 2. Development of drainage maps and materials stockpiles: 3. An inventory of exposed materials: 4. Spill reporting and response procedures: 5. A preventative maintenance program: 6. Employee training: 7. Certification that storm water discharges are not mixed with non-storm water discharges: 8. Compliance site evaluations and potential pollutant source identification, and: 9. Visual examinations of storm water discharges.

PRETREATMENT REQUIREMENTS

The permittee has not been designated for pretreatment program development because it does not meet conditions which necessitate a full program. The flow through the plant is less than five (5) MGD, there are no categorical industries discharging to the treatment facility, industrial discharges comprise less than 1 percent of the flow through the treatment facility, and there is no indication of pass through or interference with the operation of the treatment facility such as upsets or violations of the POTW's UPDES permit limits.

Although the permittee does not have to develop a State-approved pretreatment program, any wastewater discharges to the sanitary sewer are subject to Federal, State and local regulations. Pursuant to *Section 307* of the *Clean Water Act*, the permittee shall comply with all applicable Federal General Pretreatment Regulations promulgated, found in *40 CFR 403* and the State Pretreatment Requirements found in *UAC R317-8-8*.

An industrial waste survey (IWS) is required of the permittee as stated in Part II of the permit. The IWS is to assess the needs of the permittee regarding pretreatment assistance. The IWS is required to be submitted within sixty (60) days after the issuance of the permit. If an Industrial User begins to discharge or an existing Industrial User changes their discharge, the permittee must resubmit an IWS no later than sixty days prior to the introduction or change as stated in Part II of the permit.

It is recommended that the permittee perform an annual evaluation of the need to revise or develop technically based local limits for pollutants of concern, to implement the general and specific prohibitions *40 CFR, Part 403.5(a)* and *Part 403.5(b)*. This evaluation may indicate that present local limits are sufficiently protective, need to be revised or should be developed. It is required, as per *UAC R317-8-8.8(4)(c)*, that the permittee submit for review and public notice any local limits that are developed to the Division of Water Quality for review.

BIOMONITORING REQUIREMENTS

A nationwide effort to control toxic discharges where effluent toxicity is an existing or potential

concern is regulated in accordance with the *State of Utah Permitting and Enforcement Guidance Document for Whole Effluent Toxicity Control (biomonitoring)*. Authority to require effluent biomonitoring is provided in *Permit Conditions, UAC R317-8-4.2, Permit Provisions, UAC R317-8-5.3* and *Water Quality Standards, UAC R317-2-5* and *R317 -2-7.2*.

Since the permittee is a major municipal discharger, the renewal permit will require acute whole effluent toxicity (WET) testing and limits.

The permit will contain the standard requirements for accelerated testing upon failure of a WET test and a PTI (Preliminary Toxicity Investigation) and TRE (Toxicity Reduction Evaluation) as necessary.

The receiving stream water quality monitoring data indicate no impairment of the stream. Therefore, there will be no numerical toxicity limitation and no chronic testing required at this time.

PERMIT DURATION

It is recommended that this permit be effective for a duration of five (5) years.

Drafted by
Kim Shelley, Discharge
Mark Schmitz, Biosolids
Utah Division of Water Quality

PUBLIC NOTICE

Began: December 27, 2012
Ended: February 1, 2013
Public Noticed in the Sun Advocate.

No comments were received during the public comment period. Therefore, the permit and FSSOB are the same as the draft documents that were public noticed.

Utah Division of Water Quality
Statement of Basis
ADDENDUM
Wasteload Analysis and Antidegradation Level I Review - FINAL

Date: **December 18, 2012**

Prepared by: **Nicholas von Stackelberg, P.E.**
Water Quality Management Section

Facility: **Price River Water Improvement District Wastewater Treatment Plant, Wellington, UT**
UPDES No. UT0021814

Receiving water: **Price River (2B, 3C, 4)**

This addendum summarizes the wasteload analysis that was performed to determine water quality based effluent limits (WQBEL) for this discharge. Wasteload analyses are performed to determine point source effluent limitations necessary to maintain designated beneficial uses by evaluating projected effects of discharge concentrations on in-stream water quality. The wasteload analysis also takes into account downstream designated uses (UAC R317-2-8). Projected concentrations are compared to numeric water quality standards to determine acceptability. The numeric criteria in this wasteload analysis may be modified by narrative criteria and other conditions determined by staff of the Division of Water Quality.

Discharge
Outfall 001: Price River

The maximum daily design discharge is 8 MGD and the maximum monthly design discharge is 4 MGD for the facility. The facility has had steady operations for the past five years and only anticipates limited growth during the permit duration; therefore, a maximum daily discharge of 3.0 MGD and maximum monthly discharge of 2.2 MGD were used for the wasteload analysis.

Receiving Water
The receiving water for Outfall 001 is the Price River, which is tributary to the Green River, and the Colorado River.

Per UAC R317-2-13.1.b, the designated beneficial uses for the Price River from the confluence with the Green River to the Carbon Canal Diversion at Price City Golf Course are 2B, 3C, and 4.

- *Class 2B - Protected for infrequent primary contact recreation. Also protected for secondary contact recreation where there is a low likelihood of ingestion of water or a low degree of bodily contact with the water. Examples include, but are not limited to, wading, hunting, and fishing.*

- *Class 3C - Protected for nongame fish and other aquatic life, including the necessary aquatic organisms in their food chain.*

- *Class 4 - Protected for agricultural uses including irrigation of crops and stock watering.*

Typically, the critical flow for the wasteload analysis is considered the lowest stream flow for seven consecutive days with a ten year return frequency (7Q10). Due to a lack of flow records for the Price River downstream of the irrigation diversions, the 20th percentile of flow measurements from water quality monitoring conducted above the facility outfall was calculated to estimate the annual critical flow in the receiving water (14.0 cfs). Insufficient flow data was available to estimate seasonal low flow.

For chronic conditions, the critical low flow was simulated; for acute conditions, 50% of the critical low flow was simulated.

TMDL

A TMDL for total dissolved solids (TDS) was completed for this segment of the Price River (*Price River, San Rafael River, and Muddy Creek TMDLs for Total Dissolved Solids, West Colorado Watershed Management Unit, Utah; EPA Approval Date August 4, 2004*). A site specific standard was recommended for TDS. Per UAC R317-2-14 Table 2.14.1, a site specific standard of 1,700 mg/L applies to the Price River and tributaries from Soldier Creek to Carbon Canal Diversion.

Mixing Zone

The allowable mixing zone is 15 minutes of travel time for acute conditions, not to exceed 50% of stream width, and 2,500 feet for chronic conditions, per UAC R317-2-5. Water quality standards must be met at the end of the mixing zone.

Based on field observations of specific conductivity across the cross-section during the synoptic survey data collection, the discharge was fully mixed approximately 75 meters downstream of the discharge point. Therefore, the allowable mixing zone is 75 meters.

Parameters of Concern

The potential parameters of concern identified for the discharge/receiving water were total suspended solids (TSS), total dissolved solids (TDS), dissolved oxygen (DO), BOD_5, total phosphorus (TP), total nitrogen (TN), total ammonia (TAM), E. coli, pH, and total residual chlorine (TRC) as determined in consultation with the UPDES Permit Writer.

Water Quality Modeling

A QUAL2Kw model of the receiving water was built and calibrated under contract by Utah State University (USU). The model was calibrated to synoptic survey data collected in the summer of 2010 by USU and DWQ (8/30 to 9/1/2010). The model extends from immediately above the plant discharge to the crossing at Ridge Road (approximately 0.8 km).

Receiving water quality data was obtained from monitoring site 4992390 Price River above Price WWTP at Wellington Bridge. The average seasonal value was calculated for each constituent with available data in the receiving water.

For determining the receiving water criteria and limits due to ammonia toxicity, the effluent was assumed to have a pH of 7.3 for chronic conditions and 7.6 for acute conditions. Average seasonal temperatures were used for the effluent.

The calibrated model was used for determining WQBELs. Effluent concentrations were adjusted so that water quality standards were not exceeded at the end of the mixing zone. Where WQBELs exceeded secondary standards or categorical limits, the concentration in the model was set at the secondary standard or categorical limit.

The calibration model and the wasteload model are available for review by request.

WET Limits

The percent of effluent in the receiving water in a fully mixed condition, and acute and chronic dilution in a not fully mixed condition are calculated in the WLA in order to generate WET limits. The LC_{50} (lethal concentration, 50%) percent effluent for acute toxicity and the IC_{25} (inhibition concentration, 25%) percent effluent for chronic toxicity, as determined by the WET test, needs to be below the WET limits, as determined by the WLA. The WET limit for LC_{50} is typically 100% effluent and does not need to be determined by the WLA.

Table 1: WET Limits for IC_{25}

Season	Percent Effluent
Summer	18%
Fall	18%
Winter	18%
Spring	18%

Effluent Limits

The effect of the effluent on the DO in the receiving water was evaluated using the QUAL2Kw model. A DO sag downstream in the Price River resulting from the plant discharge was observed and predicted by the model due to decay of BOD in the effluent and benthic algal growth and decomposition resulting from nutrients in the effluent. However, the DO sag was not predicted to exceed water quality criteria and recovery was beginning to occur within the model extents. The benthic algae growth appeared to be limited by light as a result of high turbidity due to suspended solids. Therefore, limits beyond secondary standards are not required for DO and BOD_5 (Table 2).

QUAL2Kw rates, input and output for DO and nutrient related constituents are summarized in Appendix A.

A simple mixing analysis was conducted for constituents not related to DO and nutrients such as dissolved metals and TRC. The simple mixing analysis WQBELs are summarized in Appendix B.

Models and supporting documentation are available for review upon request.

Table 2: Water Quality Based Effluent Limits Summary

Effluent Constituent	Acute		Chronic	
	Standard	Limit	Standard	Limit
Flow (MGD)		3.0		2.2
Ammonia (mg/L)[1]	Varies[2]	16.0	Varies[3]	10.0
Dissolved Oxygen Min. (mg/L)	3.0	5.0	5.0	5.0
BOD_5 (mg/L)	None	35	None	25
TRC (mg/L)	0.019	0.076	0.011	0.056

1: Ammonia limit due to toxicity requirements.
2: Standard varies with pH.
3: Standard varies with pH and temperature.

Antidegradation Level I Review

The objective of the Level I ADR is to ensure the protection of existing uses, defined as the beneficial uses attained in the receiving water on or after November 28, 1975. No evidence is known that the existing uses deviate from the designated beneficial uses for the receiving water. Therefore, the beneficial uses will be protected if the discharge remains below the WQBELs presented in this wasteload.

A Level II Antidegradation Review (ADR) is not required for this discharge, as pollutant concentration and load will not increase under this permit renewal.

WLA Document: *price_potw_wla_2012_final.docx*
QUAL2Kw Calibration Model: *Qual2kw Price Calibration 1. 1.xls*
QUAL2Kw Wasteload Model: *price_potw_wla_2012.xlsm*

WASTELOAD ANALYSIS [WLA] Date: 12/18/2012
Appendix A: QUAL2Kw Analysis Results

DiscRarging Facility:	Price Water Improvement District WWTP		
UPDES No:	UT-0021814		
Permit Flow [MGD]:	3.00	Maximum Daily Flow	
	2.20	Maximum Monthly Flow	
Receiving Water:	Price River		
Stream Classification:	2B, 3C, 4		
Stream Flows [cfs]:	14.00	Summer (July-Sept)	Critical Low Flow
	14.00	Fall (Oct-Dec)	
	14.00	Winter (Jan-Mar)	
	14.00	Spring (Apr-June)	
Acute River Width:	50%		
Chronic River Width:	100%		

Modeling Information

A QUAL2Kw model was used to determine these effluent limits.

Model Inputs

The following is upstream and discharge information that was utilized as inputs for the analysis.

Headwater/Upstream Information	Summer	Fall	Winter	Spring
Flow (cfs)	14.0	14.0	14.0	14.0
Temperature (deg C)	16.4	4.6	6.0	9.6
Specific Conductance (µmhos)	1943	2242	1137	955
Inorganic Suspended Solids (mg/L)	265.2	33.7	304.8	309.8
Dissolved Oxygen (mg/L)	7.2	11.9	9.6	9.2
$CBOD_5$ (mg/L)	3.7	3.7	3.7	3.7
Organic Nitrogen (mg/L)	0.400	0.400	0.400	0.400
NH4-Nitrogen (mg/L)	0.088	0.025	0.042	0.042
NO3-Nitrogen (mg/L)	0.925	0.647	0.280	0.203
Organic Phosphorus (mg/L)	0.242	0.023	0.261	0.239
Inorganic Ortho-Phosphorus (mg/L)	0.015	0.010	0.010	0.013
Phytoplankton (µg/L)	7.000	7.000	7.000	7.000
Detritus [POM] (mg/L)	66.3	8.4	76.2	77.5
Alkalinity (mg/L)	219	219	219	219
pH	8.3	8.3	8.5	8.6

Discharge Information - Chronic	Summer	Fall	Winter	Spring
Flow (mgd)	2.2			
Temperature (deg C)	21.0			
Specific Conductance (µmhos)	1795			
Inorganic Suspended Solids (mg/L)	6.1			
Dissolved Oxygen (mg/L)	5.0			
$CBOD_5$ (mg/L)	25.0			
Organic Nitrogen (mg/L)	5.000			
NH4-Nitrogen (mg/L)	10.000			
NO3-Nitrogen (mg/L)	12.050			
Organic Phosphorus (mg/L)	5.000			
Inorganic Ortho-Phosphorus (mg/L)	5.000			
Phytoplankton (µg/L)	11.000			
Detritus [POM] (mg/L)	0.0			
Alkalinity (mg/L)	208			
pH	7.3			

Discharge Information - Acute	Summer	Fall	Winter	Spring
Flow (mgd)	3.0			
Temperature (deg C)	21.0			
Specific Conductance (μmhos)	1795			
Inorganic Suspended Solids (mg/L)	6.1			
Dissolved Oxygen (mg/L)	5.0			
$CBOD_5$ (mg/L)	35.0			
Organic Nitrogen (mg/L)	10.000			
NH4-Nitrogen (mg/L)	16.000			
NO3-Nitrogen (mg/L)	12.050			
Organic Phosphorus (mg/L)	5.000			
Inorganic Ortho-Phosphorus (mg/L)	5.000			
Phytoplankton (μg/L)	11.000			
Detritus [POM] (mg/L)	0.0			
Alkalinity (mg/L)	208			
pH	7.6			

All model numerical inputs, intermediate calculations, outputs and graphs are available for discussion, inspection and copy at the Division of Water Quality.

Effluent Limitations

Current State water quality standards are required to be met under a variety of conditions including in-stream flows targeted to the 7-day, 10-year low flow (R317-2-9).

Other conditions used in the modeling effort reflect the environmental conditions expected at low stream flows.

Effluent Limitations based upon Water Quality Standards for DO and Ammonia Toxicity

In-stream criteria of downstream segments for Dissolved Oxygen and Ammonia will be met with an effluent limitation as follows:

Chronic	Standard	Summer	Fall	Winter	Spring
Flow (MGD)	N/A	2.2			
Organic Nitrogen (mg/L)	N/A	None			
NH4-Nitrogen (mg/L)	Varies	10.0			
NO3-Nitrogen (mg/L)	N/A	None			
Inorganic Phosphorus (mg/L)	N/A	None			
$CBOD_5$ (mg/L)	N/A	25.0			
Dissolved Oxygen [30-day Ave] (mg/L)	5.0	5.0			

Acute	Standard	Summer	Fall	Winter	Spring
Flow (cfs)	N/A	3.0			
Organic Nitrogen (mg/L)	N/A	None			
NH4-Nitrogen (mg/L)	Varies	16.0			
NO3-Nitrogen (mg/L)	N/A	None			
Inorganic Phosphorus (mg/L)	N/A	None			
$CBOD_5$ (mg/L)	N/A	35.0			
Dissolved Oxygen [Minimum] (mg/L)	3.0	5.0			

Summary Comments

The mathematical modeling and best professional judgement indicate that violations of receiving water beneficial uses with their associated water quality standards, including important down-stream segments, will not occur for the evaluated parameters of concern as discussed above if the effluent limitations indicated above are met.

Coefficients and Other Model Information

Parameter	*Value*	*Units*
Stoichiometry:		
Carbon	40	gC
Nitrogen	7.2	gN
Phosphorus	1	gP
Dry weight	100	gD
Chlorophyll	1	gA
Inorganic suspended solids:		
Settling velocity	0.2	m/d
Oxygen:		
Reaeration model	USGS(pool-riffle)	
Temp correction	1.024	
Reaeration wind effect	None	
O2 for carbon oxidation	2.69	gO2/gC
O2 for NH4 nitrification	4.57	gO2/gN
Oxygen inhib model CBOD oxidation	Exponential	
Oxygen inhib parameter CBO D oxidation	0.60	L/mgO2
Oxygen inhib model nitrification	Exponential	
Oxygen inhib parameter nitrifi cation	0.60	L/mgO2
Oxygen enhance model denitrification	Exponential	
Oxygen enhance parameter denitrification	0.60	L/mgO2
Oxygen inhib model phyto resp	Exponential	
Oxygen inhib parameter phy to resp	0.60	L/mgO2
Oxygen enhance model bot alg resp	Exponential	
Oxygen enhance parameter bot alg resp	0.60	L/mgO2
Slow CBOD:		
Hydrolysis rate	0	/d
Temp correction	1.047	
Oxidation rate	0.103	/d
Temp correction	1.047	
Fast CBOD:		
Oxidation rate	10	/d
Temp correction	1.047	
Organic N:		
Hydrolysis	0.2532525	/d
Temp correction	1.07	
Settling velocity	0.186698	m/d
Ammonium:		
Nitrification	0.052449	/d
Temp correction	1.07	
Nitrate:		
Denitrification	0.3067175	/d
Temp correction	1.07	
Sed denitrification transfer coeff	0.74405	m/d
Temp correction	1.07	
Organic P:		
Hydrolysis	0.1347925	/d
Temp correction	1.07	
Settling velocity	0.132374	m/d
Inorganic P:		
Settling velocity	1.9476	m/d
Sed P oxygen attenuation hal f sat constant	0.10486	mgO2/L

Phytoplankton:		
Max Growth rate	2.424195	/d
Temp correction	1.07	
Respiration rate	0.2453945	/d
Temp correction	1.07	
Death rate	0.07159	/d
Temp correction	1	
Nitrogen half sat constant	15	ugN/L
Phosphorus half sat constant	2	ugP/L
Inorganic carbon half sat constant	1.30E-05	moles/L
Phytoplankton use HCO3- as substrate	Yes	
Light model	Smith	
Light constant	57.6	langleys/d
Ammonia preference	16.82115	ugN/L
Settling velocity	0.098591	m/d
Bottom Plants:		
Growth model	Zero-order	
Max Growth rate	15.75627	gD/m2/d or /d
Temp correction	1.07	
First-order model carrying capacity	100	gD/m2
Basal respiration rate	0.0691094	/d
Photo-respiration rate parameter	0.01	unitless
Temp correction	1.07	
Excretion rate	0.3327	/d
Temp correction	1.07	
Death rate	1.66875	/d
Temp correction	1.07	
External nitrogen half sat constant	350.448	ugN/L
External phosphorus half sat constant	67.2535	ugP/L
Inorganic carbon half sat constant	7.41E-05	moles/L
Bottom algae use HCO3- as substrate	Yes	
Light model	Smith	
Light constant	68.6698	mgO^2/L
Ammonia preference	17.5728	ugN/L
Subsistence quota for nitrogen	0.8808192	mgN/gD
Subsistence quota for phosphorus	0.0874835	mgP/gD
Maximum uptake rate for nitrogen	743.668	mgN/gD/d
Maximum uptake rate for phosphorus	144.8225	mgP/gD/d
Internal nitrogen half sat ratio	1.597312	
Internal phosphorus half sat ratio	4.9713625	
Nitrogen uptake water column fraction	1	
Phosphorus uptake water column fraction	1	
Detritus (POM):		
Dissolution rate	0.279779	/d
Temp correction	1.07	
Settling velocity	0.0739985	m/d
pH:		
Partial pressure of carbon dioxide	370	ppm

Atmospheric Inputs:	Summer	Fall	Winter	Spring
Max. Air Temperature, F	88.2	51.8	42.9	72.4
Min. Air Temperature, F	50.5	17.7	14.1	36.2
Dew Point, Temp., F	54.5	29.9	26.0	44.3
Wind, ft./sec. @ 21 ft.	6.6	5.8	5.8	8.4
Cloud Cover, %	0.1	0.1	0.1	0.1

Other Inputs:		
Bottom Algae Coverage	100.0%	
Bottom SOD Coverage	100.0%	
Prescribed SOD	0.1	gO2/m2/d

WASTELOAD ANALYSIS [WLA] Date: 12/18/2012

Appendix B: Simple Mixing Analysis Results

Discharging Facility:	Price Water Improvement District WWTP		
UPDES No:	UT-0021814		
Permit Flow [MGD]:	3.00	Maximum Daily Flow	
	2.20	Maximum Monthly Flow	
Receiving Water:	Price River		
Stream Classification:	2B, 3C, 4		
Stream Flows [cfs]:	14.00	Summer (July-Sept)	Critical Low Flow
	14.00	Fall (Oct-Dec)	
	14.00	Winter (Jan-Mar)	
	14.00	Spring (Apr-June)	
Acute River Width:	50%		
Chronic River Width:	100%		

Modeling Information

A simple mixing analysis was used to determine these effluent limits.

All model numerical inputs, intermediate calculations, outputs and graphs are available for discussion, inspection and copy at the Division of Water Quality.

Effluent Limitations

Current State water quality standards are required to be met under a variety of conditions including in-stream flows targeted to the 7-day, 10-year low flow (R317-2-9).

Other conditions used in the modeling effort reflect the environmental conditions expected at low stream flows.

Effluent Limitations for Protection of Recreation (Class 2B Waters)

Parameter	Maximum Concentration
Physical	
pH Minimum	6.5
pH Maximum	9.0
Bacteriological	
E. coli (30 Day Geometric Mean)	206 (#/100 mL)
E. coli (Maximum)	668 (#/100 mL)

Effluent Limitations for Protection of Aquatic Wildlife (Class 3C Waters)

Parameter	Maximum Concentration
Physical	
Temperature	Max (deg C)
Summer	26.4
Fall	14.7
Winter	16.0
Spring	19.7

Inorganics	Chronic Standard (4 Day Average)			Acute Standard (1 Hour Average)		
	Standard	Limit	Unit	Standard	Limit	Unit
Total Residual Chlorine (TRC)	0.011	0.056	mg/L	0.019	0.048	mg/L
Phenol				0.010	0.018	mg/L
Hydrogen Sulfide (Undissociated)				0.002	0.004	mg/L

Dissolved Metals

Parameter	Chronic Standard (4 Day Average) Standard	Limit	Unit	Acute Standard (1 Hour Average) Standard	Limit	Unit
Aluminum	87.0	265.9	µg/L	750.0	1315.5	µg/L
Arsenic	150.0	458.5	µg/L	340.0	596.4	µg/L
Cadmium	0.6	2.0	µg/L	7.7	13.6	µg/L
Chromium VI	11.0	33.6	µg/L	16.0	28.1	µg/L
Chromium III	230.7	705.0	µg/L	1773.3	3110.5	µg/L
Copper	29.3	89.5	µg/L	49.6	87.0	µg/L
Cyanide	22.0	67.2	µg/L	5.2	9.1	µg/L
Iron				1000.0	1754.1	µg/L
Lead	10.9	33.5	µg/L	280.8	492.6	µg/L
Mercury	0.012	0.037	µg/L	2.4	4.2	µg/L
Nickel	168.0	513.6	µg/L	1512.9	2653.7	µg/L
Selenium	4.6	14.1	µg/L	18.4	32.3	µg/L
Silver				34.9	61.2	µg/L
Tributylin	0.072	0.220	µg/L	0.46	0.81	µg/L
Zinc	382.4	1168.8	µg/L	379.3	665.3	µg/L

Based upon a Hardness of 400 mg/l as $CaCO_3$
Ambient concentration assumed 1/2 of water quality standard

Organics [Pesticides]

Parameter	Chronic Standard (4 Day Average) Concentration			Acute Standard (1 Hour Average) Concentration		
Aldrin				1.500	2.631	µg/L
Chlordane	0.0043	0.013	µg/L	1.200	2.105	µg/L
DDT, DDE	0.001	0.003	µg/L	0.550	0.965	µg/L
Diazinon	0.17	0.520	µg/L	0.17	0.298	µg/L
Dieldrin	0.0056	0.017	µg/L	0.240	0.421	µg/L
Endosulfan, a & b	0.056	0.171	µg/L	0.110	0.193	µg/L
Endrin	0.036	0.110	µg/L	0.086	0.151	µg/L
Heptachlor & H. epoxide	0.0038	0.012	µg/L	0.260	0.456	µg/L
Lindane	0.08	0.245	µg/L	1.000	1.754	µg/L
Methoxychlor				0.030	0.053	µg/L
Mirex				0.001	0.002	µg/L
Nonylphenol	6.6	20.173	µg/L	28.0	49.113	µg/L
Parathion	0.0130	0.040	µg/L	0.066	0.116	µg/L
PCB's	0.014	0.043	µg/L			
Pentachlorophenol	15.00	45.848	µg/L	19.000	33.327	µg/L
Toxephene	0.0002	0.001	µg/L	0.730	1.280	µg/L

Radiological

Parameter	Maximum Concentration
Gross Alpha	15 pCi/L

Effluent Limitation for Protection of Agriculture (Class 4 Waters)

Parameter	Maximum Concentration Standard	Limit	Unit	
Total Dissolved Solids	1700	1700	mg/L	Site specific standard
Boron	75	229	µg/L	
Arsenic	100	306	µg/L	
Cadmium	10	31	µg/L	
Chromium	100	306	µg/L	
Copper	200	611	µg/L	
Lead	100	306	µg/L	
Selenium	50	153	µg/L	
Gross Alpha	15	46	pCi/L	

	FLOW		PH EFFLUENT			COLIFORM						TSS				BOD				TDS	AMMONIA	DO
						FECAL		TOTAL		E.COLI			EFFLUENT				EFFLUENT					
DMR MONTH	30 DAY AVG	DAILY MAX	DAILY MIN	DAILY MAX	TRC EFF	7 DAY MAX	30 DAY AVG	7 DAY MAX	30 DAY AVG	7 DAY MAX	30 DAY AVE	INFLUENT	30 DAY AVG	7 DAY MAX	REMOVAL	INFLUENT	30 DAY AVG	7 DAY MAX	REMOVAL	DAILY MAX	DAILY MAX	DAILY MIN
			6.5	9		200	250	2000	2500	126	158		25	35	85		25	35	85			
May-07	1.8	2	6.9	7.2	0	2.0	2.0	72.9	224.5			392.1	8.9	11.5	97.3	262.4	8.4	11.5	96.51	1210	3	6.7
Jun-07	1.8	2	6.8	7.2	0	2.8	4.7	270.7	409.9			332.8	8.6	10.5	97.4	195.5	7.7	9	92.32	1200	2.2	6.4
Jul-07	1.9	2.2	6.8	7.2	0	2.3	3.7	101.7	167.5			244.4	8.5	9	95.8	137.1	6.6	9	94.22	1230	2.2	6.3
Aug-07	1.9	2.1	6.9	7.2	0	2.0	2.0	53.5	273.9			187.7	10.1	12	94.1	111.9	9.3	10.5	91.42	1220	1.7	6
Sep-07	1.8	2	6.8	7.2	0	2.5	5.0	281.4	530.3			276.6	13.3	16	95.0	145.5	8.7	10.5	93.72	1180	0.4	6.1
Oct-07	1.8	1.9	6.6	7.2	0	2.7	4.5	197.8	315.0			253.8	13.56	18.5	94.7	174.6	8.9	12	94.26	1190	0.5	6
Nov-07	1.8	1.9	6.9	7.7	0	2.0	2.0	334.3	669.7			212.4	15.5	17.5	92.6	164.8	10.5	11.5	92.24	1180	0.6	6.7
Dec-07	1.8	2	6.7	7.2	0					1.4	2.0	304.6	11.4	12	96.0	212.9	8.8	10.5	95.13	1070	1.2	7.2
Jan-08	1.8	2.1	6.7	7.2	0					1.6	2.0	233.0	9.6	10.5	94.9	158.1	7.5	10	94.84	1180	2.1	7.4
Feb-08	1.9	2	6.8	7.2	0					3.3	7.1	302.8	9.8	11	96.6	169.1	8	10.5	94.91	1260	4.9	6.8
Mar-08	1.8	2	6.9	7.2	0					2.7	7.5	332.3	8.8	10	97.3	171.1	7	8	95.62	1190	10.9	7.4
Apr-08	1.7	2	6.8	7.2	0					1.8	10.4	343.8	6.9	9.5	97.8	197.6	8.5	11	95.27	1160	13.5	6.8
May-08	1.8	2	6.8	7.2	0					1.3	2.4	253.3	7.1	7.5	95.3	169	7	8	95.16	1020	7.7	6.7
Jun-08	1.8	2	6.8	7.2	0.02					11.6	20.0	331.8	11.5	15.5	96.5	200.8	8.4	8.5	95.2	1260	0.07	6.6
Jul-08	59.7	1.9	6.8	7.1	0.01					19.0	23.2	248.6	10.4	12.5	95.4	178.5	7.5	8.5	95.7	1200	<.4	7.6
Aug-08	1.9	2.1	6.6	7.2	0.05					5.7	14.3	232.8	6.8	11.5	96.9	187.8	6.3	8.5	95.96	1220	2.1	7
Sep-08	1.9	2.2	6.9	7.2	0.04					2.7	4.6	263.6	7.4	9	96.8	131	7	7.5	94.49	1190	3.3	7.3
Oct-08	1.8	2.3	6.7	7.2	0.02					4.2	14.0	258.6	7.3	10	96.9	154.6	6.6	8.5	95.49	1240	1.4	7.6
Nov-08	1.8	2.2	6.8	7.2	0.02					3.2	9.5	331.8	7.9	9	97.6	178.9	5.9	7	96.55	1170	3.3	7.9
Dec-08	1.8	2	6.7	7.1	0.02					1.3	1.7	353.5	8.8	10.5	97.3	198.4	7	11.5	96.28	1110	2.6	8
Jan-09	1.8	1.9	6.7	7.2	0.05					1.2	3.5	306.5	8.7	10	97.0	202.8	8.6	10.5	95.51	997	6	8.3
Feb-09	1.8	1.9	6.8	7.1	0					1.2	2.0	218.5	7.6	9.5	96.4	160.1	8.4	9.5	94.71	1160	5.2	8.2
Mar-09	1.7	2.1	6.8	7.2	0.03					2.1	11.6	340.3	7.3	8	97.0	176.8	8.5	10.5	95.16	1070	12.6	8.1
Apr-09	1.7	1.9	6.8	7.2	0.04					4.9	7.2	242.0	7.9	9	96.7	166.3	8.6	9	94.81	1060	10.7	8.1
May-09	1.8	2.1	6.7	7.2	0.03					4.4	11.0	261.0	10.8	16	95.9	161.7	7.5	10	95.01	1.2	2.8	8
Jun-09	1.8	1	6.9	7.1	0.04					29.0	37.0	240.6	13.5	15	94.3	154.3	10.4	12.5	93.17	1290	9	6.8
Jul-09	1	1	6.9	7.3	0.07					13.9	32.9	216.5	13.6	17	93.8	151.3	9.6	14	93.67	1290	8.5	7.4
Aug-09	1	1	6.8	7.2	0.06					29.8	50.7	233.2	13.8	20.5	93.8	145.8	9.4	12.5	93.43	1190	8.1	7.5
Sep-09	1	1	6.9	7.2	0.05					11.4	20.4	246.5	13.1	13.5	94.6	139.8	11.4	13.5	91.71	1220	4.6	7.3
Oct-09	1.7	2	6.7	7.2	0.03					2.8	3.5	293.0	10.7	14	96.3	157.2	7.7	10.5	95.03	1160	5	7.8
Nov-09	1.7	2.1	6.6	7.2	0.04					2.6	10.6	234.5	7.4	8.5	96.8	127.3	5.4	6	95.59	1080	3.6	7.7
Dec-09	1.7	1.8	6.5	6.8	0.04					11.4	18.2	296.3	6.1	8	97.9	182.6	5	5	96.92	1030	5.2	7.8
Jan-10	1.6	1.7	6.8	7.2	0.03					10.8	39.2	261.0	8	11.5	97.0	163.2	7.1	8.5	95.64	NODI=X	9.7	8
Feb-10	1.6	1.8	6.8	7.1	0.05					14.7	174.6	335.0	7.8	9	96.9	214.4	7.9	9.5	96.34	1090	14.9	8.2

Mar-10	1.7	2	6.8	7.2	0.03	1.0	1.0	303.8	6	6.5	97.9	182.6	8.4	9	95.32	1180	10.6	8.1
Apr-10	1.6	1.8	6.9	7.1	0.02	1.1	1.4	299.1	8.9	15	96.9	216.6	9.1	16	95.2	1150	16.3	7.4
May-10	1.7	1.9	6.7	7.1	0	1.9	7.7	304.7	11.7	15	96.0	191.9	7.9	10	95.65	1180	8.5	7.4
Jun-10	1.7	1.9	6.7	7.8	0.06	3.2	5.1	302.8	12.4	23	96.1	190.8	7.1	8	96.2	1230	5.6	7.4
Jul-10	1.8	2.1	6.8	7.1	0.07	1.9	2.4	337.2	9.9	11	96.8	181.9	6.3	7	96.27	1190	3.2	7.2
Aug-10	1.8	2	6.8	7.2	0.1	11.1	18.4	287.4	14.4	37	93.3	170.7	6.3	10.5	95.56	1140	9	6.9
Sep-10	1.8	2.1	6.5	7.1	0.05	7.7	27.3	272.8	8.9	9.5	96.6	169.1	5.8	7	96.55	1140	10	7.2
Oct-10	1.8	2.4	6.7	7.2	0.06	5.5	25.7	384.0	11.3	16	96.0	213.3	7	9.5	96.08	1100	2.7	7
Nov-10	1.7	1.8	6.9	7.2	0.04	1.1	1.4	444.1	9.8	12.5	95.8	254.9	5	5	97.19	1190	9.6	7.4
Dec-10	1.7	2.6	6.8	7.1	0.03	1.0	1.0	313.1	9.6	13	96.4	197.9	6.5	7.5	96.77	1170	13.1	7.6
Jan-11	1.7	2.2	6.8	7.2	0.08	1.1	1.4	507.0	11.3	13	97.4	318	9.1	9.1	96.99	1200	15.3	7.9
Feb-11	47.3	1.7	6.8	7.2	0.07	2.0	3.7	402.5	10	11	96.8	214.9	9.6	11	94.75	1170	15.2	8.1
Mar-11	1.6	1.8	6.8	7.1	0.09	1.2	1.4	629.3	7.4	9.5	98.2	312.9	6.9	9	97.42	1170	14.5	7
Apr-11	1.7	1.9	6.8	7.2	0.05	1.6	5.8	312.5	8.8	19.5	97.4	205.8	11.2	16.5	94.44	1160	15.5	5.2
May-11	1.8	2.5	6.7	7.5	0.05	4.5	162.5	317.3	12	20.5	95.4	202.6	14.3	25	92.21	1300	18.7	5.5
Jun-11	1.9	2.5	6.7	7.6	0.07	1.0	1.0	369.3	6.8	7.5	97.2	200.4	7.3	8.5	95.81	1300	12.4	5.1
Jul-11	61.9	2.5	6.6	7.1	0.06	1.3	19.3	240.5	9.2	23.5	95.1	131.2	7.4	11	93.88	NODI=9	4.1	6.8
Aug-11	60.7	2.2	6.7	7.2	0.06	4.9	5.9	330.5	11.1	16.5	96.5	161.4	7.8	10.5	95.22	1380	6	6.2
Sep-11	1.9	2.1	6.7	7.2	0.04	2.1	4.0	297.5	7.1	9	95.3	148.9	5.3	5.5	95.54	1290	6.7	7
Oct-11	60.1	2.7	6.5	7.2	0.04	3.8	8.5	375.7	6	7.5	97.9	193.2	5.7	8	96.1	1460	1.2	7.3
Nov-11	1.8	2	6.6	7	0.04	4.8	6.9	289.1	5.1	7	97.6	188.6	5	5	96.34	1280	0.8	7.6
Dec-11	1.7	2	6.7	7.2	0.04	3.3	9.9	286.5	5.2	7	97.8	329.8	5.3	6	97.69	1150	2.6	6.8
Jan-12	1.7	2	6.5	7	0.09	1.0	1.0	195.0	6.4	8	95.7	136.9	7.4	11	93.89	1070	4	8.1
Feb-12	1.7	1.8	6.8	7.2	0.09	1.0	1.0	323.4	6.1	7.5	97.1	228.1	5.5	7	96.75	1100	8	8.5
Mar-12	1.6	1.8	6.7	7.6	0.06	13.8	809.9	260.0	6.2	10	97.0	185	9.4	21	95.02	1040	21	7.4
Apr-12	1.6	1.8	6.8	7.2	0.06	1.1	1.4	255.3	5.4	6	97.8	202.9	6.8	13	96.7	1090	15.1	8.3
May-12	1.8	1.9	6.7	7.1	0.04	1.1	1.7	232.5	5.6	7	96.3	171.3	6	8	96.29	1080	7.8	7.9
Jun-12	1.8	2	6.6	7.2	0.05	6.9	33.5	193.5	6.4	8	95.3	131.1	7.4	11	94.11	1210	2.3	7.6

RED INDICATES AN EFFLUENT VIOLATION