



Utah Division of Solid & Hazardous Waste



USED OIL TRANSPORTER PERMIT

Permittee Name: Washakie Renewable Energy Oil Recyclers

Permittee Mailing Address: 3950 South 700 East, Suite 100
Salt Lake City, UT 84107

Permittee Phone Number: (435) 866-2292

Permittee Contact: Shannon Muir, Facility Manager
(435) 225-5866
Email: Shannon.muir@wreoilrecyclers.com

Facility Address: 1474 West 1500 South
Woods Cross, UT 84087

Facility Contact: Shannon Muir, Facility Manager

Type of Permit: Used Oil Transporter Permit

Permit #: UOP-0**XXX**

EPA ID #: UTR000012898

Signature: _____ Date Issued: _____

Scott T. Anderson, Director
Division of Solid and Hazardous Waste

I.A. Operations

- I.A.1 Washakie Renewable Energy Oil Recyclers (hereafter also referred to as “Permittee”) is hereby authorized to operate as a Used Oil Transporter in accordance with all applicable requirements of R315-15 of the Utah Administrative Code and of the Used Oil Management Act (the Act) 19-6-701 et. seq., Utah Code Annotated and this Permit.
- I.A.2 This Permit shall be effective for ten years in accordance with R315-15-15 of the Utah Administrative Code. This Permit shall be reviewed by the Director five years after the Permit issuance or when the Director determines the Permit requires review.
- I.A.3 Attachments incorporated by reference are enforceable conditions of this Permit, as are documents incorporated by reference into the attachments. Language in this Permit supersedes any conflicting language in the attachments or documents incorporated into the attachments.

I.B. Permit Revocation

- I.B.1 Violation of any permit condition or failure to comply (Is there a difference between “violation” and “failure to comply?”) with any provision of the applicable statutes and rules shall be grounds for imposing statutory sanctions, including revocation of the permit. The Director shall notify the Permittee in writing of his intent to revoke this Permit.

I.C. Permit Modification

- I.C.1. The Permittee may request modifications of this Permit by submitting a written permit modification request to the Director. If the Director determines the modification request is substantive, a public hearing, a 15-day public comment period or both may be required before the modification request is approved. Implementing a modification prior to the Director’s written approval constitutes a violation of this Permit and may be grounds for enforcement action or permit revocation.
- I.C.2. The Director may modify this Permit as necessary to protect human health and the environment or because of statutory or regulatory changes.

I.D. Spill Prevention

- I.D.1 The Permittee shall maintain and operate all used oil transportation vehicles and associated equipment to minimize the possibility of fire, explosion or sudden or non-sudden release of used oil to air, ground, soil, surface and groundwater and sewer systems which could threaten human health and the environment.

I.E. Record Retention

- I.E.1. The Permittee shall maintain all applicable used oil records required by R315-15 of the Utah Administrative Code and this Permit at the Permittee's facility located at 1474 West 1500 South, Woods Cross, UT 84087.
- I.E.2. All records shall be readily accessible for inspection by Division representatives for a minimum of three years. Records may be in a hard copy or electronic format.

I.F. Tracking

- I.F.1. The Permittee shall document the volume of used oil collected at each location and transported by the Permittee.
- I.F.2. Used oil records for pickups shall document the transporter's name, address, EPA identification number, the name and EPA identification number (where applicable) of the generator or used oil handler from whom the oil was collected, date and time of acceptance and signatures of both the transporter and authorized representative of the generator or handler from whom the oil was obtained.
- I.F.3. Used oil records for deliveries shall document the transporter's name, address, EPA identification number, the name and EPA identification number (where applicable) of the burner or used oil handler to whom the oil was delivered, date and time of delivery and signatures of both the transporter and authorized representative of the burner or used oil handler to whom the oil was delivered.
- I.F.4. The halogen content shall be documented on the used oil record/bill of lading at each used oil collection location prior to loading for transportation.
- I.F.5. Oil which may contain PCBs shall have verified analytical results attached to the used oil collection records prior to transportation.

I.G. Analysis Plan

- I.G.1 The Permittee shall follow all sampling and analytical procedures in Condition II.D when conducting used oil sampling and analytical testing to meet the requirements of R315-15 of the Utah Administrative Code and this Permit.

I.H. Prohibited Waste

- I.H.1. Used oil that has been mixed with hazardous waste as defined by R315-1 and R315-2 of the Utah Administrative Code or PCBs as defined by R315-301-2(53) of the Utah Administrative Code shall no longer be managed as used oil and shall be subject to applicable hazardous waste and PCB-contaminated waste rules.
- I.H.2. Used oil shall not be stored in tanks, containers or storage units that previously stored hazardous waste unless these tanks, containers and storage units have been cleaned in accordance with R315-2-7 of the Utah Administrative Code.

I.H.3 The Permittee shall not place, manage, discard or otherwise dispose of used oil in any manner in accordance with R315-15-1.3 of the Utah Administrative Code.

I.I. Waste Disposal

I.I.1. The Permittee shall document and maintain records showing proper characterization, handling and disposal for all used oil related waste, including oily wastewater.

II.I.2. The Permittee shall properly characterize the used oil related waste to determine if the waste is hazardous or non-hazardous in accordance with R315-15-8 of the Utah Administrative Code. All wastes generated during used oil operations shall be handled according to this Permit and R315-15 of the Utah Administrative Code. The wastes shall be taken to an appropriate facility permitted to handle the type of waste generated.

I.J. Used Oil Storage

I.J.1 The Permittee shall not store used oil longer than 24 hours without first obtaining a transfer facility or processor permit for that storage location. This includes storage on vehicles.

I.K. Emergency Controls and Spill Plan

I.K.1. The Permittee shall take all reasonable steps to minimize releases to the environment and shall carry out such measures as are necessary to protect human health and the environment.

I.K.2. In the event of a release of used oil, the Permittee shall immediately take appropriate actions to comply with the Emergency Controls required by R315-15-9 of the Utah Administrative Code, this Permit and the Permittee's Emergency Spill Plan in Attachment 1.

I.K.3. It shall not constitute a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the Permittee's business activity in order to maintain compliance with the conditions of this Permit and attachments.

I.K.4. The Permittee shall properly characterize waste generated during the spill cleanup to ascertain if the waste is hazardous or non-hazardous in accordance with R315-15-8 of the Utah Administrative Code.

I.K.5. The Permittee shall maintain analytical and disposal records for all disposed wastes for a minimum of three years.

I.L. Liability and Financial Assurance Requirements

- I.L.1. The Permittee shall procure and maintain general liability and sudden used oil third-party environmental pollution liability coverage for any liability resulting from the Permittee's operations as required by R315-15-10 of the Utah Administrative Code.
- I.L.2. The Permittee shall provide documentation of financial responsibility, environmental pollution legal liability and general liability coverage annually to the Director for review and approval by March 1 of each reporting year.
- I.L.3. The Permittee shall notify the Director immediately of any changes to the extent and type of liability coverage in accordance with R315-15-10 of the Utah Administrative Code.

I.M. Used Oil Handler Certificate

- I.M.1 In accordance with R315-15-4.1 of the Utah Administrative Code, the Permittee shall not operate as a used oil transporter without obtaining annually a Used Oil Handler Certificate from the Director. The Permittee shall submit a used oil handler fee, pursuant to Utah Code Annotated 63J-1-504 by December 31 of each calendar year to receive certification for the subsequent calendar year.

I.N. Inspection and Inspection Access

- I.N.1. Any duly authorized employee of the Director may, at any reasonable time and upon presentation of credentials, have access to and the right to copy any records relating to used oil and to inspect, audit or sample. The employee may also make record of the inspection by photographic, electronic, audio, video or any other reasonable means to determine compliance.
- I.N.2. In addition, the authorized officers may collect soil, groundwater or surface water samples to evaluate the facility's compliance.
- I.N.3. Failure to allow reasonable access to the property by authorized employees constitutes "denial of access" and may be grounds for enforcement action or permit revocation.

I.O. Annual Report

- I.O.1 As required by R315-15-13.4 of the Utah Administrative Code, the Permittee shall prepare and submit an Annual Report to the Director by March 1 of the following year. Form UO 004 (Annual Report for Used Oil Transporter Facilities) shall be submitted annually describing the Permittee's used oil activities in Utah. The Permittee shall include all financial assurance documentation required by Form UO 004.

I.P. Other Laws

I.P.1 Nothing in this permit shall be construed to relieve the Permittee of his obligation to comply with any Federal, State or local law.

I.Q. Transfer of Permit

I.Q.1 Written approval by the Director is required to transfer this Permit to another owner or operator.

I.R. Enforceability

I.R.1 Violations documented through the enforcement process pursuant to Utah Code Annotated 19-6-112 may result in penalties assessed in accordance with R315-102 of the Utah Administrative Code.

I.S. Effective Date

I.S.1 The permit is effective on the date of signature by the Director.

Draft Public Comment

II.A. Transportation Operations

- II.A.1. The Permittee is allowed to transport and deliver used oil to another permitted transporter, transfer facility, processor or off-specification burner in accordance with R315-15-4.4 of the Utah Administrative Code.
- II.A.2. The Permittee shall not store used oil longer than 24 hours from time of collection in transportation vehicles.
- II.A.3. Used oil recovered from oily water shall be managed as used oil in accordance with R315-15 of the Utah Administrative Code and this Permit.
- II.A.4. The Permittee shall not transport used oil with PCB concentrations greater than two ppm (mg/kg).

II.B. Transport Vehicle Requirements

- II.B.1. The Permittee shall only transport used oil in the types of vehicles in Table II.A.

Table II.A: Vehicle Description

Type of Vehicle	Maximum Capacity (gallons)
24' Cargo Box Truck	1,100 gallons
Peterbuilt pump tanker	3,500 gallons
Tanker trailer	6,000 gallons
Tanker pup trailer	3,500 gallons
24' Cargo Box Truck	1,100 gallons

- II.B.2. All used oil transport vehicles are required to have the words “USED OIL” on both sides of the transport vehicle in a contrasting color that is distinguishable from the background color and at least three inches tall. These designations shall be in place at all times the transport vehicle is transporting or storing used oil.
- II.B.3. All vehicles which transport used oil shall have a copy of the Permittee’s Used Oil Emergency Spill Plan in the vehicle at all times.
- II.B.4. The Permittee shall maintain Emergency Spill Cleanup materials in all vehicles used to transport used oil as specified in Condition II.G of this Permit.

II.C. Used Oil Loading and Unloading Requirements

- II.C.1. Prior to loading, the used oil shall be tested for halogen content in accordance with Condition II.D of this Permit.

- II.C.2. Used oil transport drivers shall secure the vehicle by positioning wheel chocks and applying the emergency brakes before loading or unloading used oil.
- II.C.3. The Permittee shall inspect all used oil collection equipment (e.g., vehicles and associated pumping equipment) for any damage prior to use.
- II.C.4. The Permittee shall place buckets or other containers under piping connections to collect drips of used oil during loading and unloading operations.
- II.C.5. The Permittee shall ensure the amount of used oil to be loaded into the transport vehicle will not exceed the carrying capacity. The Permittee shall utilize a calibrated gauging instrument to measure used oil volume in each transport vehicle.
- II.C.6. The Permittee shall cleanup any spills and drippings from the used oil transfer and properly manage the cleanup materials.
- II.C.7. Shipping documents shall be maintained at the Permittee's facilities and a copy left with each business where the Permittee collects or delivers used oil.
- II.C.8. Prior to unloading the transportation vehicle, the Permittee shall perform halogen quality control testing in accordance with Method 9077 and Condition II.D of this Permit.
- II.C.9. During loading and unloading operations, the trained operator shall remain at the transfer location and maintain control of the operations throughout the entire used oil transfer.
- II.C.10. The Permittee shall not load or unload used oil from a railroad tanker without the written approval from the Director.
- II.D. Used Oil Sampling and Analytical Procedures**
- II.D.1. Prior to loading the used oil for transport, the Permittee shall collect a representative sample and screen the used oil for halogens using either an approved field method or a Utah-certified laboratory.
- II.D.2. Used oil determined to be on-specification by a Utah-registered marketer can be collected and transported without further testing. Bills of Lading or used oil transportation records shall include copies of the analytical results for reference.
- II.D.3. **Bulk and Drum Sample Collection Requirements**
- II.D.3.a. The Permittee shall ensure a representative sample is collected from tanks, totes, drums or other containers from which oil is to be collected. Sampling personnel shall be trained on appropriate sampling methods for each type of container and matrix.
- II.D.3.b. Samples collected from bulk oil containers greater than 55 gallons shall be individual samples, not composite samples.

II.D.3.c. A composite sample may be collected from individual drums or containers containing no more than 55 gallons containing used oil from the same source. A composite sample may consist of not more than four drums or 220 gallons, whichever is less, per composite sample. The composite samples shall be taken and consolidated into one sample and tested.

II.D.3.d. Drums or containers containing used oil from different sources or processes shall be sampled individually.

II.D.4. **Halogen Field Screening Methods**

II.D.4.a. For halogen field tests, the Permittee shall use CLOR-D-TECT® kits (EPA method 9077) to screen used oil when the water content of the used oil is less than or equal to 20%.

II.D.4.b. Halogen field tests of used oil containing water and/or antifreeze greater than 20% shall be screened using a HYDROCLOR Q® kit.

II.D.4.c. Results of all halogen field screening results shall be recorded on the shipping document such as a bill of lading. Results shall be initialed by the sampler.

II.D.4.d. For halogen field tests, the quality control duplicate samples shall be collected and analyzed prior to off-loading in accordance with Method 9077.

II.D.5. **Halogen Laboratory Analytical Methods**

II.D.5.a. When relying on laboratory testing, the Permittee shall submit a representative used oil sample from each container to a Utah-certified laboratory to analyze for total halogen concentrations using EPA Method 9076 or other equivalent method approved by the Director.

II.D.6. **PCB Contaminated Used Oil**

II.D.6.a. When accepting used oil which may contain PCBs for transportation, the Permittee shall comply with the requirements of R315-15-18 of the Utah Administrative Code and 40 CFR Part 761. Table II.C of this Permit lists the PCB sample preparation and analytical methods that the laboratory must use to analyze used oil samples.

Table II.C: PCB Sample Preparation and Analytical Methods

Sample Preparation	Analytical Procedure	Analytes	
		<i>PCB CAS RN</i>	<i>PCB</i>
3500C, 3580A	8082A • PCB Analytical Method • Analyses of the Aroclors bolded in the last column are mandatory. • Choose an additional two Aroclors from the last column for analysis, which will make total of seven Aroclors.	12674-11-2	1016
		147601-87-4	1210
		151820-27-8	1216
		11104-28-2	1221
		37234-40-5	1231
		11141-16-5	1232
		71328-89-7	1240
		53469-21-9	1242
		12672-29-6	1248
		165245-51-2	1250
		89577-78-6	1252
		11097-69-1	1254
		11096-82-5	1260
		37324-23-5	1262
11100-14-4	1268		

II.D.6.b. Prior to accepting used transformer oil or used oil potentially contaminated with PCBs, the generator shall provide analytical documentation of the PCB concentration.

II.D.6.c. The Permittee shall manage transformer oil or PCB-contaminated oil with concentrations of ≥ 2 mg/kg (ppm) in accordance with R315-15-18 of the Utah Administrative Code.

II.D.6.d. Records of any laboratory test results used to demonstrate PCB concentrations shall be attached to the transportation record. Used oil may not be diluted to avoid any provision in any federal or state environmental regulation.

II.E. Rebuttable Presumption

II.E.1. Used oil with a total halogen concentrations greater than 1,000 parts per million (ppm) is presumed to have been mixed with a hazardous waste and shall be managed as a hazardous waste unless the Permittee can successfully rebut the presumption.

- II.E.2. The Permittee may rebut the hazardous waste presumption in accordance with R315-15-4.5 of the Utah Administrative Code if the Permittee can demonstrate that the used oil does not contain significant concentrations of any of the halogenated hazardous constituents listed in Appendix VIII of EPA CFR 40, Part 261 which includes volatiles, semi-volatiles, PCBs, pesticides, herbicides, and dioxin/furans.
- II.E.3. If the additional testing shows that used oil has been mixed with a listed hazardous waste in R315-50-10 of the Utah Administrative Code, which incorporates by reference 40 CFR 261 Appendix VIII, the mixture shall be subject to regulation as a hazardous waste regardless of the level of halogenated constituents.
- II.E.4. The rebuttable presumption does not apply to metalworking oils/fluids containing chlorinated paraffins if they are processed through a tolling arrangement as described in R315-15-2.5(c) of the Utah Administrative Code to reclaim metalworking oils/fluids. The presumption does apply to metalworking oils/fluids if such oils/fluids are recycled in any other manner or disposed.
- II.E.5. The rebuttable presumption does not apply to used oils contaminated with chlorofluorocarbons (CFCs) removed from refrigeration units if the CFCs are destined for reclamation. The rebuttable presumption does apply to used oils contaminated with CFCs that have been mixed with used oil from sources other than refrigeration units.
- II.F. Used Oil Training**
- II.F.1. The Permittee shall train used oil handlers activities in accordance with R315-15-4 of the Utah Administrative Code and the requirements of this Permit. New employees shall not manage or process used oil unless accompanied by a trained employee or until used oil training is completed.
- II.F.2. The Permittee shall follow the written training program as specified in Attachment 2 (Training Plan). Employee training shall include identification of used oil, recordkeeping requirements and facility used oil procedures for handling, transporting, sampling and analysis, emergency response, spill reporting and personal safety.
- II.F.3. Employees shall demonstrate competence to collect a representative used oil sample and test for halogens using a CLOR-D-TECT[®] kit prior to fieldwork if Utah certified laboratory data is not available.
- II.F.4. The Permittee shall provide, at a minimum, an annual used oil training refresher course for employees handling used oil. Additional training is required if the Permittee changes used oil handling procedures or this Permit is modified.
- II.F.5. The Permittee shall keep training records for each employee for a minimum of three years. Employees and supervisors shall sign and date training attendance sheets to document class attendance. The written training syllabus outlining the topics covered during training shall be attached to each employee's training records.

II.G. Emergency Spill Response and Remediation

- II.G.1. In accordance with R315-15-9.1(a) of the Utah Administrative Code, the person responsible for the spill shall immediately take appropriate action to minimize the threat to human health and the environment and notify the DEQ Hotline at (801) 536-4123 if the spill is greater than 25 gallons or for smaller spills if posing a threat to human health or the environment.
- II.G.2. Responders shall take action to prevent spill from spreading by utilizing absorbent, dirt, booms, pads, rags, etc.
- II.G.3. Once the material is containerized, a waste characterization shall be made to determine the material's disposition.
- II.G.4. The Director may require additional cleanup action to protect human health or the environment.
- II.G.5. All costs associated with the cleanup shall be at the expense of the Permittee.
- II.G.6. Vehicle spill kits shall contain, at a minimum, the equipment listed in Table II.E of this Permit and shall be checked daily prior to collection activities.

Draft Public Comment

Table II.E: Spill Kit Requirements

Equipment Description	Quantity
Shovel	1
Buckets (5-gallon)	1
Absorbent pads	3
Granulated absorbent	15 lbs.
Spill Plan with Emergency Contact Numbers	1

II.H. Used Oil Release Notification and Reporting

II.H.1 The Permittee shall notify the Utah Department of Environmental Quality 24-hour Answering Service, (801) 536-4123, for used oil releases exceeding 25 gallons or smaller releases that pose a potential threat to human health or the environment in accordance with R315-15-15-9.1(b) of the Utah Administrative Code. All relevant information required by R315-15-15-9.1(c) shall be included.

II.H.2. In accordance with R315-15-9.1(b) of the Utah Administrative Code, the Permittee shall submit to the Director a written report within 15 days of any reportable release of used oil. All relevant information, including the amount of waste generated from cleanup efforts, the characterization of the waste (i.e. hazardous or non-hazardous), final waste determination and disposal records, shall be included. The report shall also include actions taken by the Permittee to prevent future spills.

II.H.3. An air, rail, highway or water transporter who has discharged used oil shall give notice, if required by 49 CFR 171.15, to the National Response Center at <http://nrc.uscg.mil/nrchp.html>, (800) 424-8802 or (202) 426-2675. In addition to the notification above, a written report, as required in 49 CFR 171.16, shall be presented to the Director, Office of Hazardous Materials Regulations, Materials Transportation Bureau located in Washington, D.C., 20590.

ATTACHMENT 1

EMERGENCY CONTROLS—SPILL PLAN

Draft Public Comment



Emergency Control – Spill Plan

WRE Oil Recyclers

Transfer Spill Plan Policies

Employees will be given spill plan training accordingly to the Used Oil Training Plan before handling used oil and in bi-yearly meetings for review.

Each vehicle will hold materials needed for any spill which may occur. This will include but not be limited to a 5-gallon bucket with lid, granulated absorbent material, absorbent pads, one 5-foot long “oil sock,” plastic bags, 10 shop rags, and rubber gloves.

Each spill kit will be given a laminated copy of the spill kit list, which will be regularly monitored to ensure that it has been fully stocked after any use.

All spills over 1 cup, will be reported to the supervisor after the spill has been stabilized or cleaned up.

Following a spill, supervisors will review procedure with employees to recap, and to prevent further occurrences.

Immediate Action Steps in the Event of Used Oil Spills

In the event of a spill or a release, WRE Grease Recyclers LLC will implement the following protocol. A copy of these steps will also accompany each Spill Kit to aid all WRE representative to complete all steps correctly and in a timely manner.

1. R315-15-9.l (a): Take appropriate action to minimize the threat to human health and the environment.
2. Attempt to stop further spilling/leaking if safe.
3. Take action to prevent spill from spreading (use rags, “socks,” absorbent material). Use sand, dirt, or other material, or if necessary dig a trench to contain the spill.
4. Notify law enforcement, fire, medical officials, if necessary.
5. Safeguard yourself and others, but remain at or near the scene until officials arrive. You should not leave until authorized by these officials.
6. Notify supervisor if cleanup will require a significant amount of time or if assistance is needed to contain spill or clean up area.
7. If necessary, the supervisor will notify appropriate waste cleanup company to assist with cleanup.



8. If spill meets reporting criteria, the supervisor will report spills to appropriate agencies (see "Notification for: Used Oil Spills" below).
9. Clean up the area after spills are collected. Collect materials in plastic bags, and check with supervisor to aid in properly testing and disposing of the material. This also means reporting any environmental contamination to DEQ if dirt, sand or other earth material was used in containment of the spill.

Spill Kit list	Immediate Action Steps
5 Gallon Bucket w/lid	<ol style="list-style-type: none"> 1. Take appropriate action to minimize the threat to human health and the environment. 2. Attempt to stop further spilling/leaking if safe. 3. Take action to prevent spill from spreading, especially to drains (use rags, "socks," absorbent material). Use sand, dirt, or other material, or if necessary dig a trench to contain the spill. 4. Notify law enforcement, fire, medical officials, if necessary. 5. Safeguard yourself and others, but remain at or near the scene until officials arrive. You should not leave until authorized by these officials. 6. Notify supervisor if cleanup will require a significant amount of time or if assistance is needed to contain spill or clean up area. 7. If necessary, the supervisor will notify appropriate waste cleanup company to assist with cleanup. 8. If spill meets reporting criteria, the supervisor will report spills to appropriate agencies (Utah State Department of Environmental Quality, 24-hour Answering Service, 801-536-4123). 9. Clean up the area after spills are collected. Collect materials in plastic bags, and check with supervisor to aid in properly testing and disposing of the material. This also means reporting any environmental contamination to DEQ if dirt, sand or other earth material was used in containment of the spill.
15 lbs Oil absorbent	
Dust Pan	
Hand Broom	
Absorbent pads (3)	
5' Oil Sock	
Plastic Bag(s)	
10 Shop Rags	
Rubber Gloves	

R315-15-9.3 Release Clean Up

WRE responsible for the material at the time of the release shall clean up all the released material and any residue or contaminated soil, water or other material resulting from the release. Take action as may be required by the Director so that the released material, residue or contaminated soil, water or other material no longer presents a hazard to human health or the environment. The cleanup or other required actions shall be at the expense of WRE responsible for the release.



Complete a spill report form and give it to your supervisor at end of shift. The supervisor will be responsible to follow up with requirements of R315-15-9.4 REPORTING (see below) required by the rules below.

R315-15-9.1(b) & (c) Spill Notification

Notify the Utah State Department of Environmental Quality, 24-hour Answering Service, 801-536-4123 for used oil releases exceeding 25 gallons, or smaller releases that pose a potential threat to human health or the environment. Small leaks and drips from vehicles are considered minimums and are not subject to the release clean-up provisions of R315-15-9.

Provide the following information when reporting the release:

1. Name, phone number, and address of person responsible for the release.
2. Name, title, and phone number of individual reporting.
3. Time, date, and location of release—as specific as possible including nearest town, city, highway, or waterway.
4. Description contained on the manifest and the amount of material released.
5. Cause of release.
6. Possible hazards to human health or the environment and emergency action taken to minimize that threat.
7. The extent of injuries, if any.
8. An air, rail, highway, or water transporter who has discharged used oil shall give notice, if required by 49 CFR 171.15 to the National Response Center, 800-424-8802 or 202-426-2675.
9. Report in writing as required by 49 CFR 171.16 to the Director, Office of Hazardous Materials Regulation, Materials Transportation Bureau, Department of Transportation, and Washington, D.C. 20590

R315-15-9.4 Reporting

Within 15 days after any release of used oil that is reported under R315-15-9.1(b), WRE Oil Recyclers shall submit to the Director a written report which contains the following information:

1. The person's name, address, and telephone number, date, time, location, and nature of the incident;
2. Name and quantity of material(s) involved;
3. The extent of injuries, if any;
4. An assessment of actual or potential hazards to human health or the



environment, where this is applicable in 9.4 REPORTING.

5. The estimated quantity and disposition of recovered material that resulted from the incident.

Draft Public Comment