

**STATEMENT OF BASIS
CASPER'S ICE CREAM, INC.
UPDES PERMIT NUMBER: UT0025526
MAJOR MINOR INDUSTRIAL**

FACILITY CONTACTS

Person Name:	Shawn Anderson
Position:	Facility Engineer
Telephone:	(435) 258-2477 Ext. 13
Person Name:	Kyle Smith
Position:	Vice President
Telephone:	(435) 258-2477 Ext. 18
Facility Name:	Casper's Ice Cream, Inc.
Facility Mailing Address:	11805 North 200 East Richmond, Utah 84333
Telephone:	(435) 258-2477

DESCRIPTION OF FACILITY

Casper's Ice Cream, Inc. (Casper's) is an ice cream manufacturing company that produces novelty products such as ice cream sandwiches as well as hard ice cream. It is located at 11805 North 200 East, in Richmond, Utah at latitude 41°56.81' and longitude 111°49.89'. Casper's Standard Industrial Classification (SIC) code is 2024, with a North American Industry Classification System (NAICS) code of 311520 for Ice Cream and Frozen Dessert Manufacturing.

Casper's has two pipes that leave the facility; one contains non-contact cooling water and the other contains process water. Approximately 8,000 gallons of process water are generated per day. The process water is currently being treated through several grease traps, septic tanks, and to an aerated containment pond. Process water will be blended with irrigation and non-contact cooling water then land applied on cropland located west of the facility. The non-contact cooling water is collected and discharged through Outfall 001 to a pond located between Casper's property, and a farm to the West. The pond discharges to the Cub River

SUMMARY OF CHANGES FROM PREVIOUS PERMIT

In the initial permit, chemical oxygen demand (COD) and biological oxygen demand (BOD) were included. At that time they had not finalized a disposal system for the process wash down water from the facility. There was also still a connection between the process wash down system and the cooling water system. Since the permit was first issued a land application system has been approved and installed. As a result of these changes, there is no longer a reasonable expectation of anything being discharged that would result in COD and/or BOD impact to the Cub River. COD and BOD will not have limits attached to the permit, and will no longer be required to monitor for them.

In addition to the removal of BOD and COD from the permit, the monitoring frequency for pH and total suspended solids will be adjusted to be in step with other parameters. There is a push to have all

monthly reporting submissions done electronically through a national system known as NetDMR. Eventually all DMR reporting will be done through NetDMR. This will be started during this permit cycle.

SURFACE WATER DISCHARGE

DESCRIPTION OF SURFACE WATER DISCHARGE

Casper's generates up to approximately 75,000 gallons of non-contact cooling water effluent per day. It is water from this pipe that will be discharged into the Cub River. During the months when the irrigation is needed for the fields, the non-contact cooling water will be added to the process water to be used for make up water for the irrigation system. This will bring about long periods of no discharge for the non-contact cooling water. Casper's Ice Cream is also looking into future upgrades for the system that will reduce and eliminate the need for the cooling water flow.

<u>Outfall</u>	<u>Description of Discharge Point</u>
001	Located at latitude 41° 56.81' and longitude 111° 49.89'. The discharge is through a pipe to an unnamed pond that connects to the Cub River.

RECEIVING WATERS AND STREAM CLASSIFICATION

The discharge flows into the Cub River. The Cub River is classified 2B, 3B and 4 at this location according to *Utah Administrative Code (UAC) R317-2-13*.

- Class 2B -Protected for secondary contact recreation such as boating, wading, or similar uses.
- Class 3B -Protected for warm water species of game fish and other warm water aquatic life, including the necessary aquatic organisms in their food chain.
- Class 4 -Protected for agricultural uses including irrigation of crops and stock watering.

BASIS FOR EFFLUENT LIMITATIONS

The total suspended solids (TSS) and pH limits are based on current Utah Secondary Treatment Standards, *UAC R317-1-3.2*. Oil and Grease is based on Best Professional Judgment (BPJ), and shall not exceed 10 mg/L as a maximum per sample. Temperature and dissolved oxygen (DO) are from the waste load analysis (WLA)

Based on effluent monitoring data and the existing treatment facility, the permittee is expected to be able to comply with these limitations. The WLA indicates that these limitations should be sufficiently protective of water quality, in order to meet State standards in the receiving waters.

The permit limitations are:

Parameter	Effluent Limitations			
	Max Monthly Average	Max Weekly Average	Daily Minimum	Daily Maximum
Flow, MGD	NA	NA	NA	0.01
Temperature, °C				
Winter (Jan-Mar)	NA	NA	NA	84.1
Spr (Apr-Jun)	NA	NA	NA	91.3
Sum (Jul-Sept)	NA	NA	NA	100
Fall (Oct-Dec)	NA	NA	NA	88.1
Temperature, °C	NA	NA	NA	100
TSS, mg/L	25	35	NA	NA
DO, mg/L	NA	NA	5.0	NA
Oil & Grease, mg/L *a	NA	NA	NA	10.0
pH, Standard Units	NA	NA	6.5	9.0
Phosphorus, mg/L	NA	NA	NA	0.05

NA – Not Applicable.

*a Sample for Oil and Grease when a sheen is visible.

SELF-MONITORING AND REPORTING REQUIREMENTS

The permit will require reports to be submitted quarterly, as applicable, on Discharge Monitoring Report (DMR) forms due 28 days after the end of the monitoring period. Lab sheets for biomonitoring must be attached to the biomonitoring DMR.

Self-Monitoring and Reporting Requirements *c			
Parameter	Frequency	Sample Type	Units
Total Flow	Continuous	Recorder	MGD
Temperature	Monthly	Grab	°C
TSS, Effluent	Monthly	Grab	mg/L
DO	Monthly	Grab	mg/L
Oil & Grease *d	Monthly	Grab	mg/L
pH	Monthly	Grab	SU
Phosphorus	Monthly	Grab	mg/L

*c See Definitions, *Part VI*, for definition of terms.

*d Oil and Grease should be sampled if there is visible oil, grease, or a sheen is present in the discharge.

STORM WATER

STORMWATER REQUIREMENTS

The storm water requirements in the permit are based on the UPDES Multi-Sector General Permit for Storm Water Discharges for Industrial Activity, General Permit No. UTR000000 (MSGP).

Ice Cream and Frozen Dessert facilities are not required to perform analytical monitoring so none have been included. The storm water section in the permit does contain requirements for Storm Water Pollution Prevention Plan Preparation, Discharge Certification, CWA Section 313, Visual Monitoring and Spill Prevention and Response.

PRETREATMENT REQUIREMENTS

Any process wastewater that the facility may discharge to the sanitary sewer, either as direct discharge or as a hauled waste, is subject to federal, state and local pretreatment regulations. Pursuant to section 307 of the Clean Water Act, the permittee shall comply with all applicable Federal General Pretreatment Regulations promulgated, found in 40 CFR section 403, the State Pretreatment Requirements found in *UAC R317-8-8*, and any specific local discharge limitations developed by the Publicly Owned Treatment Works (POTW) accepting the waste.

BIOMONITORING REQUIREMENTS

As part of the nationwide effort to control toxics, biomonitoring requirements are being included in all major permits and in minor permits for facilities where effluent toxicity is an existing or potential concern. Authorization for requiring effluent biomonitoring is provided for in *UAC R317-8-4.2* and *R317-8-5.3. The Whole Effluent Toxicity (WET) Control Guidance Document*, February 15, 1991, outlines guidance to be used by Utah Division of Water Quality staff and by permittee's for implementation of WET control through the UPDES discharge permit program.

Casper's is a minor facility discharging approximately 75,000 gallons per day of non-contact cooling water. Comparison of the laboratory analysis performed on their effluent to the waste load analysis on the Cub River, Casper's discharge is not likely to be toxic. As a result, biomonitoring of the effluent will not be required. However, the permit will contain a WET reopener provision.

PERMIT DURATION

It is recommended that this permit be effective for a duration of five (5) years.

Drafted by
Daniel R Griffin P.E., Discharge
Michael George, Storm Water
Utah Division of Water Quality

**WASTELOAD ANALYSIS [WLA]
Addendum: Statement of Basis
SUMMARY**

Discharging Facility: Casper Ice Cream

UPDES No: UT-0025526
Current Flow: 0.08 MGD Design Flow
Design Flow 0.08 MGD

Receiving Water: Cub River

Stream Classification: 2B, 3B, 4
Stream Flows [cfs]:
9.9 Summer (July-Sept) 20th Percentile
9.9 Fall (Oct-Dec) 20th Percentile
9.9 Winter (Jan-Mar) 20th Percentile
9.9 Spring (Apr-June) 20th Percentile
34.6 Average
Stream TDS Values:
264.0 Summer (July-Sept) Average
264.0 Fall (Oct-Dec) Average
264.0 Winter (Jan-Mar) Average
264.0 Spring (Apr-June) Average

Effluent Limits:

Flow, MGD: 0.08 MGD Design Flow
BOD, mg/l: 25.0 Summer 5.0 Indicator
Dissolved Oxygen, mg/l: 5.5 Summer 6.5 30 Day Average
TNH3, Chronic, mg/l: 101.2 Summer Varies Function of pH and Temperature
TDS, mg/l: 75922.7 Summer 1200.0

WQ Standard:

Modeling Parameters:

Acute River Width: 50.0%
Chronic River Width: 100.0%

Level 1 Antidegradation Level Completed: Level II Review not required.

Date: 2/15/2011

Permit Writer: _____
WLA by: _____
WQM Sec. Approval: _____
TMDL Sec. Approval: _____

Utah Division of Water Quality
Salt Lake City, Utah

WASTELOAD ANALYSIS [WLA]
Addendum: Statement of Basis

15-Feb-11
4:00 PM

Facilities: Casper Ice Cream
Discharging to: Cub River

UPDES No: UT-0025526

THIS IS A DRAFT DOCUMENT

I. Introduction

Wasteload analyses are performed to determine point source effluent limitations necessary to maintain designated beneficial uses by evaluating projected effects of discharge concentrations on in-stream water quality. The wasteload analysis also takes into account downstream designated uses [R317-2-8, UAC]. Projected concentrations are compared to numeric water quality standards to determine acceptability. The anti-degradation policy and procedures are also considered. The primary in-stream parameters of concern may include metals (as a function of hardness), total dissolved solids (TDS), total residual chlorine (TRC), un-ionized ammonia (as a function of pH and temperature, measured and evaluated in terms of total ammonia), and dissolved oxygen.

Mathematical water quality modeling is employed to determine stream quality response to point source discharges. Models aid in the effort of anticipating stream quality at future effluent flows at critical environmental conditions (e.g., low stream flow, high temperature, high pH, etc).

The numeric criteria in this wasteload analysis may always be modified by narrative criteria and other conditions determined by staff of the Division of Water Quality.

II. Receiving Water and Stream Classification

Cub River:	2B, 3B, 4
Antidegradation Review:	Level I review completed. Level II review not required.

III. Numeric Stream Standards for Protection of Aquatic Wildlife

Total Ammonia (TNH ₃)	Varies as a function of Temperature and pH Rebound. See Water Quality Standards
Chronic Total Residual Chlorine (TRC)	0.011 mg/l (4 Day Average) 0.019 mg/l (1 Hour Average)
Chronic Dissolved Oxygen (DO)	6.50 mg/l (30 Day Average) 5.00 mg/l (7Day Average) 4.00 mg/l (1 Day Average)
Maximum Total Dissolved Solids	1200.0 mg/l

**Utah Division of Water Quality
Salt Lake City, Utah**

Acute and Chronic Heavy Metals (Dissolved)

Parameter	4 Day Average (Chronic) Standard		1 Hour Average (Acute) Standard		
	Concentration	Load*	Concentration		Load*
Aluminum	87.00 ug/l**	0.058 lbs/day	750.00	ug/l	0.501 lbs/day
Arsenic	190.00 ug/l	0.127 lbs/day	340.00	ug/l	0.227 lbs/day
Cadmium	0.61 ug/l	0.000 lbs/day	6.52	ug/l	0.004 lbs/day
Chromium III	211.92 ug/l	0.142 lbs/day	4433.71	ug/l	2.963 lbs/day
ChromiumVI	11.00 ug/l	0.007 lbs/day	16.00	ug/l	0.011 lbs/day
Copper	23.85 ug/l	0.016 lbs/day	39.41	ug/l	0.026 lbs/day
Iron			1000.00	ug/l	0.668 lbs/day
Lead	12.88 ug/l	0.009 lbs/day	330.60	ug/l	0.221 lbs/day
Mercury	0.0120 ug/l	0.000 lbs/day	2.40	ug/l	0.002 lbs/day
Nickel	132.13 ug/l	0.088 lbs/day	1188.44	ug/l	0.794 lbs/day
Selenium	4.60 ug/l	0.003 lbs/day	20.00	ug/l	0.013 lbs/day
Silver	N/A ug/l	N/A lbs/day	25.04	ug/l	0.017 lbs/day
Zinc	303.93 ug/l	0.203 lbs/day	303.93	ug/l	0.203 lbs/day

* Allowed below discharge

**Chronic Aluminum standard applies only to waters with a pH < 7.0 and a Hardness < 50 mg/l as CaCO3

Metals Standards Based upon a Hardness of 300 mg/l as CaCO3

Organics [Pesticides]

Parameter	4 Day Average (Chronic) Standard		1 Hour Average (Acute) Standard		
	Concentration	Load*	Concentration		Load*
Aldrin			1.500	ug/l	0.001 lbs/day
Chlordane	0.004 ug/l	0.232 lbs/day	1.200	ug/l	0.001 lbs/day
DDT, DDE	0.001 ug/l	0.054 lbs/day	0.550	ug/l	0.000 lbs/day
Dieldrin	0.002 ug/l	0.102 lbs/day	1.250	ug/l	0.001 lbs/day
Endosulfan	0.056 ug/l	3.020 lbs/day	0.110	ug/l	0.000 lbs/day
Endrin	0.002 ug/l	0.124 lbs/day	0.090	ug/l	0.000 lbs/day
Guthion			0.010	ug/l	0.000 lbs/day
Heptachlor	0.004 ug/l	0.205 lbs/day	0.260	ug/l	0.000 lbs/day
Lindane	0.080 ug/l	4.314 lbs/day	1.000	ug/l	0.001 lbs/day
Methoxychlor			0.030	ug/l	0.000 lbs/day
Mirex			0.010	ug/l	0.000 lbs/day
Parathion			0.040	ug/l	0.000 lbs/day
PCB's	0.014 ug/l	0.755 lbs/day	2.000	ug/l	0.001 lbs/day
Pentachlorophenol	13.00 ug/l	700.963 lbs/day	20.000	ug/l	0.013 lbs/day
Toxephene	0.0002 ug/l	0.011 lbs/day	0.7300	ug/l	0.000 lbs/day

**Utah Division of Water Quality
Salt Lake City, Utah**

IV. Numeric Stream Standards for Protection of Agriculture

	4 Day Average (Chronic) Standard		1 Hour Average (Acute) Standard	
	Concentration	Load*	Concentration	Load*
Arsenic			100.0 ug/l	lbs/day
Boron			750.0 ug/l	lbs/day
Cadmium			10.0 ug/l	0.00 lbs/day
Chromium			100.0 ug/l	lbs/day
Copper			200.0 ug/l	lbs/day
Lead			100.0 ug/l	lbs/day
Selenium			50.0 ug/l	lbs/day
TDS, Summer			1200.0 mg/l	0.40 tons/day

V. Numeric Stream Standards for Protection of Human Health (Class 1C Waters)

	4 Day Average (Chronic) Standard		1 Hour Average (Acute) Standard	
	Concentration	Load*	Concentration	Load*
Metals				
Arsenic			ug/l	lbs/day
Barium			ug/l	lbs/day
Cadmium			ug/l	lbs/day
Chromium			ug/l	lbs/day
Lead			ug/l	lbs/day
Mercury			ug/l	lbs/day
Selenium			ug/l	lbs/day
Silver			ug/l	lbs/day
Fluoride (3)			ug/l	lbs/day
to			ug/l	lbs/day
Nitrates as N			ug/l	lbs/day

Chlorophenoxy Herbicides

2,4-D	ug/l	lbs/day
2,4,5-TP	ug/l	lbs/day
Endrin	ug/l	lbs/day
ocyclohexane (Lindane)	ug/l	lbs/day
Methoxychlor	ug/l	lbs/day
Toxaphene	ug/l	lbs/day

VI. Numeric Stream Standards the Protection of Human Health from Water & Fish Consumption [Toxics]

	Maximum Conc., ug/l - Acute Standards			
	Class 1C		Class 3A, 3B	
	[2 Liters/Day for 70 Kg Person over 70 Yr.]		[6.5 g for 70 Kg Person over 70 Yr.]	
Toxic Organics				
Acenaphthene	ug/l	lbs/day	2700.0 ug/l	145.58 lbs/day
Acrolein	ug/l	lbs/day	780.0 ug/l	42.06 lbs/day
Acrylonitrile	ug/l	lbs/day	0.7 ug/l	0.04 lbs/day
Benzene	ug/l	lbs/day	71.0 ug/l	3.83 lbs/day
Benzidine	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Carbon tetrachloride	ug/l	lbs/day	4.4 ug/l	0.24 lbs/day
Chlorobenzene	ug/l	lbs/day	21000.0 ug/l	1132.33 lbs/day
1,2,4-Trichlorobenzene				
Hexachlorobenzene	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
1,2-Dichloroethane	ug/l	lbs/day	99.0 ug/l	5.34 lbs/day

**Utah Division of Water Quality
Salt Lake City, Utah**

1,1,1-Trichloroethane				
Hexachloroethane	ug/l	lbs/day	8.9 ug/l	0.48 lbs/day
1,1-Dichloroethane				
1,1,2-Trichloroethane	ug/l	lbs/day	42.0 ug/l	2.26 lbs/day
1,1,2,2-Tetrachloroethane	ug/l	lbs/day	11.0 ug/l	0.59 lbs/day
Chloroethane			0.0 ug/l	0.00 lbs/day
Bis(2-chloroethyl) ether	ug/l	lbs/day	1.4 ug/l	0.08 lbs/day
2-Chloroethyl vinyl ether	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
2-Chloronaphthalene	ug/l	lbs/day	4300.0 ug/l	231.86 lbs/day
2,4,6-Trichlorophenol	ug/l	lbs/day	6.5 ug/l	0.35 lbs/day
p-Chloro-m-cresol			0.0 ug/l	0.00 lbs/day
Chloroform (HM)	ug/l	lbs/day	470.0 ug/l	25.34 lbs/day
2-Chlorophenol	ug/l	lbs/day	400.0 ug/l	21.57 lbs/day
1,2-Dichlorobenzene	ug/l	lbs/day	17000.0 ug/l	916.64 lbs/day
1,3-Dichlorobenzene	ug/l	lbs/day	2600.0 ug/l	140.19 lbs/day
1,4-Dichlorobenzene	ug/l	lbs/day	2600.0 ug/l	140.19 lbs/day
3,3'-Dichlorobenzidine	ug/l	lbs/day	0.1 ug/l	0.00 lbs/day
1,1-Dichloroethylene	ug/l	lbs/day	3.2 ug/l	0.17 lbs/day
1,2-trans-Dichloroethylene	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
2,4-Dichlorophenol	ug/l	lbs/day	790.0 ug/l	42.60 lbs/day
1,2-Dichloropropane	ug/l	lbs/day	39.0 ug/l	2.10 lbs/day
1,3-Dichloropropylene	ug/l	lbs/day	1700.0 ug/l	91.66 lbs/day
2,4-Dimethylphenol	ug/l	lbs/day	2300.0 ug/l	124.02 lbs/day
2,4-Dinitrotoluene	ug/l	lbs/day	9.1 ug/l	0.49 lbs/day
2,6-Dinitrotoluene	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
1,2-Diphenylhydrazine	ug/l	lbs/day	0.5 ug/l	0.03 lbs/day
Ethylbenzene	ug/l	lbs/day	29000.0 ug/l	1563.69 lbs/day
Fluoranthene	ug/l	lbs/day	370.0 ug/l	19.95 lbs/day
4-Chlorophenyl phenyl ether				
4-Bromophenyl phenyl ether				
Bis(2-chloroisopropyl) ether	ug/l	lbs/day	170000.0 ug/l	9166.45 lbs/day
Bis(2-chloroethoxy) methane	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Methylene chloride (HM)	ug/l	lbs/day	1600.0 ug/l	86.27 lbs/day
Methyl chloride (HM)	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Methyl bromide (HM)	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Bromoform (HM)	ug/l	lbs/day	360.0 ug/l	19.41 lbs/day
Dichlorobromomethane	ug/l	lbs/day	22.0 ug/l	1.19 lbs/day
Chlorodibromomethane	ug/l	lbs/day	34.0 ug/l	1.83 lbs/day
Hexachlorobutadiene(c)	ug/l	lbs/day	50.0 ug/l	2.70 lbs/day
Hexachlorocyclopentadiene	ug/l	lbs/day	17000.0 ug/l	916.64 lbs/day
Isophorone	ug/l	lbs/day	600.0 ug/l	32.35 lbs/day
Naphthalene				
Nitrobenzene	ug/l	lbs/day	1900.0 ug/l	102.45 lbs/day
2-Nitrophenol	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
4-Nitrophenol	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
2,4-Dinitrophenol	ug/l	lbs/day	14000.0 ug/l	754.88 lbs/day
4,6-Dinitro-o-cresol	ug/l	lbs/day	765.0 ug/l	41.25 lbs/day
N-Nitrosodimethylamine	ug/l	lbs/day	8.1 ug/l	0.44 lbs/day
N-Nitrosodiphenylamine	ug/l	lbs/day	16.0 ug/l	0.86 lbs/day
N-Nitrosodi-n-propylamine	ug/l	lbs/day	1.4 ug/l	0.08 lbs/day
Pentachlorophenol	ug/l	lbs/day	8.2 ug/l	0.44 lbs/day

**Utah Division of Water Quality
Salt Lake City, Utah**

Phenol	ug/l	lbs/day	4.6E+06 ug/l	2.48E+05 lbs/day
Bis(2-ethylhexyl)phthala	ug/l	lbs/day	5.9 ug/l	0.32 lbs/day
Butyl benzyl phthalate	ug/l	lbs/day	5200.0 ug/l	280.39 lbs/day
Di-n-butyl phthalate	ug/l	lbs/day	12000.0 ug/l	647.04 lbs/day
Di-n-octyl phthlate				
Diethyl phthalate	ug/l	lbs/day	120000.0 ug/l	6470.43 lbs/day
Dimethyl phthlate	ug/l	lbs/day	2.9E+06 ug/l	1.56E+05 lbs/day
Benzo(a)anthracene (P/	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Benzo(a)pyrene (PAH)	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Benzo(b)fluoranthene (F	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Benzo(k)fluoranthene (F	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Chrysene (PAH)	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Acenaphthylene (PAH)				
Anthracene (PAH)	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Dibenzo(a,h)anthracene	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Indeno(1,2,3-cd)pyrene	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Pyrene (PAH)	ug/l	lbs/day	11000.0 ug/l	593.12 lbs/day
Tetrachloroethylene	ug/l	lbs/day	8.9 ug/l	0.48 lbs/day
Toluene	ug/l	lbs/day	200000 ug/l	10784.05 lbs/day
Trichloroethylene	ug/l	lbs/day	81.0 ug/l	4.37 lbs/day
Vinyl chloride	ug/l	lbs/day	525.0 ug/l	28.31 lbs/day
				lbs/day
				lbs/day
Pesticides				
Aldrin	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Dieldrin	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Chlordane	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
4,4'-DDT	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
4,4'-DDE	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
4,4'-DDD	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
alpha-Endosulfan	ug/l	lbs/day	2.0 ug/l	0.11 lbs/day
beta-Endosulfan	ug/l	lbs/day	2.0 ug/l	0.11 lbs/day
Endosulfan sulfate	ug/l	lbs/day	2.0 ug/l	0.11 lbs/day
Endrin	ug/l	lbs/day	0.8 ug/l	0.04 lbs/day
Endrin aldehyde	ug/l	lbs/day	0.8 ug/l	0.04 lbs/day
Heptachlor	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Heptachlor epoxide				
PCB's				
PCB 1242 (Arochlor 124	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
PCB-1254 (Arochlor 124	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
PCB-1221 (Arochlor 122	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
PCB-1232 (Arochlor 122	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
PCB-1248 (Arochlor 124	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
PCB-1260 (Arochlor 126	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
PCB-1016 (Arochlor 10	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Pesticide				
Toxaphene	ug/l		0.0 ug/l	0.00 lbs/day
Dioxin				
Dioxin (2,3,7,8-TCDD)	ug/l	lbs/day		

**Utah Division of Water Quality
Salt Lake City, Utah**

Metals

Antimony	ug/l	lbs/day		
Arsenic	ug/l	lbs/day	4300.00 ug/l	231.86 lbs/day
Asbestos	ug/l	lbs/day		
Beryllium				
Cadmium				
Chromium (III)				
Chromium (VI)				
Copper				
Cyanide	ug/l	lbs/day	2.2E+05 ug/l	11862.46 lbs/day
Lead	ug/l	lbs/day		
Mercury			0.15 ug/l	0.01 lbs/day
Nickel			4600.00 ug/l	248.03 lbs/day
Selenium	ug/l	lbs/day		
Silver	ug/l	lbs/day		
Thallium			6.30 ug/l	0.34 lbs/day
Zinc				

There are additional standards that apply to this receiving water, but were not considered in this modeling/waste load allocation analysis.

VII. Mathematical Modeling of Stream Quality

Model configuration was accomplished utilizing standard modeling procedures. Data points were plotted and coefficients adjusted as required to match observed data as closely as possible.

The modeling approach used in this analysis included one or a combination of the following models.

(1) The Utah River Model, Utah Division of Water Quality, 1992. Based upon STREAMDO IV (Region VIII) and Supplemental Ammonia Toxicity Models; EPA Region VIII, Sept. 1990 and QUAL2E (EPA, Athens, GA).

(2) Utah Ammonia/Chlorine Model, Utah Division of Water Quality, 1992.

(3) AMMTOX Model, University of Colorado, Center of Limnology, and EPA Region 8

(4) Principles of Surface Water Quality Modeling and Control. Robert V. Thomann, et.al. Harper Collins Publisher, Inc. 1987, pp. 644.

Coefficients used in the model were based, in part, upon the following references:

(1) Rates, Constants, and Kinetics Formulations in Surface Water Quality Modeling. Environmental Research Laboratory, Office of Research and Development, U.S. Environmental Protection Agency, Athens Georgia. EPA/600/3-85/040 June 1985.

**Utah Division of Water Quality
Salt Lake City, Utah**

(2) Principles of Surface Water Quality Modeling and Control. Robert V. Thomann, et.al.
Harper Collins Publisher, Inc. 1987, pp. 644.

VIII. Modeling Information

The required information for the model may include the following information for both the upstream conditions at low flow and the effluent conditions:

Flow, Q, (cfs or MGD)	D.O. mg/l
Temperature, Deg. C.	Total Residual Chlorine (TRC), mg/l
pH	Total NH3-N, mg/l
BOD5, mg/l	Total Dissolved Solids (TDS), mg/l
Metals, ug/l	Toxic Organics of Concern, ug/l

Other Conditions

In addition to the upstream and effluent conditions, the models require a variety of physical and biological coefficients and other technical information. In the process of actually establishing the permit limits for an effluent, values are used based upon the available data, model calibration, literature values, site visits and best professional judgement.

Model Inputs

The following is upstream and discharge information that was utilized as inputs for the analysis. Dry washes are considered to have an upstream flow equal to the flow of the discharge.

Current Upstream Information

	Stream								
	Critical Low								
	Flow	Temp.	pH	T-NH3	BOD5	DO	TRC	TDS	
	cfs	Deg. C		mg/l as N	mg/l	mg/l	mg/l	mg/l	
Summer (Irrig. Season)	9.9	18.2	8.3	0.01	0.50	7.19	0.00	264.0	
Fall	9.9	6.2	8.3	0.01	0.50	---	0.00	264.0	
Winter	9.9	2.3	8.1	0.01	0.50	---	0.00	264.0	
Spring	9.9	9.5	8.2	0.01	0.50	---	0.00	264.0	
Dissolved Metals	Al	As	Cd	CrIII	CrVI	Copper	Fe	Pb	
	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l	
All Seasons	1.59*	0.53*	0.053*	0.53*	2.65*	0.53*	0.83*	0.53*	
Dissolved Metals	Hg	Ni	Se	Ag	Zn	Boron			
	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l			
All Seasons	0.0000	0.53*	1.06*	0.1*	0.053*	10.0			* 1/2 MDL

**Utah Division of Water Quality
Salt Lake City, Utah**

Projected Discharge Information

Season	Flow, MGD	Temp.	TDS mg/l	TDS tons/day
Summer	0.08000	17.0	500.00	0.16677
Fall	0.08000	15.0		
Winter	0.08000	12.0		
Spring	0.08000	15.0		

All model numerical inputs, intermediate calculations, outputs and graphs are available for discussion, inspection and copy at the Division of Water Quality.

IX. Effluent Limitations

Current State water quality standards are required to be met under a variety of conditions including in-stream flows targeted to the 7-day, 10-year low flow (R317-2-9).

Other conditions used in the modeling effort coincide with the environmental conditions expected at low stream flows.

Effluent Limitation for Flow based upon Water Quality Standards

In-stream criteria of downstream segments will be met with an effluent flow maximum value as follows:

Season	Daily Average	
Summer	0.080 MGD	0.124 cfs
Fall	0.080 MGD	0.124 cfs
Winter	0.080 MGD	0.124 cfs
Spring	0.080 MGD	0.124 cfs

Flow Requirement or Loading Requirement

The calculations in this wasteload analysis utilize the maximum effluent discharge flow of 0.08 MGD. If the discharger is allowed to have a flow greater than 0.08 MGD during 7Q10 conditions, and effluent limit concentrations as indicated, then water quality standards will be violated. In order to prevent this from occurring, the permit writers must include the discharge flow limitation as indicated above; or, include loading effluent limits in the permit.

Effluent Limitation for Whole Effluent Toxicity (WET) based upon WET Policy

Effluent Toxicity will not occur in downstream segments if the values below are met.

WET Requirements	LC50 >	8.4% Effluent	[Acute]
	IC25 >	1.2% Effluent	[Chronic]

**Utah Division of Water Quality
Salt Lake City, Utah**

Effluent Limitation for Biological Oxygen Demand (BOD) based upon Water Quality Standards or Regulations

In-stream criteria of downstream segments for Dissolved Oxygen will be met with an effluent BOD limitation as follows:

Season	Concentration	
Summer	25.0 mg/l as BOD5	16.7 lbs/day
Fall	25.0 mg/l as BOD5	16.7 lbs/day
Winter	25.0 mg/l as BOD5	16.7 lbs/day
Spring	25.0 mg/l as BOD5	16.7 lbs/day

Effluent Limitation for Dissolved Oxygen (DO) based upon Water Quality Standards

In-stream criteria of downstream segments for Dissolved Oxygen will be met with an effluent D.O. limitation as follows:

Season	Concentration
Summer	5.50
Fall	5.50
Winter	5.50
Spring	5.50

Effluent Limitation for Total Ammonia based upon Water Quality Standards

In-stream criteria of downstream segments for Total Ammonia will be met with an effluent limitation (expressed as Total Ammonia as N) as follows:

Season		Concentration	Load
Summer	4 Day Avg. - Chronic	101.2 mg/l as N	67.5 lbs/day
	1 Hour Avg. - Acute	98.4 mg/l as N	65.6 lbs/day
Fall	4 Day Avg. - Chronic	135.0 mg/l as N	90.1 lbs/day
	1 Hour Avg. - Acute	103.4 mg/l as N	69.0 lbs/day
Winter	4 Day Avg. - Chronic	181.0 mg/l as N	120.7 lbs/day
	1 Hour Avg. - Acute	145.8 mg/l as N	97.3 lbs/day
Spring	4 Day Avg. - Chronic	134.6 mg/l as N	89.8 lbs/day
	1 Hour Avg. - Acute	103.4 mg/l as N	69.0 lbs/day

Acute limit calculated with an Acute Zone of Initial Dilution (ZID) to be equal to 50.0%.

**Utah Division of Water Quality
Salt Lake City, Utah**

Effluent Limitation for Total Residual Chlorine based upon Water Quality Standards

In-stream criteria of downstream segments for Total Residual Chlorine will be met with an effluent limitation as follows:

Season		Concentration		Load	
Summer	4 Day Avg. - Chronic	0.808	mg/l	0.54	lbs/day
	1 Hour Avg. - Acute	0.736	mg/l	0.49	lbs/day
Fall	4 Day Avg. - Chronic	0.808	mg/l	0.54	lbs/day
	1 Hour Avg. - Acute	0.736	mg/l	0.49	lbs/day
Winter	4 Day Avg. - Chronic	0.808	mg/l	0.54	lbs/day
	1 Hour Avg. - Acute	0.736	mg/l	0.49	lbs/day
Spring	4 Day Avg. - Chronic	0.808	mg/l	0.00	lbs/day
	1 Hour Avg. - Acute	0.736	mg/l	0.00	lbs/day

Effluent Limitations for Total Dissolved Solids based upon Water Quality Standards

Season		Concentration		Load	
Summer	Maximum, Acute	75922.7	mg/l	25.32	tons/day
Fall	Maximum, Acute	75922.7	mg/l	25.32	tons/day
Winter	Maximum, Acute	75922.7	mg/l	25.32	tons/day
Spring	4 Day Avg. - Chronic	75922.7	mg/l	25.32	tons/day

Colorado Salinity Forum Limits Determined by Permitting Section

Effluent Limitations for Total Recoverable Metals based upon Water Quality Standards

In-stream criteria of downstream segments for Dissolved Metals will be met with an effluent limitation as follows (based upon a hardness of 300 mg/l):

	4 Day Average		1 Hour Average		Load
	Concentration	Load	Concentration	Load	
Aluminum*	N/A	N/A	30,591.8	ug/l	20.4 lbs/day
Arsenic*	15,294.60 ug/l	6.6 lbs/day	13,879.7	ug/l	9.3 lbs/day
Cadmium	43.02 ug/l	0.0 lbs/day	263.5	ug/l	0.2 lbs/day
Chromium III	17,066.19 ug/l	7.4 lbs/day	181,377.8	ug/l	121.2 lbs/day
Chromium VI*	571.82 ug/l	0.2 lbs/day	496.0	ug/l	0.3 lbs/day
Copper	1,864.56 ug/l	0.8 lbs/day	1,580.9	ug/l	1.1 lbs/day
Iron*	N/A	N/A	40,866.1	ug/l	27.3 lbs/day
Lead	977.90 ug/l	0.4 lbs/day	13,495.1	ug/l	9.0 lbs/day
Mercury*	0.97 ug/l	0.0 lbs/day	98.2	ug/l	0.1 lbs/day
Nickel	10,616.97 ug/l	4.6 lbs/day	48,594.4	ug/l	32.5 lbs/day
Selenium*	244.89 ug/l	0.1 lbs/day	754.9	ug/l	0.5 lbs/day
Silver	N/A ug/l	N/A lbs/day	1,024.6	ug/l	0.7 lbs/day

**Utah Division of Water Quality
Salt Lake City, Utah**

Zinc	24,561.24 ug/l	10.6 lbs/day	12,432.6	ug/l	8.3 lbs/day
Cyanide*	420.33 ug/l	0.2 lbs/day	900.2	ug/l	0.6 lbs/day

*Limits for these metals are based on the dissolved standard.

**Effluent Limitations for Heat/Temperature based upon
Water Quality Standards**

Summer	100.0 Deg. C.	212.0 Deg. F
Fall	88.1 Deg. C.	190.5 Deg. F
Winter	84.1 Deg. C.	183.4 Deg. F
Spring	91.3 Deg. C.	196.4 Deg. F

**Effluent Limitations for Organics [Pesticides]
Based upon Water Quality Standards**

In-stream criteria of downstream segments for Organics [Pesticides] will be met with an effluent limit as follows:

	4 Day Average		1 Hour Average		
	Concentration	Load	Concentration		Load
Aldrin			1.5E+00	ug/l	1.55E-03 lbs/day
Chlordane	4.30E-03 ug/l	2.87E-03 lbs/day	1.2E+00	ug/l	1.24E-03 lbs/day
DDT, DDE	1.00E-03 ug/l	6.67E-04 lbs/day	5.5E-01	ug/l	5.69E-04 lbs/day
Dieldrin	1.90E-03 ug/l	1.27E-03 lbs/day	1.3E+00	ug/l	1.29E-03 lbs/day
Endosulfan	5.60E-02 ug/l	3.74E-02 lbs/day	1.1E-01	ug/l	1.14E-04 lbs/day
Endrin	2.30E-03 ug/l	1.53E-03 lbs/day	9.0E-02	ug/l	9.31E-05 lbs/day
Guthion	0.00E+00 ug/l	0.00E+00 lbs/day	1.0E-02	ug/l	1.03E-05 lbs/day
Heptachlor	3.80E-03 ug/l	2.53E-03 lbs/day	2.6E-01	ug/l	2.69E-04 lbs/day
Lindane	8.00E-02 ug/l	5.34E-02 lbs/day	1.0E+00	ug/l	1.03E-03 lbs/day
Methoxychlor	0.00E+00 ug/l	0.00E+00 lbs/day	3.0E-02	ug/l	3.10E-05 lbs/day
Mirex	0.00E+00 ug/l	0.00E+00 lbs/day	1.0E-02	ug/l	1.03E-05 lbs/day
Parathion	0.00E+00 ug/l	0.00E+00 lbs/day	4.0E-02	ug/l	4.14E-05 lbs/day
PCB's	1.40E-02 ug/l	9.34E-03 lbs/day	2.0E+00	ug/l	2.07E-03 lbs/day
Pentachlorophenol	1.30E+01 ug/l	8.67E+00 lbs/day	2.0E+01	ug/l	2.07E-02 lbs/day
Toxephene	2.00E-04 ug/l	1.33E-04 lbs/day	7.3E-01	ug/l	7.55E-04 lbs/day

**Utah Division of Water Quality
Salt Lake City, Utah**

**Effluent Targets for Pollution Indicators
Based upon Water Quality Standards**

In-stream criteria of downstream segments for Pollution Indicators will be met with an effluent limit as follows:

	1 Hour Average	
	Concentration	Loading
Gross Beta (pCi/l)	50.0 pCi/L	
BOD (mg/l)	5.0 mg/l	3.3 lbs/day
Nitrates as N	4.0 mg/l	2.7 lbs/day
Total Phosphorus as P	0.05 mg/l	0.0 lbs/day
Total Suspended Solids	90.0 mg/l	60.2 lbs/day

Note: Pollution indicator targets are for information purposes only.

**Effluent Limitations for Protection of Human Health [Toxics Rule]
Based upon Water Quality Standards (Most stringent of 1C or 3A & 3B as appropriate.)**

In-stream criteria of downstream segments for Protection of Human Health [Toxics] will be met with an effluent limit as follows:

	Maximum Concentration	
	Concentration	Load
Toxic Organics		
Acenaphthene	2.18E+05 ug/l	1.46E+02 lbs/day
Acrolein	6.30E+04 ug/l	4.21E+01 lbs/day
Acrylonitrile	5.33E+01 ug/l	3.56E-02 lbs/day
Benzene	5.74E+03 ug/l	3.83E+00 lbs/day
Benzidine	ug/l	lbs/day
Carbon tetrachloride	3.56E+02 ug/l	2.37E-01 lbs/day
Chlorobenzene	1.70E+06 ug/l	1.13E+03 lbs/day
1,2,4-Trichlorobenzene		
Hexachlorobenzene	6.22E-02 ug/l	4.15E-05 lbs/day
1,2-Dichloroethane	8.00E+03 ug/l	5.34E+00 lbs/day
1,1,1-Trichloroethane		
Hexachloroethane	7.19E+02 ug/l	4.80E-01 lbs/day
1,1-Dichloroethane		
1,1,2-Trichloroethane	3.39E+03 ug/l	2.26E+00 lbs/day
1,1,2,2-Tetrachloroethane	8.89E+02 ug/l	5.93E-01 lbs/day
Chloroethane		
Bis(2-chloroethyl) ether	1.13E+02 ug/l	7.55E-02 lbs/day
2-Chloroethyl vinyl ether		
2-Chloronaphthalene	3.48E+05 ug/l	2.32E+02 lbs/day
2,4,6-Trichlorophenol	5.25E+02 ug/l	3.50E-01 lbs/day
p-Chloro-m-cresol		
Chloroform (HM)	3.80E+04 ug/l	2.53E+01 lbs/day
2-Chlorophenol	3.23E+04 ug/l	2.16E+01 lbs/day
1,2-Dichlorobenzene	1.37E+06 ug/l	9.17E+02 lbs/day
1,3-Dichlorobenzene	2.10E+05 ug/l	1.40E+02 lbs/day

**Utah Division of Water Quality
Salt Lake City, Utah**

1,4-Dichlorobenzene	2.10E+05 ug/l	1.40E+02 lbs/day
3,3'-Dichlorobenzidine	6.22E+00 ug/l	4.15E-03 lbs/day
1,1-Dichloroethylene	2.59E+02 ug/l	1.73E-01 lbs/day
1,2-trans-Dichloroethylene1		
2,4-Dichlorophenol	6.39E+04 ug/l	4.26E+01 lbs/day
1,2-Dichloropropane	3.15E+03 ug/l	2.10E+00 lbs/day
1,3-Dichloropropylene	1.37E+05 ug/l	9.17E+01 lbs/day
2,4-Dimethylphenol	1.86E+05 ug/l	1.24E+02 lbs/day
2,4-Dinitrotoluene	7.36E+02 ug/l	4.91E-01 lbs/day
2,6-Dinitrotoluene		
1,2-Diphenylhydrazine	4.36E+01 ug/l	2.91E-02 lbs/day
Ethylbenzene	2.34E+06 ug/l	1.56E+03 lbs/day
Fluoranthene	2.99E+04 ug/l	2.00E+01 lbs/day
4-Chlorophenyl phenyl ether		
4-Bromophenyl phenyl ether		
Bis(2-chloroisopropyl) ether	1.37E+07 ug/l	9.17E+03 lbs/day
Bis(2-chloroethoxy) methane		
Methylene chloride (HM)	1.29E+05 ug/l	8.63E+01 lbs/day
Methyl chloride (HM)		
Methyl bromide (HM)		
Bromoform (HM)	2.91E+04 ug/l	1.94E+01 lbs/day
Dichlorobromomethane(HM)	1.78E+03 ug/l	1.19E+00 lbs/day
Chlorodibromomethane (HM)	2.75E+03 ug/l	1.83E+00 lbs/day
Hexachlorocyclopentadiene	1.37E+06 ug/l	9.17E+02 lbs/day
Isophorone	4.85E+04 ug/l	3.24E+01 lbs/day
Naphthalene		
Nitrobenzene	1.54E+05 ug/l	1.02E+02 lbs/day
2-Nitrophenol		
4-Nitrophenol		
2,4-Dinitrophenol	1.13E+06 ug/l	7.55E+02 lbs/day
4,6-Dinitro-o-cresol	6.18E+04 ug/l	4.12E+01 lbs/day
N-Nitrosodimethylamine	6.55E+02 ug/l	4.37E-01 lbs/day
N-Nitrosodiphenylamine	1.29E+03 ug/l	8.63E-01 lbs/day
N-Nitrosodi-n-propylamine	1.13E+02 ug/l	7.55E-02 lbs/day
Pentachlorophenol	6.63E+02 ug/l	4.42E-01 lbs/day
Phenol	3.72E+08 ug/l	2.48E+05 lbs/day
Bis(2-ethylhexyl)phthalate	4.77E+02 ug/l	3.18E-01 lbs/day
Butyl benzyl phthalate	4.20E+05 ug/l	2.80E+02 lbs/day
Di-n-butyl phthalate	9.70E+05 ug/l	6.47E+02 lbs/day
Di-n-octyl phthlate		
Diethyl phthalate	9.70E+06 ug/l	6.47E+03 lbs/day
Dimethyl phthlate	2.34E+08 ug/l	1.56E+05 lbs/day
Benzo(a)anthracene (PAH)	2.51E+00 ug/l	1.67E-03 lbs/day
Benzo(a)pyrene (PAH)	2.51E+00 ug/l	1.67E-03 lbs/day
Benzo(b)fluoranthene (PAH)	2.51E+00 ug/l	1.67E-03 lbs/day
Benzo(k)fluoranthene (PAH)	2.51E+00 ug/l	1.67E-03 lbs/day
Chrysene (PAH)	2.51E+00 ug/l	1.67E-03 lbs/day
Acenaphthylene (PAH)		
Anthracene (PAH)		
Dibenzo(a,h)anthracene (PAH)	2.51E+00 ug/l	1.67E-03 lbs/day
Indeno(1,2,3-cd)pyrene (PAH)	2.51E+00 ug/l	1.67E-03 lbs/day

**Utah Division of Water Quality
Salt Lake City, Utah**

Pyrene (PAH)	8.89E+05 ug/l	5.93E+02 lbs/day
Tetrachloroethylene	7.19E+02 ug/l	4.80E-01 lbs/day
Toluene	1.62E+07 ug/l	1.08E+04 lbs/day
Trichloroethylene	6.55E+03 ug/l	4.37E+00 lbs/day
Vinyl chloride	4.24E+04 ug/l	2.83E+01 lbs/day

Pesticides

Aldrin	1.13E-02 ug/l	7.55E-06 lbs/day
Dieldrin	1.13E-02 ug/l	7.55E-06 lbs/day
Chlordane	4.77E-02 ug/l	3.18E-05 lbs/day
4,4'-DDT	4.77E-02 ug/l	3.18E-05 lbs/day
4,4'-DDE	4.77E-02 ug/l	3.18E-05 lbs/day
4,4'-DDD	6.79E-02 ug/l	4.53E-05 lbs/day
alpha-Endosulfan	1.62E+02 ug/l	1.08E-01 lbs/day
beta-Endosulfan	1.62E+02 ug/l	1.08E-01 lbs/day
Endosulfan sulfate	1.62E+02 ug/l	1.08E-01 lbs/day
Endrin	6.55E+01 ug/l	4.37E-02 lbs/day
Endrin aldehyde	6.55E+01 ug/l	4.37E-02 lbs/day
Heptachlor	1.70E-02 ug/l	1.13E-05 lbs/day
Heptachlor epoxide		

PCB's

PCB 1242 (Arochlor 1242)	3.64E-03 ug/l	2.43E-06 lbs/day
PCB-1254 (Arochlor 1254)	3.64E-03 ug/l	2.43E-06 lbs/day
PCB-1221 (Arochlor 1221)	3.64E-03 ug/l	2.43E-06 lbs/day
PCB-1232 (Arochlor 1232)	3.64E-03 ug/l	2.43E-06 lbs/day
PCB-1248 (Arochlor 1248)	3.64E-03 ug/l	2.43E-06 lbs/day
PCB-1260 (Arochlor 1260)	3.64E-03 ug/l	2.43E-06 lbs/day
PCB-1016 (Arochlor 1016)	3.64E-03 ug/l	2.43E-06 lbs/day

Pesticide

Toxaphene	6.06E-02 ug/l	4.04E-05 lbs/day
-----------	---------------	------------------

Metals

Antimony	ug/l	lbs/day
Arsenic	ug/l	lbs/day
Asbestos	ug/l	lbs/day
Beryllium		
Cadmium		
Chromium (III)		
Chromium (VI)		
Copper	ug/l	lbs/day
Cyanide	ug/l	lbs/day
Lead		
Mercury	ug/l	lbs/day
Nickel	ug/l	lbs/day
Selenium		
Silver		
Thallium	ug/l	lbs/day
Zinc		

**Utah Division of Water Quality
Salt Lake City, Utah**

Cyanide	900.2	420.3	
Iron	40866.1		
Lead	8019.7	977.9	
Mercury	12.125	0.970	
Nickel	48594.4	10617	
Selenium	754.9	244.9	
Silver	1024.6	N/A	
Thallium	509.2		
Zinc	12432.6	24561.2	Acute Controls
Boron	60623.95		

Other Effluent Limitations are based upon R317-1.

E. coli 126.0 organisms per 100 ml

X. Antidegradation Considerations

The Utah Antidegradation Policy allows for degradation of existing quality where it is determined that such lowering of water quality is necessary to accommodate important economic or social development in the area in which the waters are protected [R317-2-3]. It has been determined that certain chemical parameters introduced by this discharge will cause an increase of the concentration of said parameters in the receiving waters. Under no conditions will the increase in concentration be allowed to interfere with existing instream water uses.

The antidegradation rules and procedures allow for modification of effluent limits less than those based strictly upon mass balance equations utilizing 100% of the assimilative capacity of the receiving water. Additional factors include considerations for "Blue-ribbon" fisheries, special recreational areas, threatened and endangered species, and drinking water sources.

An Antidegradation Level I Review was conducted on this discharge and its effect on the receiving water. Based upon that review, it has been determined that an Antidegradation Level II Review is not required. Basic renewal, no increase in effluent flow or concentration.

XI. Colorado River Salinity Forum Considerations

Discharges in the Colorado River Basin are required to have their discharge at a TDS loading of less than 1.00 tons/day unless certain exemptions apply. Refer to the Forum's Guidelines for additional information allowing for an exceedence of this value.

XII. Summary Comments

The mathematical modeling and best professional judgement indicate that violations of receiving water beneficial uses with their associated water quality standards, including important down-stream segments, will not occur for the evaluated parameters of concern as discussed above if the effluent limitations indicated above are met.

**Utah Division of Water Quality
Salt Lake City, Utah**

XIII. Notice of UPDES Requirement

This Addendum to the Statement of Basis does not authorize any entity or party to discharge to the waters of the State of Utah. That authority is granted through a UPDES permit issued by the Utah Division of Water Quality. The numbers presented here may be changed as a function of other factors. Dischargers are strongly urged to contact the Permits Section for further information. Permit writers may utilize other information to adjust these limits and/or to determine other limits based upon best available technology and other considerations provided that the values in this wasteload analysis [TMDL] are not compromised. See special provisions in Utah Water Quality Standards for adjustments in the Total Dissolved Solids values based upon background concentration.

XIV. TMDL Requirements

Casper Ice Cream discharges to a segment of the Cub River that is 303(d) listed for total phosphorous (TP). A TP TMDL was completed for the Cub River on December 23, 1997. The TMDL requires a total phosphorous effluent limit of .05 mg/L for Casper Ice Cream.

*Calculation based on limited flow and concentration data

	1/day	1/day	1/day	1/day	1/day	1/day	1/day	1/day
	0.000	0.000	4.000	3.679	0.000	0.000	32.000	28.780
BENTHIC DEMAND (SOD)20 gm/m2/day		BENTHIC DEMAND (SOD)T gm/m2/day						
1.000		0.892						
K1 CBOD {theta}	K2 Reaer. {theta}	K3 NH3 {theta}	K4 Open {theta}	K5 NH3 Loss {theta}	K6 NO2+3 {theta}	K(CI) TRC {theta}	S Benthic {theta}	
1.0	1.0	1.1	1.0	1.0	1.0	1.1	1.1	

Antidegradation Review

An antidegradation review (ADR) was conducted to determine whether the proposed activity complies with the applicable antidegradation requirements for receiving waters that may be affected. The Level I ADR evaluated the criteria of R317-2-3.5(b) and determined that the proposed discharge will not require a Level II Antidegradation Review. The Proposed permit is a simple renewal. No increase in effluent flow or concentration.

Casper's Ice Cream DMR Data											
Casper's Ice Cream	FLOW		PH EFFLUENT		DO DAILY MIN	Phosphorus EFFLUENT MAX	TSS EFFLUENT DAY MAX	BOD EFFLUENT DAY MAX	COD EFFLUENT DAY MAX	THERMAL LOADING	OIL GREASE
	DMR MONTH	30 DAY AVE	DAILY MAX	DAILY MIN							
	gpd	gpd	6.5	9	5.5	0.05	25	25	25	Result	10
2010 Q4	0	0									
2010 Q3	0.005	0.005	8	8	6	0.03	10	0	0	17	0
2010 Q2	0	0									
2010 Q1	0	0									
2009 Q4	0	0									
2009 Q3	0	0									
2009 Q2	0	0									
2009 Q1	0	0									
2008 Q4	0	0									
2008 Q3	0	0									
2008 Q2	0	0									
2008 Q1	0	0									
2007 Q4	0	0									
2007 Q3	0.01	0.01	7.5	8	8	0.08	0	7	3	26	0
2007 Q2	0.0096	0.0096	7.5	7.5	9	0.04	0	0	0	17	0
2007 Q1	0	0									
2006 Q4	0	0									
2006 Q3	0	0									
2006 Q2	0	0									
2006 Q1	0	0									

Casper's Ice Cream State Monitoring Data											
Casper's Ice Cream	FLOW		PH EFFLUENT		DO DAILY MIN	Phosphorus EFFLUENT MAX	TSS EFFLUENT DAY MAX	BOD EFFLUENT DAY MAX	COD EFFLUENT DAY MAX	THERMAL LOADING	OIL GREASE
	DMR MONTH	30 DAY AVE	DAILY MAX	DAILY MIN							
	gpd	gpd	6.5	9	5.5	0.05	25	25	25	Result	10
10/12/06			7.76	7.76	9.54	0.02	4	5			