

Utah Division of Water Quality
Salt Lake City, Utah

WASTELOAD ANALYSIS [WLA]
Addendum: Statement of Basis
SUMMARY

Wasteload Applicable for Non-Irrigation Season (October-March)

Discharging Facility: Western Energy Operating
UPDES No: UT-0021768
Current Flow: 1.50 MGD Design Flow
Design Flow 1.50 MGD

Receiving Water: Union Canal => Ashley Creek
Stream Classification: 2B, 3B, 4

Stream Flows [cfs]: 13.40 Non-irrigation 20th Percentile
Stream TDS Values: 1766.0 Non-irrigation Average

Effluent Limits:		WQ Standard:	
Flow, MGD:	1.50 MGD Design Flow		
BOD, mg/l:	25.0 Non-irrigator	5.0	Indicator
Dissolved Oxygen, mg/l	4.0 Non-irrigator	5.5	30 Day Average
TNH3, Chronic, mg/l:	15.0 Non-irrigator	Varies Function of pH and Temperature	
TDS, mg/l:	1200.0 Non-irrigator	1200.0	

Modeling Parameters:
Acute River Width: 50.0%
Chronic River Width: 100.0%

Level 1 Antidegradation Level Completed: Level II Review not required.

Date: 7/24/2014

Permit Writer: _____
WLA by: Eric M. Williams _____
WQM Sec. Approval: _____
TMDL Sec. Approval: _____

7-24-14

Utah Division of Water Quality
Salt Lake City, Utah

WASTELOAD ANALYSIS [WLA]
Addendum: Statement of Basis

24-Jul-14
4:00 PM

Facilities: Western Energy Operating
Discharging to: Union Canal => Ashley Creek

UPDES No: UT-0021768

I. Introduction

Wasteload analyses are performed to determine point source effluent limitations necessary to maintain designated beneficial uses by evaluating projected effects of discharge concentrations on in-stream water quality. The wasteload analysis also takes into account downstream designated uses [R317-2-8, UAC]. Projected concentrations are compared to numeric water quality standards to determine acceptability. The anti-degradation policy and procedures are also considered. The primary in-stream parameters of concern may include metals (as a function of hardness), total dissolved solids (TDS), total residual chlorine (TRC), un-ionized ammonia (as a function of pH and temperature, measured and evaluated in terms of total ammonia), and dissolved oxygen.

Mathematical water quality modeling is employed to determine stream quality response to point source discharges. Models aid in the effort of anticipating stream quality at future effluent flows at critical environmental conditions (e.g., low stream flow, high temperature, high pH, etc).

The numeric criteria in this wasteload analysis may always be modified by narrative criteria and other conditions determined by staff of the Division of Water Quality.

II. Receiving Water and Stream Classification

Union Canal => Ashley Creek:	2B, 3B, 4
Antidegradation Review:	Level I review completed. Level II review not required.

III. Numeric Stream Standards for Protection of Aquatic Wildlife

Total Ammonia (TNH3)	Varies as a function of Temperature and pH Rebound. See Water Quality Standards
Chronic Total Residual Chlorine (TRC)	0.011 mg/l (4 Day Average) 0.019 mg/l (1 Hour Average)
Chronic Dissolved Oxygen (DO)	5.50 mg/l (30 Day Average) 4.00 mg/l (7Day Average) 3.00 mg/l (1 Day Average)
Maximum Total Dissolved Solids	1200.0 mg/l

**Utah Division of Water Quality
Salt Lake City, Utah**

Acute and Chronic Heavy Metals (Dissolved)

Parameter	4 Day Average (Chronic) Standard		1 Hour Average (Acute) Standard		
	Concentration	Load*	Concentration		Load*
Aluminum	87.00 ug/l**	1.090 lbs/day	750.00	ug/l	9.399 lbs/day
Arsenic	190.00 ug/l	2.381 lbs/day	340.00	ug/l	4.261 lbs/day
Cadmium	0.99 ug/l	0.012 lbs/day	12.62	ug/l	0.158 lbs/day
Chromium III	360.78 ug/l	4.521 lbs/day	7548.22	ug/l	94.592 lbs/day
ChromiumVI	11.00 ug/l	0.138 lbs/day	16.00	ug/l	0.201 lbs/day
Copper	41.56 ug/l	0.521 lbs/day	72.69	ug/l	0.911 lbs/day
Iron			1000.00	ug/l	12.532 lbs/day
Lead	29.46 ug/l	0.369 lbs/day	755.92	ug/l	9.473 lbs/day
Mercury	0.0120 ug/l	0.000 lbs/day	2.40	ug/l	0.030 lbs/day
Nickel	228.93 ug/l	2.869 lbs/day	2059.07	ug/l	25.804 lbs/day
Selenium	4.60 ug/l	0.058 lbs/day	20.00	ug/l	0.251 lbs/day
Silver	N/A ug/l	N/A lbs/day	76.55	ug/l	0.959 lbs/day
Zinc	527.04 ug/l	6.605 lbs/day	527.04	ug/l	6.605 lbs/day

* Allowed below discharge

**Chronic Aluminum standard applies only to waters with a pH < 7.0 and a Hardness < 50 mg/l as CaCO3

Metals Standards Based upon a Hardness of 574.47 mg/l as CaCO3

Organics [Pesticides]

Parameter	4 Day Average (Chronic) Standard		1 Hour Average (Acute) Standard		
	Concentration	Load*	Concentration		Load*
Aldrin			1.500	ug/l	0.019 lbs/day
Chlordane	0.004 ug/l	0.364 lbs/day	1.200	ug/l	0.015 lbs/day
DDT, DDE	0.001 ug/l	0.085 lbs/day	0.550	ug/l	0.007 lbs/day
Dieldrin	0.002 ug/l	0.161 lbs/day	1.250	ug/l	0.016 lbs/day
Endosulfan	0.056 ug/l	4.745 lbs/day	0.110	ug/l	0.001 lbs/day
Endrin	0.002 ug/l	0.195 lbs/day	0.090	ug/l	0.001 lbs/day
Guthion			0.010	ug/l	0.000 lbs/day
Heptachlor	0.004 ug/l	0.322 lbs/day	0.260	ug/l	0.003 lbs/day
Lindane	0.080 ug/l	6.779 lbs/day	1.000	ug/l	0.013 lbs/day
Methoxychlor			0.030	ug/l	0.000 lbs/day
Mirex			0.010	ug/l	0.000 lbs/day
Parathion			0.040	ug/l	0.001 lbs/day
PCB's	0.014 ug/l	1.186 lbs/day	2.000	ug/l	0.025 lbs/day
Pentachlorophenol	13.00 ug/l	1101.535 lbs/day	20.000	ug/l	0.251 lbs/day
Toxephene	0.0002 ug/l	0.017 lbs/day	0.7300	ug/l	0.009 lbs/day

**Utah Division of Water Quality
Salt Lake City, Utah**

IV. Numeric Stream Standards for Protection of Agriculture

	4 Day Average (Chronic) Standard		1 Hour Average (Acute) Standard	
	Concentration	Load*	Concentration	Load*
Arsenic			100.0 ug/l	lbs/day
Boron			750.0 ug/l	lbs/day
Cadmium			10.0 ug/l	0.06 lbs/day
Chromium			100.0 ug/l	lbs/day
Copper			200.0 ug/l	lbs/day
Lead			100.0 ug/l	lbs/day
Selenium			50.0 ug/l	lbs/day
TDS, Summer			1200.0 mg/l	7.52 tons/day

V. Numeric Stream Standards for Protection of Human Health (Class 1C Waters)

	4 Day Average (Chronic) Standard		1 Hour Average (Acute) Standard	
	Concentration	Load*	Concentration	Load*
Metals				
Arsenic			ug/l	lbs/day
Barium			ug/l	lbs/day
Cadmium			ug/l	lbs/day
Chromium			ug/l	lbs/day
Lead			ug/l	lbs/day
Mercury			ug/l	lbs/day
Selenium			ug/l	lbs/day
Silver			ug/l	lbs/day
Fluoride (3)			ug/l	lbs/day
to			ug/l	lbs/day
Nitrates as N			ug/l	lbs/day

Chlorophenoxy Herbicides

2,4-D	ug/l	lbs/day
2,4,5-TP	ug/l	lbs/day
Endrin	ug/l	lbs/day
ocyclohexane (Lindane)	ug/l	lbs/day
Methoxychlor	ug/l	lbs/day
Toxaphene	ug/l	lbs/day

VI. Numeric Stream Standards the Protection of Human Health from Water & Fish Consumption [Toxics]

Toxic Organics	Maximum Conc., ug/l - Acute Standards			
	Class 1C [2 Liters/Day for 70 Kg Person over 70 Yr.]		Class 3A, 3B [6.5 g for 70 Kg Person over 70 Yr.]	
Acenaphthene	ug/l	lbs/day	2700.0 ug/l	228.78 lbs/day
Acrolein	ug/l	lbs/day	780.0 ug/l	66.09 lbs/day
Acrylonitrile	ug/l	lbs/day	0.7 ug/l	0.06 lbs/day
Benzene	ug/l	lbs/day	71.0 ug/l	6.02 lbs/day
Benzidine	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Carbon tetrachloride	ug/l	lbs/day	4.4 ug/l	0.37 lbs/day
Chlorobenzene	ug/l	lbs/day	21000.0 ug/l	1779.40 lbs/day
1,2,4-Trichlorobenzene				
Hexachlorobenzene	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
1,2-Dichloroethane	ug/l	lbs/day	99.0 ug/l	8.39 lbs/day

**Utah Division of Water Quality
Salt Lake City, Utah**

1,1,1-Trichloroethane				
Hexachloroethane	ug/l	lbs/day	8.9 ug/l	0.75 lbs/day
1,1-Dichloroethane				
1,1,2-Trichloroethane	ug/l	lbs/day	42.0 ug/l	3.56 lbs/day
1,1,2,2-Tetrachloroethane	ug/l	lbs/day	11.0 ug/l	0.93 lbs/day
Chloroethane			0.0 ug/l	0.00 lbs/day
Bis(2-chloroethyl) ether	ug/l	lbs/day	1.4 ug/l	0.12 lbs/day
2-Chloroethyl vinyl ether	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
2-Chloronaphthalene	ug/l	lbs/day	4300.0 ug/l	364.35 lbs/day
2,4,6-Trichlorophenol	ug/l	lbs/day	6.5 ug/l	0.55 lbs/day
p-Chloro-m-cresol			0.0 ug/l	0.00 lbs/day
Chloroform (HM)	ug/l	lbs/day	470.0 ug/l	39.82 lbs/day
2-Chlorophenol	ug/l	lbs/day	400.0 ug/l	33.89 lbs/day
1,2-Dichlorobenzene	ug/l	lbs/day	17000.0 ug/l	1440.47 lbs/day
1,3-Dichlorobenzene	ug/l	lbs/day	2600.0 ug/l	220.31 lbs/day
1,4-Dichlorobenzene	ug/l	lbs/day	2600.0 ug/l	220.31 lbs/day
3,3'-Dichlorobenzidine	ug/l	lbs/day	0.1 ug/l	0.01 lbs/day
1,1-Dichloroethylene	ug/l	lbs/day	3.2 ug/l	0.27 lbs/day
1,2-trans-Dichloroethylene	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
2,4-Dichlorophenol	ug/l	lbs/day	790.0 ug/l	66.94 lbs/day
1,2-Dichloropropane	ug/l	lbs/day	39.0 ug/l	3.30 lbs/day
1,3-Dichloropropylene	ug/l	lbs/day	1700.0 ug/l	144.05 lbs/day
2,4-Dimethylphenol	ug/l	lbs/day	2300.0 ug/l	194.89 lbs/day
2,4-Dinitrotoluene	ug/l	lbs/day	9.1 ug/l	0.77 lbs/day
2,6-Dinitrotoluene	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
1,2-Diphenylhydrazine	ug/l	lbs/day	0.5 ug/l	0.05 lbs/day
Ethylbenzene	ug/l	lbs/day	29000.0 ug/l	2457.27 lbs/day
Fluoranthene	ug/l	lbs/day	370.0 ug/l	31.35 lbs/day
4-Chlorophenyl phenyl ether				
4-Bromophenyl phenyl ether				
Bis(2-chloroisopropyl) ether	ug/l	lbs/day	170000.0 ug/l	14404.69 lbs/day
Bis(2-chloroethoxy) methane	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Methylene chloride (HM)	ug/l	lbs/day	1600.0 ug/l	135.57 lbs/day
Methyl chloride (HM)	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Methyl bromide (HM)	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Bromoform (HM)	ug/l	lbs/day	360.0 ug/l	30.50 lbs/day
Dichlorobromomethane	ug/l	lbs/day	22.0 ug/l	1.86 lbs/day
Chlorodibromomethane	ug/l	lbs/day	34.0 ug/l	2.88 lbs/day
Hexachlorobutadiene(c)	ug/l	lbs/day	50.0 ug/l	4.24 lbs/day
Hexachlorocyclopentadiene	ug/l	lbs/day	17000.0 ug/l	1440.47 lbs/day
Isophorone	ug/l	lbs/day	600.0 ug/l	50.84 lbs/day
Naphthalene				
Nitrobenzene	ug/l	lbs/day	1900.0 ug/l	160.99 lbs/day
2-Nitrophenol	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
4-Nitrophenol	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
2,4-Dinitrophenol	ug/l	lbs/day	14000.0 ug/l	1186.27 lbs/day
4,6-Dinitro-o-cresol	ug/l	lbs/day	765.0 ug/l	64.82 lbs/day
N-Nitrosodimethylamine	ug/l	lbs/day	8.1 ug/l	0.69 lbs/day
N-Nitrosodiphenylamine	ug/l	lbs/day	16.0 ug/l	1.36 lbs/day
N-Nitrosodi-n-propylamine	ug/l	lbs/day	1.4 ug/l	0.12 lbs/day
Pentachlorophenol	ug/l	lbs/day	8.2 ug/l	0.69 lbs/day

Utah Division of Water Quality

Salt Lake City, Utah

Phenol	ug/l	lbs/day	4.6E+06 ug/l	3.90E+05 lbs/day
Bis(2-ethylhexyl)phthala	ug/l	lbs/day	5.9 ug/l	0.50 lbs/day
Butyl benzyl phthalate	ug/l	lbs/day	5200.0 ug/l	440.61 lbs/day
Di-n-butyl phthalate	ug/l	lbs/day	12000.0 ug/l	1016.80 lbs/day
Di-n-octyl phthlate				
Diethyl phthalate	ug/l	lbs/day	120000.0 ug/l	10168.02 lbs/day
Dimethyl phthlate	ug/l	lbs/day	2.9E+06 ug/l	2.46E+05 lbs/day
Benzo(a)anthracene (P/	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Benzo(a)pyrene (PAH)	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Benzo(b)fluoranthene (F	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Benzo(k)fluoranthene (F	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Chrysene (PAH)	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Acenaphthylene (PAH)				
Anthracene (PAH)	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Dibenzo(a,h)anthracene	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Indeno(1,2,3-cd)pyrene	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Pyrene (PAH)	ug/l	lbs/day	11000.0 ug/l	932.07 lbs/day
Tetrachloroethylene	ug/l	lbs/day	8.9 ug/l	0.75 lbs/day
Toluene	ug/l	lbs/day	200000 ug/l	16946.70 lbs/day
Trichloroethylene	ug/l	lbs/day	81.0 ug/l	6.86 lbs/day
Vinyl chloride	ug/l	lbs/day	525.0 ug/l	44.49 lbs/day
				lbs/day
				lbs/day
Pesticides				
Aldrin	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Dieldrin	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Chlordane	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
4,4'-DDT	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
4,4'-DDE	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
4,4'-DDD	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
alpha-Endosulfan	ug/l	lbs/day	2.0 ug/l	0.17 lbs/day
beta-Endosulfan	ug/l	lbs/day	2.0 ug/l	0.17 lbs/day
Endosulfan sulfate	ug/l	lbs/day	2.0 ug/l	0.17 lbs/day
Endrin	ug/l	lbs/day	0.8 ug/l	0.07 lbs/day
Endrin aldehyde	ug/l	lbs/day	0.8 ug/l	0.07 lbs/day
Heptachlor	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Heptachlor epoxide				
PCB's				
PCB 1242 (Arochlor 124	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
PCB-1254 (Arochlor 124	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
PCB-1221 (Arochlor 124	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
PCB-1232 (Arochlor 124	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
PCB-1248 (Arochlor 124	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
PCB-1260 (Arochlor 124	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
PCB-1016 (Arochlor 101	ug/l	lbs/day	0.0 ug/l	0.00 lbs/day
Pesticide				
Toxaphene	ug/l		0.0 ug/l	0.00 lbs/day
Dioxin				
Dioxin (2,3,7,8-TCDD)	ug/l	lbs/day		

**Utah Division of Water Quality
Salt Lake City, Utah**

Metals

Antimony	ug/l	lbs/day		
Arsenic	ug/l	lbs/day	4300.00 ug/l	364.35 lbs/day
Asbestos	ug/l	lbs/day		
Beryllium				
Cadmium				
Chromium (III)				
Chromium (VI)				
Copper				
Cyanide	ug/l	lbs/day	2.2E+05 ug/l	18641.37 lbs/day
Lead	ug/l	lbs/day		
Mercury			0.15 ug/l	0.01 lbs/day
Nickel			4600.00 ug/l	389.77 lbs/day
Selenium	ug/l	lbs/day		
Silver	ug/l	lbs/day		
Thallium			6.30 ug/l	0.53 lbs/day
Zinc				

There are additional standards that apply to this receiving water, but were not considered in this modeling/waste load allocation analysis.

VII. Mathematical Modeling of Stream Quality

Model configuration was accomplished utilizing standard modeling procedures. Data points were plotted and coefficients adjusted as required to match observed data as closely as possible.

The modeling approach used in this analysis included one or a combination of the following models.

- (1) The Utah River Model, Utah Division of Water Quality, 1992. Based upon STREAMDO IV (Region VIII) and Supplemental Ammonia Toxicity Models; EPA Region VIII, Sept. 1990 and QUAL2E (EPA, Athens, GA).
- (2) Utah Ammonia/Chlorine Model, Utah Division of Water Quality, 1992.
- (3) AMMTOX Model, University of Colorado, Center of Limnology, and EPA Region 8
- (4) Principles of Surface Water Quality Modeling and Control. Robert V. Thomann, et.al. Harper Collins Publisher, Inc. 1987, pp. 644.

Coefficients used in the model were based, in part, upon the following references:

- (1) Rates, Constants, and Kinetics Formulations in Surface Water Quality Modeling. Environmental Research Laboratory, Office of Research and Development, U.S. Environmental Protection Agency, Athens Georgia. EPA/600/3-85/040 June 1985.

**Utah Division of Water Quality
Salt Lake City, Utah**

(2) Principles of Surface Water Quality Modeling and Control. Robert V. Thomann, et.al.
Harper Collins Publisher, Inc. 1987, pp. 644.

VIII. Modeling Information

The required information for the model may include the following information for both the upstream conditions at low flow and the effluent conditions:

Flow, Q, (cfs or MGD)	D.O. mg/l
Temperature, Deg. C.	Total Residual Chlorine (TRC), mg/l
pH	Total NH3-N, mg/l
BOD5, mg/l	Total Dissolved Solids (TDS), mg/l
Metals, ug/l	Toxic Organics of Concern, ug/l

Other Conditions

In addition to the upstream and effluent conditions, the models require a variety of physical and biological coefficients and other technical information. In the process of actually establishing the permit limits for an effluent, values are used based upon the available data, model calibration, literature values, site visits and best professional judgement.

Model Inputs

The following is upstream and discharge information that was utilized as inputs for the analysis. Dry washes are considered to have an upstream flow equal to the flow of the discharge.

Current Upstream Information

	Stream							
	Critical Low							
	Flow	Temp.	pH	T-NH3	BOD5	DO	TRC	TDS
	cfs	Deg. C		mg/l as N	mg/l	mg/l	mg/l	mg/l
Summer (Irrig. Season)	13.40	3.9	8.1	0.01	0.05	9.89	0.00	1766.0
Fall	13.40	3.9	8.1	0.01	0.05	---	0.00	1766.0
Winter	13.40	3.9	8.1	0.01	0.05	---	0.00	1766.0
Spring	13.40	3.9	8.1	0.01	0.05	---	0.00	1766.0
Dissolved Metals	Al	As	Cd	CrIII	CrVI	Copper	Fe	Pb
All Seasons	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l
	1.59*	0.53*	0.053*	0.53*	2.65*	0.53*	0.83*	0.53*
Dissolved Metals	Hg	Ni	Se	Ag	Zn	Boron		
All Seasons	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l		
	0.0000	0.53*	1.06*	0.1*	0.053*	10.0		* 1/2 MDL

**Utah Division of Water Quality
Salt Lake City, Utah**

Projected Discharge Information

Season	Flow, MGD	Temp.	TDS mg/l	TDS tons/day
non-irrigation	1.50000	19.1	1250.00	7.81718

All model numerical inputs, intermediate calculations, outputs and graphs are available for discussion, inspection and copy at the Division of Water Quality.

IX. Effluent Limitations

Current State water quality standards are required to be met under a variety of conditions including in-stream flows targeted to the 7-day, 10-year low flow (R317-2-9).

Other conditions used in the modeling effort coincide with the environmental conditions expected at low stream flows.

Effluent Limitation for Flow based upon Water Quality Standards

In-stream criteria of downstream segments will be met with an effluent flow maximum value as follows:

Season	Daily Average	
non-irrigation	1.500 MGD	2.321 cfs

Flow Requirement or Loading Requirement

The calculations in this wasteload analysis utilize the maximum effluent discharge flow of 1.5 MGD. If the discharger is allowed to have a flow greater than 1.5 MGD during 7Q10 conditions, and effluent limit concentrations as indicated, then water quality standards will be violated. In order to prevent this from occurring, the permit writers must include the discharge flow limitation as indicated above; or, include loading effluent limits in the permit.

Effluent Limitation for Whole Effluent Toxicity (WET) based upon WET Policy

Effluent Toxicity will not occur in downstream segments if the values below are met.

WET Requirements	LC50 >	115.4% Effluent	[Acute]
	IC25 >	14.8% Effluent	[Chronic]

**Utah Division of Water Quality
Salt Lake City, Utah**

Effluent Limitation for Biological Oxygen Demand (BOD) based upon Water Quality Standards or Regulations

In-stream criteria of downstream segments for Dissolved Oxygen will be met with an effluent BOD limitation as follows:

Season	Concentration	
non-irrigation	25.0 mg/l as BOD5	312.7 lbs/day

Effluent Limitation for Dissolved Oxygen (DO) based upon Water Quality Standards

In-stream criteria of downstream segments for Dissolved Oxygen will be met with an effluent D.O. limitation as follows:

Season	Concentration
non-irrigation	4.00

Effluent Limitation for Total Ammonia based upon Water Quality Standards

In-stream criteria of downstream segments for Total Ammonia will be met with an effluent limitation (expressed as Total Ammonia as N) as follows:

Season	Concentration	Load	
non-irrigation	4 Day Avg. - Chronic	15.0 mg/l as N	188.0 lbs/day
	1 Hour Avg. - Acute	21.8 mg/l as N	273.0 lbs/day

Acute limit calculated with an Acute Zone of Initial Dilution (ZID) to be equal to 50.0%.

**Utah Division of Water Quality
Salt Lake City, Utah**

Effluent Limitation for Total Residual Chlorine based upon Water Quality Standards

In-stream criteria of downstream segments for Total Residual Chlorine will be met with an effluent limitation as follows:

Season	Concentration	Load
non-irrigation 4 Day Avg. - Chronic	0.069 mg/l	0.86 lbs/day
1 Hour Avg. - Acute	0.071 mg/l	0.89 lbs/day

Effluent Limitations for Total Dissolved Solids based upon Water Quality Standards

Season	Concentration	Load
non-irrigation Maximum, Acute	1200.0 mg/l	7.50 tons/day

Ashley Creek is listed on Utah's 303(d) list as impaired for TDS (2010)
No assimilative capacity exists for this pollutant. Effluent limit equals the standard.

Colorado Salinity Forum Limits Determined by Permitting Section

Effluent Limitations for Hydrogen Sulfide (undisassociated) based upon Water Quality Standards

Season	Concentration	Load
non-irrigation Maximum, Acute	7.8 mg/l	0.03 tons/day

Effluent Limitations for Total Recoverable Metals based upon Water Quality Standards

In-stream criteria of downstream segments for Dissolved Metals will be met with an effluent limitation as follows (based upon a hardness of 574.47 mg/l):

	4 Day Average Concentration	Load	1 Hour Average Concentration	Load
Aluminum*	N/A	N/A	2,908.6 ug/l	36.4 lbs/day
Arsenic*	1,282.59 ug/l	10.4 lbs/day	1,319.4 ug/l	16.5 lbs/day
Cadmium	6.24 ug/l	0.1 lbs/day	48.8 ug/l	0.6 lbs/day
Chromium III	2,439.56 ug/l	19.7 lbs/day	29,340.0 ug/l	367.7 lbs/day

**Utah Division of Water Quality
Salt Lake City, Utah**

Chromium VI*	51.57 ug/l	0.4 lbs/day	50.7	ug/l	0.6 lbs/day
Copper	276.93 ug/l	2.2 lbs/day	280.3	ug/l	3.5 lbs/day
Iron*	N/A	N/A	3,883.7	ug/l	48.7 lbs/day
Lead	194.97 ug/l	1.6 lbs/day	2,936.2	ug/l	36.8 lbs/day
Mercury*	0.08 ug/l	0.0 lbs/day	9.3	ug/l	0.1 lbs/day
Nickel	1,546.32 ug/l	12.5 lbs/day	8,002.0	ug/l	100.3 lbs/day
Selenium*	21.98 ug/l	0.2 lbs/day	73.2	ug/l	0.9 lbs/day
Silver	N/A ug/l	N/A lbs/day	297.6	ug/l	3.7 lbs/day
Zinc	3,570.02 ug/l	28.9 lbs/day	2,048.5	ug/l	25.7 lbs/day
Cyanide*	35.23 ug/l	0.3 lbs/day	85.5	ug/l	1.1 lbs/day

*Limits for these metals are based on the dissolved standard.

**Effluent Limitations for Heat/Temperature based upon
Water Quality Standards**

non-irrigation	11.7 Deg. C.	53.0 Deg. F
----------------	--------------	-------------

**Effluent Limitations for Organics [Pesticides]
Based upon Water Quality Standards**

In-stream criteria of downstream segments for Organics [Pesticides] will be met with an effluent limit as follows:

	4 Day Average Concentration	Load	1 Hour Average Concentration		Load
Aldrin			1.5E+00	ug/l	2.91E-02 lbs/day
Chlordane	4.30E-03 ug/l	5.38E-02 lbs/day	1.2E+00	ug/l	2.33E-02 lbs/day
DDT, DDE	1.00E-03 ug/l	1.25E-02 lbs/day	5.5E-01	ug/l	1.07E-02 lbs/day
Dieldrin	1.90E-03 ug/l	2.38E-02 lbs/day	1.3E+00	ug/l	2.42E-02 lbs/day
Endosulfan	5.60E-02 ug/l	7.00E-01 lbs/day	1.1E-01	ug/l	2.13E-03 lbs/day
Endrin	2.30E-03 ug/l	2.88E-02 lbs/day	9.0E-02	ug/l	1.74E-03 lbs/day
Guthion	0.00E+00 ug/l	0.00E+00 lbs/day	1.0E-02	ug/l	1.94E-04 lbs/day
Heptachlor	3.80E-03 ug/l	4.75E-02 lbs/day	2.6E-01	ug/l	5.04E-03 lbs/day
Lindane	8.00E-02 ug/l	1.00E+00 lbs/day	1.0E+00	ug/l	1.94E-02 lbs/day
Methoxychlor	0.00E+00 ug/l	0.00E+00 lbs/day	3.0E-02	ug/l	5.82E-04 lbs/day
Mirex	0.00E+00 ug/l	0.00E+00 lbs/day	1.0E-02	ug/l	1.94E-04 lbs/day
Parathion	0.00E+00 ug/l	0.00E+00 lbs/day	4.0E-02	ug/l	7.75E-04 lbs/day
PCB's	1.40E-02 ug/l	1.75E-01 lbs/day	2.0E+00	ug/l	3.88E-02 lbs/day
Pentachlorophenol	1.30E+01 ug/l	1.63E+02 lbs/day	2.0E+01	ug/l	3.88E-01 lbs/day
Toxephene	2.00E-04 ug/l	2.50E-03 lbs/day	7.3E-01	ug/l	1.42E-02 lbs/day

**Utah Division of Water Quality
Salt Lake City, Utah**

**Effluent Targets for Pollution Indicators
Based upon Water Quality Standards**

In-stream criteria of downstream segments for Pollution Indicators will be met with an effluent limit as follows:

	1 Hour Average	
	Concentration	Loading
Gross Beta (pCi/l)	50.0 pCi/L	
BOD (mg/l)	5.0 mg/l	62.7 lbs/day
Nitrates as N	4.0 mg/l	50.1 lbs/day
Total Phosphorus as P	0.05 mg/l	0.6 lbs/day
Total Suspended Solids	90.0 mg/l	1127.9 lbs/day

Note: Pollution indicator targets are for information purposes only.

**Effluent Limitations for Protection of Human Health [Toxics Rule]
Based upon Water Quality Standards (Most stringent of 1C or 3A & 3B as appropriate.)**

In-stream criteria of downstream segments for Protection of Human Health [Toxics] will be met with an effluent limit as follows:

	Maximum Concentration	
	Concentration	Load
Toxic Organics		
Acenaphthene	1.83E+04 ug/l	2.29E+02 lbs/day
Acrolein	5.28E+03 ug/l	6.61E+01 lbs/day
Acrylonitrile	4.47E+00 ug/l	5.59E-02 lbs/day
Benzene	4.81E+02 ug/l	6.02E+00 lbs/day
Benzidine	ug/l	lbs/day
Carbon tetrachloride	2.98E+01 ug/l	3.73E-01 lbs/day
Chlorobenzene	1.42E+05 ug/l	1.78E+03 lbs/day
1,2,4-Trichlorobenzene		
Hexachlorobenzene	5.22E-03 ug/l	6.52E-05 lbs/day
1,2-Dichloroethane	6.71E+02 ug/l	8.39E+00 lbs/day
1,1,1-Trichloroethane		
Hexachloroethane	6.03E+01 ug/l	7.54E-01 lbs/day
1,1-Dichloroethane		
1,1,2-Trichloroethane	2.85E+02 ug/l	3.56E+00 lbs/day
1,1,2,2-Tetrachloroethane	7.45E+01 ug/l	9.32E-01 lbs/day
Chloroethane		
Bis(2-chloroethyl) ether	9.48E+00 ug/l	1.19E-01 lbs/day
2-Chloroethyl vinyl ether		
2-Chloronaphthalene	2.91E+04 ug/l	3.64E+02 lbs/day
2,4,6-Trichlorophenol	4.40E+01 ug/l	5.51E-01 lbs/day
p-Chloro-m-cresol		
Chloroform (HM)	3.18E+03 ug/l	3.98E+01 lbs/day
2-Chlorophenol	2.71E+03 ug/l	3.39E+01 lbs/day
1,2-Dichlorobenzene	1.15E+05 ug/l	1.44E+03 lbs/day
1,3-Dichlorobenzene	1.76E+04 ug/l	2.20E+02 lbs/day

Utah Division of Water Quality
Salt Lake City, Utah

1,4-Dichlorobenzene	1.76E+04 ug/l	2.20E+02 lbs/day
3,3'-Dichlorobenzidine	5.22E-01 ug/l	6.52E-03 lbs/day
1,1-Dichloroethylene	2.17E+01 ug/l	2.71E-01 lbs/day
1,2-trans-Dichloroethylene1		
2,4-Dichlorophenol	5.35E+03 ug/l	6.69E+01 lbs/day
1,2-Dichloropropane	2.64E+02 ug/l	3.30E+00 lbs/day
1,3-Dichloropropylene	1.15E+04 ug/l	1.44E+02 lbs/day
2,4-Dimethylphenol	1.56E+04 ug/l	1.95E+02 lbs/day
2,4-Dinitrotoluene	6.16E+01 ug/l	7.71E-01 lbs/day
2,6-Dinitrotoluene		
1,2-Diphenylhydrazine	3.66E+00 ug/l	4.58E-02 lbs/day
Ethylbenzene	1.96E+05 ug/l	2.46E+03 lbs/day
Fluoranthene	2.51E+03 ug/l	3.14E+01 lbs/day
4-Chlorophenyl phenyl ether		
4-Bromophenyl phenyl ether		
Bis(2-chloroisopropyl) ether	1.15E+06 ug/l	1.44E+04 lbs/day
Bis(2-chloroethoxy) methane		
Methylene chloride (HM)	1.08E+04 ug/l	1.36E+02 lbs/day
Methyl chloride (HM)		
Methyl bromide (HM)		
Bromoform (HM)	2.44E+03 ug/l	3.05E+01 lbs/day
Dichlorobromomethane(HM)	1.49E+02 ug/l	1.86E+00 lbs/day
Chlorodibromomethane (HM)	2.30E+02 ug/l	2.88E+00 lbs/day
Hexachlorocyclopentadiene	1.15E+05 ug/l	1.44E+03 lbs/day
Isophorone	4.06E+03 ug/l	5.08E+01 lbs/day
Naphthalene		
Nitrobenzene	1.29E+04 ug/l	1.61E+02 lbs/day
2-Nitrophenol		
4-Nitrophenol		
2,4-Dinitrophenol	9.48E+04 ug/l	1.19E+03 lbs/day
4,6-Dinitro-o-cresol	5.18E+03 ug/l	6.48E+01 lbs/day
N-Nitrosodimethylamine	5.49E+01 ug/l	6.86E-01 lbs/day
N-Nitrosodiphenylamine	1.08E+02 ug/l	1.36E+00 lbs/day
N-Nitrosodi-n-propylamine	9.48E+00 ug/l	1.19E-01 lbs/day
Pentachlorophenol	5.56E+01 ug/l	6.95E-01 lbs/day
Phenol	3.12E+07 ug/l	3.90E+05 lbs/day
Bis(2-ethylhexyl)phthalate	4.00E+01 ug/l	5.00E-01 lbs/day
Butyl benzyl phthalate	3.52E+04 ug/l	4.41E+02 lbs/day
Di-n-butyl phthalate	8.13E+04 ug/l	1.02E+03 lbs/day
Di-n-octyl phthlate		
Diethyl phthalate	8.13E+05 ug/l	1.02E+04 lbs/day
Dimethyl phthlate	1.96E+07 ug/l	2.46E+05 lbs/day
Benzo(a)anthracene (PAH)	2.10E-01 ug/l	2.63E-03 lbs/day
Benzo(a)pyrene (PAH)	2.10E-01 ug/l	2.63E-03 lbs/day
Benzo(b)fluoranthene (PAH)	2.10E-01 ug/l	2.63E-03 lbs/day
Benzo(k)fluoranthene (PAH)	2.10E-01 ug/l	2.63E-03 lbs/day
Chrysene (PAH)	2.10E-01 ug/l	2.63E-03 lbs/day
Acenaphthylene (PAH)		
Anthracene (PAH)		
Dibenzo(a,h)anthracene (PAH)	2.10E-01 ug/l	2.63E-03 lbs/day
Indeno(1,2,3-cd)pyrene (PAH)	2.10E-01 ug/l	2.63E-03 lbs/day

**Utah Division of Water Quality
Salt Lake City, Utah**

Pyrene (PAH)	7.45E+04 ug/l	9.32E+02 lbs/day
Tetrachloroethylene	6.03E+01 ug/l	7.54E-01 lbs/day
Toluene	1.35E+06 ug/l	1.69E+04 lbs/day
Trichloroethylene	5.49E+02 ug/l	6.86E+00 lbs/day
Vinyl chloride	3.56E+03 ug/l	4.45E+01 lbs/day

Pesticides

Aldrin	9.48E-04 ug/l	1.19E-05 lbs/day
Dieldrin	9.48E-04 ug/l	1.19E-05 lbs/day
Chlordane	4.00E-03 ug/l	5.00E-05 lbs/day
4,4'-DDT	4.00E-03 ug/l	5.00E-05 lbs/day
4,4'-DDE	4.00E-03 ug/l	5.00E-05 lbs/day
4,4'-DDD	5.69E-03 ug/l	7.12E-05 lbs/day
alpha-Endosulfan	1.35E+01 ug/l	1.69E-01 lbs/day
beta-Endosulfan	1.35E+01 ug/l	1.69E-01 lbs/day
Endosulfan sulfate	1.35E+01 ug/l	1.69E-01 lbs/day
Endrin	5.49E+00 ug/l	6.86E-02 lbs/day
Endrin aldehyde	5.49E+00 ug/l	6.86E-02 lbs/day
Heptachlor	1.42E-03 ug/l	1.78E-05 lbs/day
Heptachlor epoxide		

PCB's

PCB 1242 (Arochlor 1242)	3.05E-04 ug/l	3.81E-06 lbs/day
PCB-1254 (Arochlor 1254)	3.05E-04 ug/l	3.81E-06 lbs/day
PCB-1221 (Arochlor 1221)	3.05E-04 ug/l	3.81E-06 lbs/day
PCB-1232 (Arochlor 1232)	3.05E-04 ug/l	3.81E-06 lbs/day
PCB-1248 (Arochlor 1248)	3.05E-04 ug/l	3.81E-06 lbs/day
PCB-1260 (Arochlor 1260)	3.05E-04 ug/l	3.81E-06 lbs/day
PCB-1016 (Arochlor 1016)	3.05E-04 ug/l	3.81E-06 lbs/day

Pesticide

Toxaphene	5.08E-03 ug/l	6.36E-05 lbs/day
-----------	---------------	------------------

Metals

Antimony	ug/l	lbs/day
Arsenic	ug/l	lbs/day
Asbestos	ug/l	lbs/day
Beryllium		
Cadmium		
Chromium (III)		
Chromium (VI)		
Copper	ug/l	lbs/day
Cyanide	ug/l	lbs/day
Lead		
Mercury	ug/l	lbs/day
Nickel	ug/l	lbs/day
Selenium		
Silver		
Thallium	ug/l	lbs/day
Zinc		

**Utah Division of Water Quality
Salt Lake City, Utah**

Dioxin

Dioxin (2,3,7,8-TCDD) 9.48E-08 ug/l 1.19E-09 lbs/day

**Metals Effluent Limitations for Protection of All Beneficial Uses
Based upon Water Quality Standards and Toxics Rule**

	Class 4 Acute Agricultural ug/l	Class 3 Acute Aquatic Wildlife ug/l	Acute Toxics Drinking Water Source ug/l	Acute Toxics Wildlife ug/l	1C Acute Health Criteria ug/l	Acute Most Stringent ug/l	Class 3 Chronic Aquatic Wildlife ug/l
Aluminum		2908.6				2908.6	N/A
Antimony				29130.9		29130.9	
Arsenic	677.5	1319.4			0.0	677.5	1282.6
Barium						0.0	
Beryllium						0.0	
Cadmium	67.3	48.8			0.0	48.8	6.2
Chromium (III)		29340.0			0.0	29340.0	2439.6
Chromium (VI)	672.9	50.7			0.0	50.72	51.57
Copper	1350.3	280.3				280.3	276.9
Cyanide		85.5	1490415.9			85.5	35.2
Iron		3883.7				3883.7	
Lead	672.9	2936.2			0.0	672.9	195.0
Mercury		9.33		1.02	0.0	1.02	0.081
Nickel		8002.0		31163.2		8002.0	1546.3
Selenium	329.5	73.2			0.0	73.2	22.0
Silver		297.6			0.0	297.6	
Thallium				42.7		42.7	
Zinc		2048.5				2048.5	3570.0
Boron	5081.0					5081.0	

Summary Effluent Limitations for Metals [Wasteload Allocation, TMDL]

[If Acute is more stringent than Chronic, then the Chronic takes on the Acute value.]

	WLA Acute ug/l	WLA Chronic ug/l	
Aluminum	2908.6	N/A	
Antimony	29130.86		
Arsenic	677.5	1282.6	Acute Controls
Asbestos	0.00E+00		
Barium			
Beryllium			
Cadmium	48.8	6.2	
Chromium (III)	29340.0	2440	
Chromium (VI)	50.7	51.6	Acute Controls
Copper	280.3	276.9	

**Utah Division of Water Quality
Salt Lake City, Utah**

Cyanide	85.5	35.2	
Iron	3883.7		
Lead	672.9	195.0	
Mercury	1.016	0.081	
Nickel	8002.0	1546	
Selenium	73.2	22.0	
Silver	297.6	N/A	
Thallium	42.7		
Zinc	2048.5	3570.0	Acute Controls
Boron	5080.96		

Other Effluent Limitations are based upon R317-1.

E. coli 126.0 organisms per 100 ml

X. Antidegradation Considerations

The Utah Antidegradation Policy allows for degradation of existing quality where it is determined that such lowering of water quality is necessary to accommodate important economic or social development in the area in which the waters are protected [R317-2-3]. It has been determined that certain chemical parameters introduced by this discharge will cause an increase of the concentration of said parameters in the receiving waters. Under no conditions will the increase in concentration be allowed to interfere with existing instream water uses.

The antidegradation rules and procedures allow for modification of effluent limits less than those based strictly upon mass balance equations utilizing 100% of the assimilative capacity of the receiving water. Additional factors include considerations for "Blue-ribbon" fisheries, special recreational areas, threatened and endangered species, and drinking water sources.

An Antidegradation Level I Review was conducted on this discharge and its effect on the receiving water. Based upon that review, it has been determined that an Antidegradation Level II Review is not required. Basic renewal, no increase in effluent flow or concentration.

XI. Colorado River Salinity Forum Considerations

Discharges in the Colorado River Basin are required to have their discharge at a TDS loading of less than 1.00 tons/day unless certain exemptions apply. Refer to the Forum's Guidelines for additional information allowing for an exceedence of this value.

XII. Summary Comments

The mathematical modeling and best professional judgement indicate that violations of receiving water beneficial uses with their associated water quality standards, including important down-stream segments, will not occur for the evaluated parameters of concern as discussed above if the effluent limitations indicated above are met.

**Utah Division of Water Quality
Salt Lake City, Utah**

XIII. Notice of UPDES Requirement

This Addendum to the Statement of Basis does not authorize any entity or party to discharge to the waters of the State of Utah. That authority is granted through a UPDES permit issued by the Utah Division of Water Quality. The numbers presented here may be changed as a function of other factors. Dischargers are strongly urged to contact the Permits Section for further information. Permit writers may utilize other information to adjust these limits and/or to determine other limits based upon best available technology and other considerations provided that the values in this wasteload analysis [TMDL] are not compromised. See special provisions in Utah Water Quality Standards for adjustments in the Total Dissolved Solids values based upon background concentration.

Utah Division of Water Quality
Salt Lake City, Utah

Antidegradation Review

An antidegradation review (ADR) was conducted to determine whether the proposed activity complies with the applicable antidegradation requirements for receiving waters that may be affected. The Level I ADR evaluated the criteria of R317-2-3.5(b) and determined that the proposed discharge will not require a Level II Antidegradation Review. The proposed permit is a simple renewal. No increase in effluent flow or concentration.

